

Handloader's Guide

For Smokeless Powders



Shotshell • Rifle • Handgun

Before using any of the loading data contained in this guide,
please be sure to read all of the safety information.



SAFETY INFORMATION

This IMR *Handloader's Guide* presents revised and updated information on the use of IMR powders to reload shotshell, handgun and rifle ammunition. This *Guide* is not intended to be a "how to" manual for reloading, and we strongly recommend that all handloaders carefully read one or more of the reloading manuals which cover the subject in detail. This *Guide* is offered to be used at your own discretion and risk. Since we have no control over the circumstances of use, we assume no liability for the results obtained. And we guarantee only that our powders meet our manufacturing standards.

It is possible that changes in components which could affect ballistic performance could occur without our knowledge. The components used and specified in all our data were those that were commercially available to the handloader at the time our tests were conducted. It is the responsibility of the handloader to check each of his components to insure that they are the same as specified in our data.

Improper modifications and/or alterations can render any type of firearm unsafe. All work should be conducted by the manufacturer or a qualified gunsmith. It is highly recommended that a shooter have his guns checked periodically by a qualified gunsmith to insure that they are in safe operating condition. Treat all guns as being loaded and read and practice all the rules of safe gun handling and shooting.

The future of handloading is dependent upon the safe handling and storage of powder and primers and the safe use of all ammunition. In this regard, read and follow the recommendations of the Sporting Arms and Ammunition Manufacturers' Institute, Inc. as published in "Properties and Storage of Smokeless Powder." A copy of this pamphlet is bound into this *Handloader's Guide*.

SHOTSHELL

The shotshell data section offers a wide selection of target and field loads. There have been a number of changes and modifications in shotshell components which make it increasingly important that the handloader carefully check all of the components being used to insure that they are the same as shown. If you have reason to question any of your components, contact the manufacturer.

Our goal in developing this shotshell data was to offer a selection of "factory duplication" loads, specifying the average velocity and chamber pressure of the rounds tested. However, not all factory loads can be duplicated because the components utilized are not available to the handloader. All of the ballistics data specified were obtained using once-fired cases and components available to the handloaders at the time our tests were performed.

All of the shotshell data presented were developed using **lead** shot. Do not attempt to reload any of the loads listed using **steel** shot. Substituting steel shot in any load developed for lead shot could be very dangerous.

To obtain a reasonable duplication of the ballistic results listed, you must reload exactly as shown. Substitution of components especially primers and/or alteration in powder charge or type of powder could result in extremely dangerous reloads.

Good, uniform, efficient reloads result only from careful reloading procedures. Always check powder and shot weights on a reliable scale, use the exact components specified, seat wads properly and use only cases that are in good condition. Never leave to chance the

powder type and/or weight and the lead shot weight that you are loading in a shell. Inspect all reloaded shells to insure that crimp closely duplicates that of factory loads.

Unfortunately, time and space do not permit publication of loads utilizing all of the many components available. Loading data utilizing IMR powders for wads not listed in this *Guide* may be obtained by contacting the wad manufacturer.

RIFLE

The rifle data section contains data for most of the popular cartridges. The components specified were those that were commercially available to the handloader at the time the tests were performed.

The powder charge weights specified represent loads that developed **Maximum Allowable Chamber Pressures** with the test barrels used and components specified, with the exception of loads that are specified as (C) compressed charges which may represent case capacity rather than maximum chamber pressure. All tests were conducted utilizing commercial barrels in a Universal Receiver.

It is not unusual for reloads assembled with particular components and fired in the individual reloader's gun to give ballistic results (particularly chamber pressures) that vary in either direction from the published data. To compensate for any component and/or gun combination that would tend to yield pressures in excess of the published data, it is recommended that the powder charge be reduced 10% initially. (This reduction in powder charge weight should also be made each time that any of the components in the load are changed.) After firing several loads at the lower powder charge weight—without ANY evidence of excessive chamber pressure—the powder charge weight may then be increased in 0.5 grain increments as accuracy needs and pressure indications permit. The subject of excessive pressure along with illustrations is included in most reloading manuals, and should be read before attempting any reloading.

Always make certain that you use the correct ammunition in your rifle.

This data must be used only with IMR Smokeless Powders. **Never use this data for powders that may have similar numerical designations!**

HANDGUN

The handgun section contains loads for the more popular handgun cartridges utilizing the handloading components commercially available at the time our tests were conducted. We have also included a section of handgun data for the T/C Contender in cartridge and component combinations of particular interest to the metallic silhouette shooter. Test components used are specified and these exact components must be used to achieve a reasonable duplication of the ballistic data shown.

The powder charge weights specified represent loads that developed **Maximum Allowable Chamber Pressures** with the test barrels and components used, with the exception of loads that are specified as (C) compressed charges and therefore may represent case capacity rather than maximum chamber pressure, and loads that duplicate factory velocity. All tests were conducted utilizing commercial barrels in a Universal Receiver.

Always practice all of the principals of SAFE RELOADING and enjoy good shooting.

RELOADING SAFETY

Reloading ammunition is an enjoyable hobby, and can be conducted safely if certain rules are followed:

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. Exercise care and common sense at all times. 2. Don't become distracted when you are handloading. 3. Never load in haste. A careless mistake can be serious. 4. Use equipment as manufacturer recommends.
Never take shortcuts. 5. Store powder in a cool, dry place at all times. 6. Never use a powder unless you are positive of its identity. 7. Never substitute smokeless powder for black powder. 8. Never use IMR powder data for any other powder types with similar numerical designations. 9. Keep powder away from heat and open flames. 10. Never smoke while handling powder. 11. Keep powder out of reach of children. 12. Don't mix powders. 13. Don't keep more powder in an open container than you need. 14. Observe all maximum load warnings in handbooks. 15. Work up all new loads starting 10% below the recommended maximum charge weight. | <ol style="list-style-type: none"> 16. Examine every case before loading to insure it is in good condition. 17. Watch for indications of high pressures in establishing a new load. 18. Never use smokeless powder in firearms designed for black powder. 19. DO NOT use <i>steel shot</i> in any of the shotshell loads listed in this guide. 20. Use of safety glasses while reloading is recommended. 21. Clean up any powder spills immediately. Use dust pan and brush to clean up powder. Dispose of it in accordance with recommended procedures. 22. Make sure powder container is empty before disposing of container. 23. Consult suppliers of components if you have any questions about their use. 24. Check powder charges regularly to insure using proper powder charge weight. 25. Develop a routine for reloading to guard against mistakes. |
|--|---|

NOTE:

- It should be recognized that Auto-Loading Shotguns may not function with some of the Low Chamber Pressure Loads.
- Several Handgun Calibers show Chamber Pressure in PSI.
- If you use Military Brass for certain Center-Fire Calibers the maximum powder charges should be lowered from data shown.
- **We have included a separate section in the Rifle Data Section that provides recommendations for various Calibers and Components showing Chamber Pressures in PSI units versus prior data with CUP units for the Chamber Pressure. There will be additions to this section as the data becomes available.**

TABLE OF CONTENTS

Reloading data for:	Page	Reloading data for:	Page
SHOTSHELL TARGET	4	12 gauge field	35
12 gauge target, 24 gram	4	16 gauge field	42
12 gauge target, 1 oz.	12	20 gauge field	44
12 gauge target, 1 1/8 oz.	18	.410 bore field	46
20 gauge target	28	Table of Abbreviations	46
28 gauge target	31	Powder Table	46
.410 bore target	34	Chilled Shot Table	46
SHOTSHELL FIELD	34	RIFLE - CUP DATA	47
10 gauge field	34	Weatherby Cartridges	52
12 gauge buckshot	35	RIFLE - PSI DATA	52
		HANDGUN	54
		T/C Contender	57
		Powder Selection Guide	59

SHOTSHELL TARGET DATA

12 GAUGE 2¾ INCH 24 GRAM LOADS

						LEAD	MUZZLE	CHAMBER
PRIMER		IMR POWDER		WAD COLUMN		SHOT	VELOCITY	PRESSURE
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION		(FT/SEC)	(PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL						Grams**		
FEDERAL	209A	"HI-SKOR®" 700-X	15.5 *	WIN.	WAA12SL	24	1155	5300
FEDERAL	209A	"HI-SKOR" 700-X	16.5 *	WIN.	WAA12SL	24	1205	5900
FEDERAL	209A	"HI-SKOR" 700-X	17.5 *	WIN.	WAA12SL	24	1255	6600
FEDERAL	209A	"HI-SKOR" 700-X	19.0 *	WIN.	WAA12SL	24	1325	7800
FEDERAL	209A	"HI-SKOR" 700-X	15.5 *	CB.	CB1100-12	24	1145	4800
FEDERAL	209A	"HI-SKOR" 700-X	16.5 *	CB.	CB1100-12	24	1195	5500
FEDERAL	209A	"HI-SKOR" 700-X	17.5 *	CB.	CB1100-12	24	1250	6200
FEDERAL	209A	"HI-SKOR" 700-X	19.5 *	CB.	CB1100-12	24	1335	7400
FEDERAL	209A	"HI-SKOR" 700-X	15.5 *	REM.	TGT12	24	1145	5000
FEDERAL	209A	"HI-SKOR" 700-X	16.5 *	REM.	TGT12	24	1195	5700
FEDERAL	209A	"HI-SKOR" 700-X	17.5 *	REM.	TGT12	24	1245	6200
FEDERAL	209A	"HI-SKOR" 700-X	19.5 *	REM.	TGT12	24	1325	7100
FEDERAL	209A	"HI-SKOR" 700-X	16.0 *	CB.	CB2100-12	24	1160	5300
FEDERAL	209A	"HI-SKOR" 700-X	17.0 *	CB.	CB2100-12	24	1210	6000
FEDERAL	209A	"HI-SKOR" 700-X	18.0 *	CB.	CB2100-12	24	1260	6600
FEDERAL	209A	"HI-SKOR" 700-X	19.5 *	CB.	CB2100-12	24	1330	7500
FEDERAL	209A	"HI-SKOR" 700-X	16.0 *	FED.	12S0	24	1160	5500
FEDERAL	209A	"HI-SKOR" 700-X	17.0 *	FED.	12S0	24	1205	6200
FEDERAL	209A	"HI-SKOR" 700-X	18.0 *	FED.	12S0	24	1255	6800
FEDERAL	209A	"HI-SKOR" 700-X	19.5 *	FED.	12S0	24	1325	7800
FEDERAL	209A	"HI-SKOR" 700-X	15.5 *	ACTIV	TG-30	24	1155	6100
FEDERAL	209A	"HI-SKOR" 700-X	16.5 *	ACTIV	TG-30	24	1200	6700
FEDERAL	209A	"HI-SKOR" 700-X	17.5 *	ACTIV	TG-30	24	1245	7300
FEDERAL	209A	"HI-SKOR" 700-X	19.5 *	ACTIV	TG-30	24	1335	8800
REMINGTON	209P	"HI-SKOR" 700-X	16.0 *	WIN.	WAA12SL	24	1150	4700
REMINGTON	209P	"HI-SKOR" 700-X	17.0 *	WIN.	WAA12SL	24	1205	5400
REMINGTON	209P	"HI-SKOR" 700-X	18.0 *	WIN.	WAA12SL	24	1250	5900
REMINGTON	209P	"HI-SKOR" 700-X	20.5 *	WIN.	WAA12SL	24	1325	6600
REMINGTON	209P	"HI-SKOR" 700-X	16.0 *	CB.	CB1100-12	24	1140	4000
REMINGTON	209P	"HI-SKOR" 700-X	17.5 *	CB.	CB1100-12	24	1205	4600
REMINGTON	209P	"HI-SKOR" 700-X	19.0 *	CB.	CB1100-12	24	1250	5300
REMINGTON	209P	"HI-SKOR" 700-X	21.0 *	CB.	CB1100-12	24	1320	5800
REMINGTON	209P	"HI-SKOR" 700-X	16.0 *	REM.	TGT12	24	1150	4200
REMINGTON	209P	"HI-SKOR" 700-X	17.0 *	REM.	TGT12	24	1195	4800
REMINGTON	209P	"HI-SKOR" 700-X	18.5 *	REM.	TGT12	24	1250	5700
REMINGTON	209P	"HI-SKOR" 700-X	21.0 *	REM.	TGT12	24	1330	6500
REMINGTON	209P	"HI-SKOR" 700-X	16.5 *	CB.	CB2100-12	24	1140	4000
REMINGTON	209P	"HI-SKOR" 700-X	18.0 *	CB.	CB2100-12	24	1195	4500
REMINGTON	209P	"HI-SKOR" 700-X	19.5 *	CB.	CB2100-12	24	1265	5200
REMINGTON	209P	"HI-SKOR" 700-X	21.0 *	CB.	CB2100-12	24	1330	6300
REMINGTON	209P	"HI-SKOR" 700-X	16.5 *	FED.	12S0	24	1160	4800
REMINGTON	209P	"HI-SKOR" 700-X	17.5 *	FED.	12S0	24	1205	5300
REMINGTON	209P	"HI-SKOR" 700-X	18.5 *	FED.	12S0	24	1250	6000
REMINGTON	209P	"HI-SKOR" 700-X	20.5 *	FED.	12S0	24	1340	7300
REMINGTON	209P	"HI-SKOR" 700-X	16.0 *	ACTIV	TG-30	24	1145	4800
REMINGTON	209P	"HI-SKOR" 700-X	17.5 *	ACTIV	TG-30	24	1210	5500
REMINGTON	209P	"HI-SKOR" 700-X	18.5 *	ACTIV	TG-30	24	1250	6100
REMINGTON	209P	"HI-SKOR" 700-X	20.0 *	ACTIV	TG-30	24	1320	7000
WINCHESTER	209	"HI-SKOR" 700-X	15.5 *	WIN.	WAA12SL	24	1150	5100
WINCHESTER	209	"HI-SKOR" 700-X	16.5 *	WIN.	WAA12SL	24	1200	5700
WINCHESTER	209	"HI-SKOR" 700-X	17.5 *	WIN.	WAA12SL	24	1250	6400
WINCHESTER	209	"HI-SKOR" 700-X	19.0 *	WIN.	WAA12SL	24	1320	7500
WINCHESTER	209	"HI-SKOR" 700-X	16.0 *	CB.	CB1100-12	24	1155	4900
WINCHESTER	209	"HI-SKOR" 700-X	17.0 *	CB.	CB1100-12	24	1210	5500
WINCHESTER	209	"HI-SKOR" 700-X	18.0 *	CB.	CB1100-12	24	1260	6200
WINCHESTER	209	"HI-SKOR" 700-X	19.5 *	CB.	CB1100-12	24	1335	7300
WINCHESTER	209	"HI-SKOR" 700-X	15.5 *	REM.	TGT12	24	1150	5200
WINCHESTER	209	"HI-SKOR" 700-X	16.5 *	REM.	TGT12	24	1195	5800
WINCHESTER	209	"HI-SKOR" 700-X	17.5 *	REM.	TGT12	24	1245	6400
WINCHESTER	209	"HI-SKOR" 700-X	19.5 *	REM.	TGT12	24	1335	7800
WINCHESTER	209	"HI-SKOR" 700-X	16.0 *	CB.	CB2100-12	24	1160	5300
WINCHESTER	209	"HI-SKOR" 700-X	17.0 *	CB.	CB2100-12	24	1210	5900
WINCHESTER	209	"HI-SKOR" 700-X	18.0 *	CB.	CB2100-12	24	1260	6500
WINCHESTER	209	"HI-SKOR" 700-X	19.5 *	CB.	CB2100-12	24	1335	7400
WINCHESTER	209	"HI-SKOR" 700-X	15.5 *	FED.	12S0	24	1145	5400
WINCHESTER	209	"HI-SKOR" 700-X	16.5 *	FED.	12S0	24	1195	6100
WINCHESTER	209	"HI-SKOR" 700-X	17.5 *	FED.	12S0	24	1250	6700
WINCHESTER	209	"HI-SKOR" 700-X	19.5 *	FED.	12S0	24	1330	7800
WINCHESTER	209	"HI-SKOR" 700-X	15.5 *	ACTIV	TG-30	24	1145	5600
WINCHESTER	209	"HI-SKOR" 700-X	16.5 *	ACTIV	TG-30	24	1195	6300
WINCHESTER	209	"HI-SKOR" 700-X	17.5 *	ACTIV	TG-30	24	1245	7000
WINCHESTER	209	"HI-SKOR" 700-X	19.5 *	ACTIV	TG-30	24	1335	8400

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL						Grams**		
FEDERAL	209A	PB	20.0*	WIN.	WAA12SL	24	1155	5000
FEDERAL	209A	PB	21.0*	WIN.	WAA12SL	24	1195	5300
FEDERAL	209A	PB	22.5*	WIN.	WAA12SL	24	1250	5900
FEDERAL	209A	PB	24.5*	WIN.	WAA12SL	24	1325	6600
FEDERAL	209A	PB	20.0*	CB.	CB2118-12	24	1150	4900
FEDERAL	209A	PB	21.0*	CB.	CB2118-12	24	1190	5400
FEDERAL	209A	PB	22.5*	CB.	CB2118-12	24	1250	6000
FEDERAL	209A	PB	24.5*	CB.	CB2118-12	24	1330	6900
FEDERAL	209A	PB	20.0*	REM.	TGT12	24	1145	4700
FEDERAL	209A	PB	21.5*	REM.	TGT12	24	1205	5300
FEDERAL	209A	PB	23.0*	REM.	TGT12	24	1265	6000
FEDERAL	209A	PB	24.5*	REM.	TGT12	24	1325	6700
FEDERAL	209A	PB	20.0*	FED.	12S3	24	1155	5200
FEDERAL	209A	PB	21.0*	FED.	12S3	24	1195	5600
FEDERAL	209A	PB	22.5*	FED.	12S3	24	1260	6300
FEDERAL	209A	PB	24.0*	FED.	12S3	24	1320	7000
FEDERAL	209A	PB	20.0*	ACTIV	TG-30	24	1145	5000
FEDERAL	209A	PB	21.5*	ACTIV	TG-30	24	1205	5600
FEDERAL	209A	PB	22.5*	ACTIV	TG-30	24	1250	6100
FEDERAL	209A	PB	24.5*	ACTIV	TG-30	24	1330	7000
REMINGTON	209P	PB	21.0*	WIN.	WAA12SL	24	1140	3900
REMINGTON	209P	PB	22.5*	WIN.	WAA12SL	24	1195	4400
REMINGTON	209P	PB	24.0*	WIN.	WAA12SL	24	1255	5100
REMINGTON	209P	PB	25.5*	WIN.	WAA12SL	24	1320	5700
REMINGTON	209P	PB	21.0*	CB.	CB2118-12	24	1150	4300
REMINGTON	209P	PB	22.5*	CB.	CB2118-12	24	1205	4700
REMINGTON	209P	PB	24.0*	CB.	CB2118-12	24	1265	5300
REMINGTON	209P	PB	25.5*	CB.	CB2118-12	24	1330	6100
REMINGTON	209P	PB	21.0*	REM.	TGT12	24	1145	3900
REMINGTON	209P	PB	22.5*	REM.	TGT12	24	1200	4500
REMINGTON	209P	PB	24.0*	REM.	TGT12	24	1265	5200
REMINGTON	209P	PB	25.5*	REM.	TGT12	24	1330	6000
REMINGTON	209P	PB	21.0*	FED.	12S3	24	1160	4700
REMINGTON	209P	PB	22.0*	FED.	12S3	24	1205	5100
REMINGTON	209P	PB	23.0*	FED.	12S3	24	1250	5600
REMINGTON	209P	PB	25.0*	FED.	12S3	24	1330	6600
REMINGTON	209P	PB	20.0*	ACTIV	TG-30	24	1140	4800
REMINGTON	209P	PB	22.0*	ACTIV	TG-30	24	1205	5300
REMINGTON	209P	PB	23.5*	ACTIV	TG-30	24	1260	5700
REMINGTON	209P	PB	25.0*	ACTIV	TG-30	24	1325	6400
WINCHESTER	209	PB	20.5*	WIN.	WAA12SL	24	1145	4300
WINCHESTER	209	PB	21.5*	WIN.	WAA12SL	24	1190	4800
WINCHESTER	209	PB	23.0*	WIN.	WAA12SL	24	1255	5400
WINCHESTER	209	PB	25.0*	WIN.	WAA12SL	24	1335	6200
WINCHESTER	209	PB	20.5*	CB.	CB2118-12	24	1150	4800
WINCHESTER	209	PB	21.5*	CB.	CB2118-12	24	1195	5300
WINCHESTER	209	PB	23.0*	CB.	CB2118-12	24	1260	6000
WINCHESTER	209	PB	24.5*	CB.	CB2118-12	24	1320	6600
WINCHESTER	209	PB	20.5*	REM.	TGT12	24	1140	4500
WINCHESTER	209	PB	22.0*	REM.	TGT12	24	1200	5000
WINCHESTER	209	PB	23.5*	REM.	TGT12	24	1265	5700
WINCHESTER	209	PB	25.0*	REM.	TGT12	24	1325	6300
WINCHESTER	209	PB	20.5*	FED.	12S3	24	1145	4800
WINCHESTER	209	PB	22.0*	FED.	12S3	24	1205	5600
WINCHESTER	209	PB	23.0*	FED.	12S3	24	1250	6100
WINCHESTER	209	PB	24.5*	FED.	12S3	24	1320	6900
WINCHESTER	209	PB	20.5*	ACTIV	TG-30	24	1160	5100
WINCHESTER	209	PB	21.5*	ACTIV	TG-30	24	1200	5600
WINCHESTER	209	PB	22.5*	ACTIV	TG-30	24	1250	6100
WINCHESTER	209	PB	24.5*	ACTIV	TG-30	24	1325	6900
FEDERAL	209A	SR7625	23.5*	WIN.	WAA12SL	24	1150	3800
FEDERAL	209A	SR7625	24.5*	WIN.	WAA12SL	24	1190	4200
FEDERAL	209A	SR7625	25.5	WIN.	WAA12SL	24	1255	4800
FEDERAL	209A	SR7625	27.0	WIN.	WAA12SL	24	1320	5600
FEDERAL	209A	SR7625	24.0	CB.	CB2100-12	24	1145	3400
FEDERAL	209A	SR7625	25.5	CB.	CB2100-12	24	1205	3900

***INSERT ONE 20 GA 0.135 IN CARD IN BOTTOM OF SHOTCUP **24 GRAM LOADS ARE 370.4 GRAINS, 7/8 OZ. EQUALS 382.8 GRAINS.**
NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL						Grams**		
FEDERAL	209A	SR7625	26.5	CB.	CB2100-12	24	1250	4300
FEDERAL	209A	SR7625	28.5	CB.	CB2100-12	24	1325	5000
FEDERAL	209A	SR7625	24.0	REM.	TGT12	24	1155	3700
FEDERAL	209A	SR7625	25.0	REM.	TGT12	24	1195	4000
FEDERAL	209A	SR7625	26.5	REM.	TGT12	24	1255	4600
FEDERAL	209A	SR7625	28.5	REM.	TGT12	24	1335	5400
FEDERAL	209A	SR7625	23.5	FED.	12S0	24	1145	3800
FEDERAL	209A	SR7625	25.0	FED.	12S0	24	1205	4300
FEDERAL	209A	SR7625	26.5	FED.	12S0	24	1265	4900
FEDERAL	209A	SR7625	28.0	FED.	12S0	24	1320	5400
FEDERAL	209A	SR7625	23.5*	ACTIV	TG-30	24	1155	4100
FEDERAL	209A	SR7625	24.5*	ACTIV	TG-30	24	1200	4600
FEDERAL	209A	SR7625	26.0*	ACTIV	TG-30	24	1260	5300
FEDERAL	209A	SR7625	28.0*	ACTIV	TG-30	24	1335	5900
WINCHESTER	209	SR7625	24.5*	WIN.	WAA12SL	24	1145	3500
WINCHESTER	209	SR7625	25.5	WIN.	WAA12SL	24	1195	3800
WINCHESTER	209	SR7625	27.0	WIN.	WAA12SL	24	1265	4600
WINCHESTER	209	SR7625	28.5	WIN.	WAA12SL	24	1335	5400
WINCHESTER	209	SR7625	25.0	CB.	CB2100-12	24	1155	3300
WINCHESTER	209	SR7625	26.0	CB.	CB2100-12	24	1195	3600
WINCHESTER	209	SR7625	27.5	CB.	CB2100-12	24	1250	4000
WINCHESTER	209	SR7625	29.5	CB.	CB2100-12	24	1322	4600
WINCHESTER	209	SR7625	24.5	REM.	TGT12	24	1150	3500
WINCHESTER	209	SR7625	25.5	REM.	TGT12	24	1195	3700
WINCHESTER	209	SR7625	27.0	REM.	TGT12	24	1250	4200
WINCHESTER	209	SR7625	29.0	REM.	TGT12	24	1330	4900
WINCHESTER	209	SR7625	24.5	FED.	12S0	24	1155	3700
WINCHESTER	209	SR7625	25.5	FED.	12S0	24	1200	4000
WINCHESTER	209	SR7625	27.0	FED.	12S0	24	1255	4500
WINCHESTER	209	SR7625	29.0	FED.	12S0	24	1330	5200
WINCHESTER	209	SR7625	23.5*	ACTIV	TG-30	24	1140	3900
WINCHESTER	209	SR7625	25.0*	ACTIV	TG-30	24	1200	4400
WINCHESTER	209	SR7625	26.5*	ACTIV	TG-30	24	1260	5000
WINCHESTER	209	SR7625	28.0*	ACTIV	TG-30	24	1320	5600
SHELL: REMINGTON PREMIER (RTL)						Grams**		
FEDERAL	209A	"HI-SKOR" 700-X	14.5*	WIN.	WAA12SL	24	1140	6500
FEDERAL	209A	"HI-SKOR" 700-X	15.5*	WIN.	WAA12SL	24	1195	7300
FEDERAL	209A	"HI-SKOR" 700-X	16.5*	WIN.	WAA12SL	24	1245	8200
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	24	1335	10000
FEDERAL	209A	"HI-SKOR" 700-X	15.0*	CB.	CB1100-12	24	1155	5900
FEDERAL	209A	"HI-SKOR" 700-X	16.0*	CB.	CB1100-12	24	1205	6700
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	CB.	CB1100-12	24	1255	7600
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	CB.	CB1100-12	24	1330	8900
FEDERAL	209A	"HI-SKOR" 700-X	15.0*	REM.	TGT12	24	1160	6500
FEDERAL	209A	"HI-SKOR" 700-X	16.0*	REM.	TGT12	24	1210	7400
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	REM.	TGT12	24	1265	8300
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	REM.	TGT12	24	1335	9600
FEDERAL	209A	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1155	6100
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	24	1210	6800
FEDERAL	209A	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	24	1260	7600
FEDERAL	209A	"HI-SKOR" 700-X	18.5	CB.	CB2100-12	24	1325	8600
FEDERAL	209A	"HI-SKOR" 700-X	15.0	FED.	12S0	24	1160	6600
FEDERAL	209A	"HI-SKOR" 700-X	16.0	FED.	12S0	24	1210	7400
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S0	24	1260	8100
FEDERAL	209A	"HI-SKOR" 700-X	18.5	FED.	12S0	24	1325	9200
FEDERAL	209A	"HI-SKOR" 700-X	14.5	ACTIV	TG-30	24	1155	6900
FEDERAL	209A	"HI-SKOR" 700-X	15.5	ACTIV	TG-30	24	1200	7600
FEDERAL	209A	"HI-SKOR" 700-X	16.5	ACTIV	TG-30	24	1250	8300
FEDERAL	209A	"HI-SKOR" 700-X	18.0	ACTIV	TG-30	24	1320	9600
REMINGTON	209P	"HI-SKOR" 700-X	15.0*	WIN.	WAA12SL	24	1155	6400
REMINGTON	209P	"HI-SKOR" 700-X	16.0*	WIN.	WAA12SL	24	1210	7200
REMINGTON	209P	"HI-SKOR" 700-X	17.0*	WIN.	WAA12SL	24	1255	7900
REMINGTON	209P	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	24	1320	8900
REMINGTON	209P	"HI-SKOR" 700-X	15.5*	CB.	CB1100-12	24	1155	5500
REMINGTON	209P	"HI-SKOR" 700-X	16.5*	CB.	CB1100-12	24	1210	6400
REMINGTON	209P	"HI-SKOR" 700-X	17.5*	CB.	CB1100-12	24	1260	7200
REMINGTON	209P	"HI-SKOR" 700-X	19.0*	CB.	CB1100-12	24	1335	8400
REMINGTON	209P	"HI-SKOR" 700-X	15.0*	REM.	TGT12	24	1150	5800
REMINGTON	209P	"HI-SKOR" 700-X	16.0*	REM.	TGT12	24	1200	6600
REMINGTON	209P	"HI-SKOR" 700-X	17.0*	REM.	TGT12	24	1250	7300
REMINGTON	209P	"HI-SKOR" 700-X	19.0*	REM.	TGT12	24	1335	8700
REMINGTON	209P	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1150	5700

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)						Grams**		
REMINGTON	209P	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	24	1200	6600
REMINGTON	209P	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	24	1250	7400
REMINGTON	209P	"HI-SKOR" 700-X	18.5	CB.	CB2100-12	24	1330	8600
REMINGTON	209P	"HI-SKOR" 700-X	15.0	FED.	12S0	24	1150	6100
REMINGTON	209P	"HI-SKOR" 700-X	16.0	FED.	12S0	24	1205	7200
REMINGTON	209P	"HI-SKOR" 700-X	17.0	FED.	12S0	24	1260	8200
REMINGTON	209P	"HI-SKOR" 700-X	18.5	FED.	12S0	24	1340	9800
REMINGTON	209P	"HI-SKOR" 700-X	15.0	ACTIV	TG-30	24	1155	6400
REMINGTON	209P	"HI-SKOR" 700-X	16.0	ACTIV	TG-30	24	1210	7300
REMINGTON	209P	"HI-SKOR" 700-X	17.0	ACTIV	TG-30	24	1260	8200
REMINGTON	209P	"HI-SKOR" 700-X	18.5	ACTIV	TG-30	24	1330	9300
WINCHESTER	209	"HI-SKOR" 700-X	15.0*	WIN.	WAA12SL	24	1160	6700
WINCHESTER	209	"HI-SKOR" 700-X	16.0*	WIN.	WAA12SL	24	1210	7600
WINCHESTER	209	"HI-SKOR" 700-X	17.0*	WIN.	WAA12SL	24	1260	8400
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	24	1335	9700
WINCHESTER	209	"HI-SKOR" 700-X	15.0	CB.	CB1100-12	24	1140	5300
WINCHESTER	209	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	24	1200	6300
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	24	1250	7200
WINCHESTER	209	"HI-SKOR" 700-X	18.5	CB.	CB1100-12	24	1325	8500
WINCHESTER	209	"HI-SKOR" 700-X	15.0*	REM.	TGT12	24	1155	6300
WINCHESTER	209	"HI-SKOR" 700-X	16.0*	REM.	TGT12	24	1205	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0*	REM.	TGT12	24	1260	8000
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	REM.	TGT12	24	1335	9200
WINCHESTER	209	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1145	5700
WINCHESTER	209	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	24	1200	6400
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	24	1255	7200
WINCHESTER	209	"HI-SKOR" 700-X	18.5	CB.	CB2100-12	24	1335	8500
WINCHESTER	209	"HI-SKOR" 700-X	15.0	FED.	12S0	24	1160	6300
WINCHESTER	209	"HI-SKOR" 700-X	16.0	FED.	12S0	24	1215	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0	FED.	12S0	24	1265	8100
WINCHESTER	209	"HI-SKOR" 700-X	18.5	FED.	12S0	24	1335	9400
WINCHESTER	209	"HI-SKOR" 700-X	14.5	ACTIV	TG-30	24	1135	6200
WINCHESTER	209	"HI-SKOR" 700-X	15.5	ACTIV	TG-30	24	1190	7100
WINCHESTER	209	"HI-SKOR" 700-X	17.0	ACTIV	TG-30	24	1265	8500
WINCHESTER	209	"HI-SKOR" 700-X	18.5	ACTIV	TG-30	24	1335	9700
FEDERAL	209A	PB	17.5	WIN.	WAA12SL	24	1155	6400
FEDERAL	209A	PB	18.5	WIN.	WAA12SL	24	1200	7100
FEDERAL	209A	PB	20.0	WIN.	WAA12SL	24	1265	8100
FEDERAL	209A	PB	21.5	WIN.	WAA12SL	24	1330	9000
FEDERAL	209A	PB	18.0	CB.	CB1100-12	24	1140	5100
FEDERAL	209A	PB	19.5	CB.	CB1100-12	24	1205	6100
FEDERAL	209A	PB	20.5	CB.	CB1100-12	24	1250	6800
FEDERAL	209A	PB	22.5	CB.	CB1100-12	24	1330	7800
FEDERAL	209A	PB	18.0	REM.	TGT12	24	1145	5500
FEDERAL	209A	PB	19.5	REM.	TGT12	24	1205	6300
FEDERAL	209A	PB	20.5	REM.	TGT12	24	1250	6700
FEDERAL	209A	PB	22.5	REM.	TGT12	24	1330	7800
FEDERAL	209A	PB	18.0	FED.	12S0	24	1155	6300
FEDERAL	209A	PB	19.0	FED.	12S0	24	1195	6900
FEDERAL	209A	PB	20.5	FED.	12S0	24	1255	7800
FEDERAL	209A	PB	22.0	FED.	12S0	24	1320	8700
FEDERAL	209A	PB	18.5	ACTIV	TG-30	24	1150	5800
FEDERAL	209A	PB	19.5	ACTIV	TG-30	24	1190	6300
FEDERAL	209A	PB	21.0	ACTIV	TG-30	24	1255	7100
FEDERAL	209A	PB	22.5	ACTIV	TG-30	24	1320	8000
REMINGTON	209P	PB	18.5	WIN.	WAA12SL	24	1145	5400
REMINGTON	209P	PB	19.5	WIN.	WAA12SL	24	1195	6200
REMINGTON	209P	PB	21.0	WIN.	WAA12SL	24	1265	7300
REMINGTON	209P	PB	22.5	WIN.	WAA12SL	24	1325	8000
REMINGTON	209P	PB	19.5	CB.	CB1100-12	24	1140	4300
REMINGTON	209P	PB	21.0	CB.	CB1100-12	24	1205	5100
REMINGTON	209P	PB	22.0	CB.	CB1100-12	24	1250	5600
REMINGTON	209P	PB	24.0	CB.	CB1100-12	24	1330	6400
REMINGTON	209P	PB	19.5	REM.	TGT12	24	1155	4800
REMINGTON	209P	PB	20.5	REM.	TGT12	24	1195	5200
REMINGTON	209P	PB	22.0	REM.	TGT12	24	1260	6000

***INSERT ONE 20 GA 0.135 IN CARD IN BOTTOM OF SHOTCUP **24 GRAM LOADS ARE 370.4 GRAINS, 7/8 OZ. EQUALS 382.8 GRAINS.**
NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)						Grams**		
REMINGTON	209P	PB	23.5	REM.	TGT12	24	1325	6900
REMINGTON	209P	PB	19.0	FED.	12S0	24	1145	5300
REMINGTON	209P	PB	20.5	FED.	12S0	24	1210	6300
REMINGTON	209P	PB	21.5	FED.	12S0	24	1255	6800
REMINGTON	209P	PB	23.5	FED.	12S0	24	1335	7700
REMINGTON	209P	PB	19.0	ACTIV	TG-30	24	1140	5200
REMINGTON	209P	PB	20.5	ACTIV	TG-30	24	1210	6000
REMINGTON	209P	PB	21.5	ACTIV	TG-30	24	1255	6500
REMINGTON	209P	PB	23.5	ACTIV	TG-30	24	1335	7500
WINCHESTER	209	PB	18.0	WIN.	WAA12SL	24	1140	5600
WINCHESTER	209	PB	19.5	WIN.	WAA12SL	24	1200	6400
WINCHESTER	209	PB	20.5	WIN.	WAA12SL	24	1245	7000
WINCHESTER	209	PB	22.5	WIN.	WAA12SL	24	1330	8100
WINCHESTER	209	PB	19.0	CB.	CB1100-12	24	1145	4700
WINCHESTER	209	PB	20.5	CB.	CB1100-12	24	1205	5200
WINCHESTER	209	PB	21.5	CB.	CB1100-12	24	1245	5600
WINCHESTER	209	PB	23.5	CB.	CB1100-12	24	1330	6400
WINCHESTER	209	PB	19.0	REM.	TGT12	24	1155	5200
WINCHESTER	209	PB	20.0	REM.	TGT12	24	1200	5700
WINCHESTER	209	PB	21.0	REM.	TGT12	24	1245	6200
WINCHESTER	209	PB	23.0	REM.	TGT12	24	1330	7300
WINCHESTER	209	PB	19.0	FED.	12S0	24	1145	5400
WINCHESTER	209	PB	20.5	FED.	12S0	24	1210	6300
WINCHESTER	209	PB	21.5	FED.	12S0	24	1250	6800
WINCHESTER	209	PB	23.5	FED.	12S0	24	1335	7700
WINCHESTER	209	PB	19.0	ACTIV	TG-30	24	1155	5700
WINCHESTER	209	PB	20.0	ACTIV	TG-30	24	1190	6100
WINCHESTER	209	PB	21.5	ACTIV	TG-30	24	1255	6900
WINCHESTER	209	PB	23.0	ACTIV	TG-30	24	1325	7800
FEDERAL	209A	SR7625	20.5	WIN.	WAA12SL	24	1155	5700
FEDERAL	209A	SR7625	21.5	WIN.	WAA12SL	24	1195	6200
FEDERAL	209A	SR7625	23.0	WIN.	WAA12SL	24	1250	6800
FEDERAL	209A	SR7625	25.0	WIN.	WAA12SL	24	1320	7500
FEDERAL	209A	SR7625	21.5	CB.	CB1100-12	24	1150	4600
FEDERAL	209A	SR7625	23.0	CB.	CB1100-12	24	1210	5100
FEDERAL	209A	SR7625	24.0	CB.	CB1100-12	24	1250	5600
FEDERAL	209A	SR7625	26.0	CB.	CB1100-12	24	1330	6500
FEDERAL	209A	SR7625	22.0*	REM.	FIG8	24	1150	4700
FEDERAL	209A	SR7625	23.0*	REM.	FIG8	24	1195	5200
FEDERAL	209A	SR7625	24.5*	REM.	FIG8	24	1260	6000
FEDERAL	209A	SR7625	26.0*	REM.	FIG8	24	1320	6800
FEDERAL	209A	SR7625	21.5	FED.	12S0	24	1155	5300
FEDERAL	209A	SR7625	22.5	FED.	12S0	24	1200	5700
FEDERAL	209A	SR7625	24.0	FED.	12S0	24	1260	6500
FEDERAL	209A	SR7625	25.0	FED.	12S0	24	1325	7300
FEDERAL	209A	SR7625	21.0	ACTIV	TG-30	24	1140	5100
FEDERAL	209A	SR7625	22.5	ACTIV	TG-30	24	1200	5700
FEDERAL	209A	SR7625	23.5	ACTIV	TG-30	24	1245	6200
FEDERAL	209A	SR7625	25.5	ACTIV	TG-30	24	1325	7200
REMINGTON	209P	SR7625	21.5	WIN.	WAA12SL	24	1155	4800
REMINGTON	209P	SR7625	23.0	WIN.	WAA12SL	24	1205	5300
REMINGTON	209P	SR7625	24.5	WIN.	WAA12SL	24	1255	5800
REMINGTON	209P	SR7625	26.0	WIN.	WAA12SL	24	1325	6800
REMINGTON	209P	SR7625	23.5	CB.	CB1100-12	24	1145	3200
REMINGTON	209P	SR7625	25.0	CB.	CB1100-12	24	1205	3800
REMINGTON	209P	SR7625	26.0	CB.	CB1100-12	24	1250	4400
REMINGTON	209P	SR7625	27.5	CB.	CB1100-12	24	1320	5300
REMINGTON	209P	SR7625	22.0*	REM.	FIG8	24	1140	4200
REMINGTON	209P	SR7625	23.5*	REM.	FIG8	24	1205	4900
REMINGTON	209P	SR7625	24.5*	REM.	FIG8	24	1245	5300
REMINGTON	209P	SR7625	26.5*	REM.	FIG8	24	1325	6200
REMINGTON	209P	SR7625	21.5	FED.	12S0	24	1155	4600
REMINGTON	209P	SR7625	23.0	FED.	12S0	24	1210	5300
REMINGTON	209P	SR7625	24.0	FED.	12S0	24	1250	5800
REMINGTON	209P	SR7625	26.0	FED.	12S0	24	1335	6900
REMINGTON	209P	SR7625	21.5	ACTIV	TG-30	24	1155	4900
REMINGTON	209P	SR7625	23.0	ACTIV	TG-30	24	1210	5200
REMINGTON	209P	SR7625	24.5	ACTIV	TG-30	24	1260	5600
REMINGTON	209P	SR7625	26.0	ACTIV	TG-30	24	1320	6300

***INSERT ONE 20 GA 0.135 IN CARD IN BOTTOM OF SHOTCUP **24 GRAM LOADS ARE 370.4 GRAINS, 7/8 OZ. EQUALS 382.8 GRAINS.**
NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)						Grams**		
WINCHESTER	209	SR7625	21.0	WIN.	WAA12SL	24	1160	5300
WINCHESTER	209	SR7625	22.0	WIN.	WAA12SL	24	1205	5900
WINCHESTER	209	SR7625	23.0	WIN.	WAA12SL	24	1250	6400
WINCHESTER	209	SR7625	24.5	WIN.	WAA12SL	24	1320	7300
WINCHESTER	209	SR7625	23.0	CB.	CB1100-12	24	1145	3800
WINCHESTER	209	SR7625	24.5	CB.	CB1100-12	24	1210	4400
WINCHESTER	209	SR7625	25.5	CB.	CB1100-12	24	1255	4900
WINCHESTER	209	SR7625	27.0	CB.	CB1100-12	24	1325	5700
WINCHESTER	209	SR7625	22.5*	REM.	FIG8	24	1160	4600
WINCHESTER	209	SR7625	23.5*	REM.	FIG8	24	1205	5100
WINCHESTER	209	SR7625	24.5*	REM.	FIG8	24	1245	5600
WINCHESTER	209	SR7625	26.5*	REM.	FIG8	24	1325	6500
WINCHESTER	209	SR7625	22.5	FED.	12S0	24	1160	4800
WINCHESTER	209	SR7625	23.5	FED.	12S0	24	1210	5300
WINCHESTER	209	SR7625	24.5	FED.	12S0	24	1255	6000
WINCHESTER	209	SR7625	26.0	FED.	12S0	24	1325	6900
WINCHESTER	209	SR7625	21.5	ACTIV	TG-30	24	1145	5000
WINCHESTER	209	SR7625	23.0	ACTIV	TG-30	24	1205	5600
WINCHESTER	209	SR7625	24.0	ACTIV	TG-30	24	1250	6100
WINCHESTER	209	SR7625	25.5	ACTIV	TG-30	24	1320	7000
SHELL: WINCHESTER AA						Grams**		
FEDERAL	209A	"HI-SKOR" 700-X	14.5*	WIN.	WAA12SL	24	1145	6400
FEDERAL	209A	"HI-SKOR" 700-X	15.5*	WIN.	WAA12SL	24	1195	7000
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	WIN.	WAA12SL	24	1260	8100
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	24	1320	9100
FEDERAL	209A	"HI-SKOR" 700-X	14.5*	CB.	CB1100-12	24	1140	5700
FEDERAL	209A	"HI-SKOR" 700-X	15.5*	CB.	CB1100-12	24	1190	6400
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	CB.	CB1100-12	24	1260	7400
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	CB.	CB1100-12	24	1325	8300
FEDERAL	209A	"HI-SKOR" 700-X	14.5*	REM.	TGT12	24	1140	6000
FEDERAL	209A	"HI-SKOR" 700-X	16.0*	REM.	TGT12	24	1210	7000
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	REM.	TGT12	24	1255	7800
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	REM.	TGT12	24	1320	8600
FEDERAL	209A	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1160	5900
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	24	1210	6700
FEDERAL	209A	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	24	1260	7500
FEDERAL	209A	"HI-SKOR" 700-X	18.5	CB.	CB2100-12	24	1325	8600
FEDERAL	209A	"HI-SKOR" 700-X	15.0	FED.	12S0	24	1150	6400
FEDERAL	209A	"HI-SKOR" 700-X	16.0	FED.	12S0	24	1200	7100
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S0	24	1250	7900
FEDERAL	209A	"HI-SKOR" 700-X	18.5	FED.	12S0	24	1325	9000
FEDERAL	209A	"HI-SKOR" 700-X	15.0	ACTIV	TG-30	24	1145	6000
FEDERAL	209A	"HI-SKOR" 700-X	16.0	ACTIV	TG-30	24	1205	7100
FEDERAL	209A	"HI-SKOR" 700-X	17.0	ACTIV	TG-30	24	1255	8000
FEDERAL	209A	"HI-SKOR" 700-X	18.5	ACTIV	TG-30	24	1320	9100
REMINGTON	209P	"HI-SKOR" 700-X	15.0*	WIN.	WAA12SL	24	1140	5300
REMINGTON	209P	"HI-SKOR" 700-X	16.5*	WIN.	WAA12SL	24	1200	6000
REMINGTON	209P	"HI-SKOR" 700-X	18.0*	WIN.	WAA12SL	24	1265	6800
REMINGTON	209P	"HI-SKOR" 700-X	19.5*	WIN.	WAA12SL	24	1330	7600
REMINGTON	209P	"HI-SKOR" 700-X	16.0*	CB.	CB1100-12	24	1145	4100
REMINGTON	209P	"HI-SKOR" 700-X	17.5*	CB.	CB1100-12	24	1200	4800
REMINGTON	209P	"HI-SKOR" 700-X	19.0*	CB.	CB1100-12	24	1265	5500
REMINGTON	209P	"HI-SKOR" 700-X	20.5*	CB.	CB1100-12	24	1335	6400
REMINGTON	209P	"HI-SKOR" 700-X	15.5*	REM.	TGT12	24	1150	5000
REMINGTON	209P	"HI-SKOR" 700-X	16.5*	REM.	TGT12	24	1190	5500
REMINGTON	209P	"HI-SKOR" 700-X	18.0*	REM.	TGT12	24	1250	6100
REMINGTON	209P	"HI-SKOR" 700-X	20.5*	REM.	TGT12	24	1325	6800
REMINGTON	209P	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1140	4800
REMINGTON	209P	"HI-SKOR" 700-X	16.5	CB.	CB2100-12	24	1200	5200
REMINGTON	209P	"HI-SKOR" 700-X	18.0	CB.	CB2100-12	24	1255	5600
REMINGTON	209P	"HI-SKOR" 700-X	20.0	CB.	CB2100-12	24	1325	6300
REMINGTON	209P	"HI-SKOR" 700-X	15.0	FED.	12S0	24	1150	5000
REMINGTON	209P	"HI-SKOR" 700-X	16.5	FED.	12S0	24	1190	5600
REMINGTON	209P	"HI-SKOR" 700-X	18.0	FED.	12S0	24	1250	6300
REMINGTON	209P	"HI-SKOR" 700-X	19.5	FED.	12S0	24	1320	7600
REMINGTON	209P	"HI-SKOR" 700-X	15.5	ACTIV	TG-30	24	1145	5400
REMINGTON	209P	"HI-SKOR" 700-X	16.5	ACTIV	TG-30	24	1200	6100
REMINGTON	209P	"HI-SKOR" 700-X	18.0	ACTIV	TG-30	24	1255	6700
REMINGTON	209P	"HI-SKOR" 700-X	20.0	ACTIV	TG-30	24	1330	7500

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: WINCHESTER AA						Grams**		
WINCHESTER	209	"HI-SKOR" 700-X	14.5*	WIN.	WAA12SL	24	1140	6300
WINCHESTER	209	"HI-SKOR" 700-X	15.5*	WIN.	WAA12SL	24	1190	7100
WINCHESTER	209	"HI-SKOR" 700-X	17.0*	WIN.	WAA12SL	24	1260	8200
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	24	1325	9100
WINCHESTER	209	"HI-SKOR" 700-X	14.5*	CB.	CB1100-12	24	1135	5600
WINCHESTER	209	"HI-SKOR" 700-X	15.5*	CB.	CB1100-12	24	1190	6300
WINCHESTER	209	"HI-SKOR" 700-X	17.0*	CB.	CB1100-12	24	1260	7300
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	CB.	CB1100-12	24	1325	8400
WINCHESTER	209	"HI-SKOR" 700-X	14.5*	REM.	TGT12	24	1140	6000
WINCHESTER	209	"HI-SKOR" 700-X	16.0*	REM.	TGT12	24	1205	6900
WINCHESTER	209	"HI-SKOR" 700-X	17.0*	REM.	TGT12	24	1250	7600
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	REM.	TGT12	24	1320	8700
WINCHESTER	209	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	24	1140	5400
WINCHESTER	209	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	24	1195	6400
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	24	1250	7200
WINCHESTER	209	"HI-SKOR" 700-X	18.5	CB.	CB2100-12	24	1320	8600
WINCHESTER	209	"HI-SKOR" 700-X	14.5	FED.	12S0	24	1145	6600
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S0	24	1195	7300
WINCHESTER	209	"HI-SKOR" 700-X	17.0	FED.	12S0	24	1265	8300
WINCHESTER	209	"HI-SKOR" 700-X	18.5	FED.	12S0	24	1325	9300
WINCHESTER	209	"HI-SKOR" 700-X	15.0	ACTIV	TG-30	24	1150	6200
WINCHESTER	209	"HI-SKOR" 700-X	16.0	ACTIV	TG-30	24	1205	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0	ACTIV	TG-30	24	1255	7900
WINCHESTER	209	"HI-SKOR" 700-X	18.5	ACTIV	TG-30	24	1320	8900
FEDERAL	209A	PB	18.0	WIN.	WAA12SL	24	1160	5800
FEDERAL	209A	PB	19.0	WIN.	WAA12SL	24	1195	6200
FEDERAL	209A	PB	20.5	WIN.	WAA12SL	24	1255	6900
FEDERAL	209A	PB	22.5	WIN.	WAA12SL	24	1330	7800
FEDERAL	209A	PB	18.5	CB.	CB1100-12	24	1155	4900
FEDERAL	209A	PB	20.0	CB.	CB1100-12	24	1205	5300
FEDERAL	209A	PB	21.0	CB.	CB1100-12	24	1245	5600
FEDERAL	209A	PB	23.0	CB.	CB1100-12	24	1320	6600
FEDERAL	209A	PB	18.0*	REM.	FIG8	24	1145	5200
FEDERAL	209A	PB	19.5*	REM.	FIG8	24	1200	5800
FEDERAL	209A	PB	21.0*	REM.	FIG8	24	1255	6500
FEDERAL	209A	PB	23.0*	REM.	FIG8	24	1325	7200
FEDERAL	209A	PB	18.5	FED.	12S0	24	1150	5500
FEDERAL	209A	PB	19.5	FED.	12S0	24	1190	6000
FEDERAL	209A	PB	21.0	FED.	12S0	24	1250	6600
FEDERAL	209A	PB	23.0	FED.	12S0	24	1330	7900
FEDERAL	209A	PB	18.5	ACTIV	TG-30	24	1140	5100
FEDERAL	209A	PB	20.0	ACTIV	TG-30	24	1205	6000
FEDERAL	209A	PB	21.0	ACTIV	TG-30	24	1255	6700
FEDERAL	209A	PB	23.0	ACTIV	TG-30	24	1330	7700
REMINGTON	209P	PB	18.5	WIN.	WINAA12SL	24	1140	4800
REMINGTON	209P	PB	20.0	WIN.	WINAA12SL	24	1195	5400
REMINGTON	209P	PB	21.5	WIN.	WINAA12SL	24	1255	6100
REMINGTON	209P	PB	23.5	WIN.	WINAA12SL	24	1335	7200
REMINGTON	209P	PB	19.5	CB.	CB1100-12	24	1155	4200
REMINGTON	209P	PB	20.5	CB.	CB1100-12	24	1195	4500
REMINGTON	209P	PB	22.0	CB.	CB1100-12	24	1250	5000
REMINGTON	209P	PB	24.5	CB.	CB1100-12	24	1330	5700
REMINGTON	209P	PB	19.5*	REM.	FIG8	24	1150	4500
REMINGTON	209P	PB	20.5*	REM.	FIG8	24	1190	5000
REMINGTON	209P	PB	22.0*	REM.	FIG8	24	1255	5800
REMINGTON	209P	PB	23.5*	REM.	FIG8	24	1320	6700
REMINGTON	209P	PB	19.5	FED.	12S0	24	1155	4900
REMINGTON	209P	PB	20.5	FED.	12S0	24	1200	5400
REMINGTON	209P	PB	22.0	FED.	12S0	24	1255	6100
REMINGTON	209P	PB	24.0	FED.	12S0	24	1325	6800
REMINGTON	209P	PB	19.5	ACTIV	TG-30	24	1150	4700
REMINGTON	209P	PB	20.5	ACTIV	TG-30	24	1190	5100
REMINGTON	209P	PB	22.0	ACTIV	TG-30	24	1255	5800
REMINGTON	209P	PB	23.5	ACTIV	TG-30	24	1320	6500
WINCHESTER	209	PB	18.0	WIN.	WAA12SL	24	1145	5500
WINCHESTER	209	PB	19.5	WIN.	WAA12SL	24	1200	6000
WINCHESTER	209	PB	21.0	WIN.	WAA12SL	24	1260	6500
WINCHESTER	209	PB	22.5	WIN.	WAA12SL	24	1325	7500
WINCHESTER	209	PB	19.0	CB.	CB1100-12	24	1155	4500
WINCHESTER	209	PB	20.5	CB.	CB1100-12	24	1205	5000
WINCHESTER	209	PB	22.0	CB.	CB1100-12	24	1260	5600
WINCHESTER	209	PB	23.5	CB.	CB1100-12	24	1325	6300

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 24 GRAM LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA						Grams**		
WINCHESTER	209	PB	19.0*	REM.	FIG8	24	1145	4900
WINCHESTER	209	PB	20.5*	REM.	FIG8	24	1200	5400
WINCHESTER	209	PB	22.0*	REM.	FIG8	24	1255	6100
WINCHESTER	209	PB	23.5*	REM.	FIG8	24	1320	6800
WINCHESTER	209	PB	19.0	FED.	12S0	24	1155	5200
WINCHESTER	209	PB	20.0	FED.	12S0	24	1195	5800
WINCHESTER	209	PB	21.5	FED.	12S0	24	1260	6600
WINCHESTER	209	PB	23.0	FED.	12S0	24	1325	7500
WINCHESTER	209	PB	19.0	ACTIV	TG-30	24	1135	4900
WINCHESTER	209	PB	20.5	ACTIV	TG-30	24	1205	5700
WINCHESTER	209	PB	21.5	ACTIV	TG-30	24	1250	6300
WINCHESTER	209	PB	23.5	ACTIV	TG-30	24	1330	7300
FEDERAL	209A	SR7625	21.0	WIN.	WAA12SL	24	1150	4600
FEDERAL	209A	SR7625	22.5	WIN.	WAA12SL	24	1200	5000
FEDERAL	209A	SR7625	24.0	WIN.	WAA12SL	24	1250	5400
FEDERAL	209A	SR7625	26.0	WIN.	WAA12SL	24	1330	6400
FEDERAL	209A	SR7625	22.5	CB.	CB1100-12	24	1155	3700
FEDERAL	209A	SR7625	23.5	CB.	CB1100-12	24	1195	4000
FEDERAL	209A	SR7625	25.0	CB.	CB1100-12	24	1250	4600
FEDERAL	209A	SR7625	27.0	CB.	CB1100-12	24	1335	5500
FEDERAL	209A	SR7625	22.0*	REM.	FIG8	24	1150	4200
FEDERAL	209A	SR7625	23.0*	REM.	FIG8	24	1195	4700
FEDERAL	209A	SR7625	24.5*	REM.	FIG8	24	1255	5300
FEDERAL	209A	SR7625	26.5*	REM.	FIG8	24	1330	6200
FEDERAL	209A	SR7625	22.0	FED.	12S0	24	1150	4400
FEDERAL	209A	SR7625	23.0	FED.	12S0	24	1195	4800
FEDERAL	209A	SR7625	24.5	FED.	12S0	24	1255	5400
FEDERAL	209A	SR7625	26.0	FED.	12S0	24	1320	6400
FEDERAL	209A	SR7625	21.5	ACTIV	TG-30	24	1145	4200
FEDERAL	209A	SR7625	23.0	ACTIV	TG-30	24	1205	4900
FEDERAL	209A	SR7625	24.0	ACTIV	TG-30	24	1250	5400
FEDERAL	209A	SR7625	26.0	ACTIV	TG-30	24	1325	6400
REMINGTON	209P	SR7625	22.5	WIN.	WAA12SL	24	1150	3700
REMINGTON	209P	SR7625	24.0	WIN.	WAA12SL	24	1210	4400
REMINGTON	209P	SR7625	25.0	WIN.	WAA12SL	24	1250	4800
REMINGTON	209P	SR7625	27.0	WIN.	WAA12SL	24	1320	5500
REMINGTON	209P	SR7625	23.5	CB.	CB1100-12	24	1145	3000
REMINGTON	209P	SR7625	25.0	CB.	CB1100-12	24	1205	3500
REMINGTON	209P	SR7625	26.5	CB.	CB1100-12	24	1265	4100
REMINGTON	209P	SR7625	28.0	CB.	CB1100-12	24	1330	4700
REMINGTON	209P	SR7625	23.0*	REM.	FIG8	24	1150	3700
REMINGTON	209P	SR7625	24.0*	REM.	FIG8	24	1195	4200
REMINGTON	209P	SR7625	25.5*	REM.	FIG8	24	1255	4800
REMINGTON	209P	SR7625	27.5*	REM.	FIG8	24	1335	5700
REMINGTON	209P	SR7625	22.5	FED.	12S0	24	1140	4000
REMINGTON	209P	SR7625	24.0	FED.	12S0	24	1190	4400
REMINGTON	209P	SR7625	25.5	FED.	12S0	24	1250	5200
REMINGTON	209P	SR7625	27.0	FED.	12S0	24	1320	6000
REMINGTON	209P	SR7625	22.5	ACTIV	TG-30	24	1150	3900
REMINGTON	209P	SR7625	23.5	ACTIV	TG-30	24	1195	4400
REMINGTON	209P	SR7625	25.0	ACTIV	TG-30	24	1250	4900
REMINGTON	209P	SR7625	27.5	ACTIV	TG-30	24	1325	5600
WINCHESTER	209	SR7625	22.5	WIN.	WAA12SL	24	1150	4200
WINCHESTER	209	SR7625	23.5	WIN.	WAA12SL	24	1195	4700
WINCHESTER	209	SR7625	25.0	WIN.	WAA12SL	24	1255	5300
WINCHESTER	209	SR7625	27.0	WIN.	WAA12SL	24	1330	6000
WINCHESTER	209	SR7625	23.5	CB.	CB1100-12	24	1150	3500
WINCHESTER	209	SR7625	24.5	CB.	CB1100-12	24	1190	3700
WINCHESTER	209	SR7625	26.0	CB.	CB1100-12	24	1250	4300
WINCHESTER	209	SR7625	28.0	CB.	CB1100-12	24	1330	5000
WINCHESTER	209	SR7625	22.0*	REM.	FIG8	24	1155	4300
WINCHESTER	209	SR7625	23.0*	REM.	FIG8	24	1190	4600
WINCHESTER	209	SR7625	24.5*	REM.	FIG8	24	1245	5100
WINCHESTER	209	SR7625	26.5*	REM.	FIG8	24	1320	5900
WINCHESTER	209	SR7625	22.0	FED.	12S0	24	1140	4100
WINCHESTER	209	SR7625	23.5	FED.	12S0	24	1195	4700
WINCHESTER	209	SR7625	25.0	FED.	12S0	24	1255	5300
WINCHESTER	209	SR7625	27.0	FED.	12S0	24	1335	6200
WINCHESTER	209	SR7625	22.0	ACTIV	TG-30	24	1140	4200
WINCHESTER	209	SR7625	23.5	ACTIV	TG-30	24	1200	4900
WINCHESTER	209	SR7625	25.0	ACTIV	TG-30	24	1255	5500
WINCHESTER	209	SR7625	27.0	ACTIV	TG-30	24	1335	6300

*INSERT ONE 20 GA 0.135 IN CARD IN BOTTOM OF SHOTCUP

** 24 GRAM LOADS ARE 370.4 GRAMS, 7/8 OZ. EQUALS 382.8 GRAMS

12 GAUGE 2¾ INCH 1 OUNCE LOADS

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
FEDERAL	209A	"HI-SKOR" 700-X	15.0*	WIN.	WAA12SL	1	1100	6000
FEDERAL	209A	"HI-SKOR" 700-X	16.0*	WIN.	WAA12SL	1	1150	6900
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	WIN.	WAA12SL	1	1195	7600
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	1	1250	8500
FEDERAL	209A	"HI-SKOR" 700-X	15.0	CB.	CB2100-12	1	1110	6000
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB2100-12	1	1155	6700
FEDERAL	209A	"HI-SKOR" 700-X	17.0	CB.	CB2100-12	1	1200	7300
FEDERAL	209A	"HI-SKOR" 700-X	18.0	CB.	CB2100-12	1	1245	7900
FEDERAL	209A	"HI-SKOR" 700-X	15.0*	REM.	TGT12	1	1100	5900
FEDERAL	209A	"HI-SKOR" 700-X	16.0*	REM.	TGT12	1	1145	6500
FEDERAL	209A	"HI-SKOR" 700-X	17.0*	REM.	TGT12	1	1190	7100
FEDERAL	209A	"HI-SKOR" 700-X	18.5*	REM.	TGT12	1	1255	8100
FEDERAL	209A	"HI-SKOR" 700-X	15.0	FED.	12S0	1	1110	6100
FEDERAL	209A	"HI-SKOR" 700-X	16.0	FED.	12S0	1	1155	6700
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S0	1	1195	7300
FEDERAL	209A	"HI-SKOR" 700-X	18.5	FED.	12S0	1	1250	8200
REMINGTON	209P	"HI-SKOR" 700-X	15.5*	WIN.	WAA12SL	1	1090	5800
REMINGTON	209P	"HI-SKOR" 700-X	16.5*	WIN.	WAA12SL	1	1150	6600
REMINGTON	209P	"HI-SKOR" 700-X	17.5*	WIN.	WAA12SL	1	1195	7300
REMINGTON	209P	"HI-SKOR" 700-X	19.0*	WIN.	WAA12SL	1	1260	8400
REMINGTON	209P	"HI-SKOR" 700-X	15.5	CB.	CB2100-12	1	1095	5300
REMINGTON	209P	"HI-SKOR" 700-X	16.5	CB.	CB2100-12	1	1145	5800
REMINGTON	209P	"HI-SKOR" 700-X	18.0	CB.	CB2100-12	1	1200	6600
REMINGTON	209P	"HI-SKOR" 700-X	19.5	CB.	CB2100-12	1	1255	7400
REMINGTON	209P	"HI-SKOR" 700-X	16.0*	REM.	TGT12	1	1110	5700
REMINGTON	209P	"HI-SKOR" 700-X	17.0*	REM.	TGT12	1	1155	6200
REMINGTON	209P	"HI-SKOR" 700-X	18.0*	REM.	TGT12	1	1195	6600
REMINGTON	209P	"HI-SKOR" 700-X	19.5*	REM.	TGT12	1	1255	7300
REMINGTON	209P	"HI-SKOR" 700-X	15.0	FED.	12S0	1	1110	5700
REMINGTON	209P	"HI-SKOR" 700-X	16.0	FED.	12S0	1	1145	6300
REMINGTON	209P	"HI-SKOR" 700-X	18.0	FED.	12S0	1	1210	7300
REMINGTON	209P	"HI-SKOR" 700-X	19.5	FED.	12S0	1	1250	8000
WINCHESTER	209	"HI-SKOR" 700-X	15.5*	WIN.	WAA12SL	1	1105	6000
WINCHESTER	209	"HI-SKOR" 700-X	16.5*	WIN.	WAA12SL	1	1150	6700
WINCHESTER	209	"HI-SKOR" 700-X	17.5*	WIN.	WAA12SL	1	1200	7600
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	WIN.	WAA12SL	1	1250	8500
WINCHESTER	209	"HI-SKOR" 700-X	15.5	CB.	CB2100-12	1	1110	5700
WINCHESTER	209	"HI-SKOR" 700-X	16.5	CB.	CB2100-12	1	1160	6400
WINCHESTER	209	"HI-SKOR" 700-X	17.5	CB.	CB2100-12	1	1200	7000
WINCHESTER	209	"HI-SKOR" 700-X	19.0	CB.	CB2100-12	1	1260	8100
WINCHESTER	209	"HI-SKOR" 700-X	15.5*	REM.	TGT12	1	1100	5900
WINCHESTER	209	"HI-SKOR" 700-X	16.5*	REM.	TGT12	1	1145	6600
WINCHESTER	209	"HI-SKOR" 700-X	17.5*	REM.	TGT12	1	1195	7200
WINCHESTER	209	"HI-SKOR" 700-X	18.5*	REM.	TGT12	1	1245	7800
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S0	1	1105	5900
WINCHESTER	209	"HI-SKOR" 700-X	16.5	FED.	12S0	1	1155	6700
WINCHESTER	209	"HI-SKOR" 700-X	17.5	FED.	12S0	1	1200	7300
WINCHESTER	209	"HI-SKOR" 700-X	18.5	FED.	12S0	1	1245	7800
FEDERAL	209A	PB	18.0	WIN.	WAA12SL	1	1110	6000
FEDERAL	209A	PB	19.5	WIN.	WAA12SL	1	1155	6600
FEDERAL	209A	PB	21.0	WIN.	WAA12SL	1	1205	7100
FEDERAL	209A	PB	22.5	WIN.	WAA12SL	1	1255	7600
FEDERAL	209A	PB	20.0	CB.	CB1100-12	1	1100	4600
FEDERAL	209A	PB	21.5	CB.	CB1100-12	1	1150	5100
FEDERAL	209A	PB	23.0	CB.	CB1100-12	1	1205	5700
FEDERAL	209A	PB	24.0	CB.	CB1100-12	1	1255	6300
FEDERAL	209A	PB	19.5	REM.	TGT12	1	1105	5100
FEDERAL	209A	PB	20.5	REM.	TGT12	1	1140	5500
FEDERAL	209A	PB	22.0	REM.	TGT12	1	1195	6200
FEDERAL	209A	PB	24.0	REM.	TGT12	1	1260	6800
FEDERAL	209A	PB	19.5	FED.	12S3	1	1105	5400
FEDERAL	209A	PB	20.5	FED.	12S3	1	1145	5900
FEDERAL	209A	PB	22.0	FED.	12S3	1	1210	6700
FEDERAL	209A	PB	23.0	FED.	12S3	1	1260	7100
REMINGTON	209P	PB	20.0	WIN.	WAA12SL	1	1095	4700
REMINGTON	209P	PB	21.5	WIN.	WAA12SL	1	1155	5300
REMINGTON	209P	PB	22.5	WIN.	WAA12SL	1	1195	5800
REMINGTON	209P	PB	24.0	WIN.	WAA12SL	1	1260	6600
REMINGTON	209P	PB	21.0	CB.	CB1100-12	1	1095	3800
REMINGTON	209P	PB	22.0	CB.	CB1100-12	1	1140	4300
REMINGTON	209P	PB	23.5	CB.	CB1100-12	1	1200	5000
REMINGTON	209P	PB	25.0	CB.	CB1100-12	1	1255	5600

*INSERT ONE 20 GA 0.135 IN CARD IN BOTTOM OF SHOTCUP

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
REMINGTON	209P	PB	20.5	REM.	TGT12	1	1090	4300
REMINGTON	209P	PB	22.0	REM.	TGT12	1	1160	5200
REMINGTON	209P	PB	23.0	REM.	TGT12	1	1205	5700
REMINGTON	209P	PB	24.0	REM.	TGT12	1	1250	6300
REMINGTON	209P	PB	20.0	FED.	12S3	1	1105	5200
REMINGTON	209P	PB	21.0	FED.	12S3	1	1150	5700
REMINGTON	209P	PB	22.5	FED.	12S3	1	1210	6600
REMINGTON	209P	PB	23.5	FED.	12S3	1	1250	7200
WINCHESTER	209	PB	19.5	WIN.	WAA12SL	1	1090	4900
WINCHESTER	209	PB	21.0	WIN.	WAA12SL	1	1150	5400
WINCHESTER	209	PB	22.5	WIN.	WAA12SL	1	1205	6000
WINCHESTER	209	PB	24.0	WIN.	WAA12SL	1	1265	6700
WINCHESTER	209	PB	20.5	CB.	CB1100-12	1	1100	4300
WINCHESTER	209	PB	21.5	CB.	CB1100-12	1	1145	4800
WINCHESTER	209	PB	23.0	CB.	CB1100-12	1	1205	5400
WINCHESTER	209	PB	24.5	CB.	CB1100-12	1	1260	6100
WINCHESTER	209	PB	20.0	REM.	TGT12	1	1110	5300
WINCHESTER	209	PB	21.0	REM.	TGT12	1	1155	5900
WINCHESTER	209	PB	22.0	REM.	TGT12	1	1205	6500
WINCHESTER	209	PB	23.5	REM.	TGT12	1	1255	7000
WINCHESTER	209	PB	19.5	FED.	12S3	1	1105	5100
WINCHESTER	209	PB	21.0	FED.	12S3	1	1155	5800
WINCHESTER	209	PB	22.5	FED.	12S3	1	1210	6500
WINCHESTER	209	PB	23.5	FED.	12S3	1	1250	6900
FEDERAL	209A	SR7625	22.5	WIN.	WAA12SL	1	1105	4600
FEDERAL	209A	SR7625	23.5	WIN.	WAA12SL	1	1160	5200
FEDERAL	209A	SR7625	24.5	WIN.	WAA12SL	1	1210	5900
FEDERAL	209A	SR7625	25.5	WIN.	WAA12SL	1	1265	6600
FEDERAL	209A	SR7625	22.5	CB.	CB2100-12	1	1090	4200
FEDERAL	209A	SR7625	23.5	CB.	CB2100-12	1	1140	4700
FEDERAL	209A	SR7625	25.0	CB.	CB2100-12	1	1200	5300
FEDERAL	209A	SR7625	26.0	CB.	CB2100-12	1	1250	5800
FEDERAL	209A	SR7625	22.0	REM.	TGT12	1	1100	4200
FEDERAL	209A	SR7625	23.0	REM.	TGT12	1	1145	4800
FEDERAL	209A	SR7625	24.0	REM.	TGT12	1	1190	5500
FEDERAL	209A	SR7625	25.5	REM.	TGT12	1	1250	6200
FEDERAL	209A	SR7625	22.0	FED.	12S3	1	1090	4500
FEDERAL	209A	SR7625	23.5	FED.	12S3	1	1160	5400
FEDERAL	209A	SR7625	24.5	FED.	12S3	1	1210	6000
FEDERAL	209A	SR7625	25.5	FED.	12S3	1	1255	6600
WINCHESTER	209	SR7625	22.5	WIN.	WAA12SL	1	1105	4600
WINCHESTER	209	SR7625	23.5	WIN.	WAA12SL	1	1150	4900
WINCHESTER	209	SR7625	25.0	WIN.	WAA12SL	1	1210	5300
WINCHESTER	209	SR7625	26.0	WIN.	WAA12SL	1	1250	5600
WINCHESTER	209	SR7625	22.0	CB.	CB2100-12	1	1095	4300
WINCHESTER	209	SR7625	23.5	CB.	CB2100-12	1	1145	4600
WINCHESTER	209	SR7625	25.0	CB.	CB2100-12	1	1195	4900
WINCHESTER	209	SR7625	26.5	CB.	CB2100-12	1	1245	5200
WINCHESTER	209	SR7625	22.5	REM.	TGT12	1	1105	4300
WINCHESTER	209	SR7625	23.5	REM.	TGT12	1	1145	4700
WINCHESTER	209	SR7625	25.0	REM.	TGT12	1	1205	5400
WINCHESTER	209	SR7625	26.0	REM.	TGT12	1	1245	5900
WINCHESTER	209	SR7625	21.5	FED.	12S3	1	1110	4700
WINCHESTER	209	SR7625	22.5	FED.	12S3	1	1150	5200
WINCHESTER	209	SR7625	24.0	FED.	12S3	1	1210	5900
WINCHESTER	209	SR7625	25.5	FED.	12S3	1	1255	6600
SHELL: REMINGTON PREMIER (RTL)								
FEDERAL	209A	"HI-SKOR" 700-X	14.5	WIN.	WAA12SL	1	1105	7700
FEDERAL	209A	"HI-SKOR" 700-X	15.5	WIN.	WAA12SL	1	1150	8600
FEDERAL	209A	"HI-SKOR" 700-X	16.5	WIN.	WAA12SL	1	1200	9500
FEDERAL	209A	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	1	1260	10800
FEDERAL	209A	"HI-SKOR" 700-X	14.5	CB.	CB1100-12	1	1090	6600
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	1	1160	7900
FEDERAL	209A	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	1	1205	8700
FEDERAL	209A	"HI-SKOR" 700-X	18.0	CB.	CB1100-12	1	1250	9600
FEDERAL	209A	"HI-SKOR" 700-X	14.5	REM.	TGT12	1	1100	7200

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
FEDERAL	209A	"HI-SKOR" 700-X	15.5	REM.	TGT12	1	1150	8100
FEDERAL	209A	"HI-SKOR" 700-X	16.5	REM.	TGT12	1	1205	9100
FEDERAL	209A	"HI-SKOR" 700-X	17.5	REM.	TGT12	1	1245	10000
FEDERAL	209A	"HI-SKOR" 700-X	14.5	FED.	12S3	1	1095	8000
FEDERAL	209A	"HI-SKOR" 700-X	15.5	FED.	12S3	1	1140	8900
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S3	1	1210	10300
FEDERAL	209A	"HI-SKOR" 700-X	18.0	FED.	12S3	1	1250	11200
REMINGTON	209P	"HI-SKOR" 700-X	14.5	WIN.	WAA12SL	1	1100	7300
REMINGTON	209P	"HI-SKOR" 700-X	15.5	WIN.	WAA12SL	1	1145	8100
REMINGTON	209P	"HI-SKOR" 700-X	16.5	WIN.	WAA12SL	1	1195	9000
REMINGTON	209P	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	1	1255	10500
REMINGTON	209P	"HI-SKOR" 700-X	15.0	CB.	CB1100-12	1	1105	6500
REMINGTON	209P	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	1	1150	7200
REMINGTON	209P	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	1	1195	8000
REMINGTON	209P	"HI-SKOR" 700-X	18.5	CB.	CB1100-12	1	1260	9400
REMINGTON	209P	"HI-SKOR" 700-X	14.5	REM.	TGT12	1	1090	6600
REMINGTON	209P	"HI-SKOR" 700-X	15.5	REM.	TGT12	1	1140	7500
REMINGTON	209P	"HI-SKOR" 700-X	16.5	REM.	TGT12	1	1190	8400
REMINGTON	209P	"HI-SKOR" 700-X	18.0	REM.	TGT12	1	1250	9500
REMINGTON	209P	"HI-SKOR" 700-X	14.5	FED.	12S3	1	1090	7400
REMINGTON	209P	"HI-SKOR" 700-X	15.5	FED.	12S3	1	1140	8300
REMINGTON	209P	"HI-SKOR" 700-X	17.0	FED.	12S3	1	1205	9700
REMINGTON	209P	"HI-SKOR" 700-X	18.0	FED.	12S3	1	1250	10600
WINCHESTER	209	"HI-SKOR" 700-X	15.0	WIN.	WAA12SL	1	1110	7400
WINCHESTER	209	"HI-SKOR" 700-X	16.0	WIN.	WAA12SL	1	1160	8300
WINCHESTER	209	"HI-SKOR" 700-X	17.0	WIN.	WAA12SL	1	1205	9300
WINCHESTER	209	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	1	1250	10300
WINCHESTER	209	"HI-SKOR" 700-X	15.0	CB.	CB1100-12	1	1095	6300
WINCHESTER	209	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	1	1150	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	1	1195	8200
WINCHESTER	209	"HI-SKOR" 700-X	18.0	CB.	CB1100-12	1	1240	9200
WINCHESTER	209	"HI-SKOR" 700-X	15.0	REM.	TGT12	1	1110	7300
WINCHESTER	209	"HI-SKOR" 700-X	15.5	REM.	TGT12	1	1140	7700
WINCHESTER	209	"HI-SKOR" 700-X	16.5	REM.	TGT12	1	1195	8700
WINCHESTER	209	"HI-SKOR" 700-X	18.0	REM.	TGT12	1	1255	9800
WINCHESTER	209	"HI-SKOR" 700-X	14.5	FED.	12S3	1	1090	7800
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S3	1	1135	8700
WINCHESTER	209	"HI-SKOR" 700-X	17.0	FED.	12S3	1	1210	10100
WINCHESTER	209	"HI-SKOR" 700-X	18.0	FED.	12S3	1	1255	11100
FEDERAL	209A	PB	18.0	WIN.	WAA12SL	1	1115	7000
FEDERAL	209A	PB	19.0	WIN.	WAA12SL	1	1150	7500
FEDERAL	209A	PB	20.5	WIN.	WAA12SL	1	1200	8200
FEDERAL	209A	PB	22.0	WIN.	WAA12SL	1	1255	8900
FEDERAL	209A	PB	18.5	CB.	CB1100-12	1	1095	5700
FEDERAL	209A	PB	20.0	CB.	CB1100-12	1	1155	6600
FEDERAL	209A	PB	21.0	CB.	CB1100-12	1	1195	7200
FEDERAL	209A	PB	22.5	CB.	CB1100-12	1	1255	8000
FEDERAL	209A	PB	18.5	REM.	TGT12	1	1105	6200
FEDERAL	209A	PB	19.5	REM.	TGT12	1	1145	6700
FEDERAL	209A	PB	21.0	REM.	TGT12	1	1200	7400
FEDERAL	209A	PB	22.5	REM.	TGT12	1	1255	8200
FEDERAL	209A	PB	18.0	FED.	12S3	1	1100	6500
FEDERAL	209A	PB	19.0	FED.	12S3	1	1140	7200
FEDERAL	209A	PB	20.5	FED.	12S3	1	1200	8300
FEDERAL	209A	PB	22.0	FED.	12S3	1	1260	9300
REMINGTON	209P	PB	18.0	WIN.	WAA12SL	1	1095	6500
REMINGTON	209P	PB	19.5	WIN.	WAA12SL	1	1150	7200
REMINGTON	209P	PB	20.5	WIN.	WAA12SL	1	1190	7700
REMINGTON	209P	PB	22.5	WIN.	WAA12SL	1	1265	8700
REMINGTON	209P	PB	19.5	CB.	CB1100-12	1	1100	5100
REMINGTON	209P	PB	20.5	CB.	CB1100-12	1	1150	5700
REMINGTON	209P	PB	21.5	CB.	CB1100-12	1	1190	6200
REMINGTON	209P	PB	23.0	CB.	CB1100-12	1	1250	7200
REMINGTON	209P	PB	19.0	REM.	TGT12	1	1110	5700
REMINGTON	209P	PB	20.0	REM.	TGT12	1	1150	6300
REMINGTON	209P	PB	21.5	REM.	TGT12	1	1210	7100
REMINGTON	209P	PB	22.5	REM.	TGT12	1	1250	7600
REMINGTON	209P	PB	18.5	FED.	12S3	1	1095	6100
REMINGTON	209P	PB	20.0	FED.	12S3	1	1155	7100
REMINGTON	209P	PB	21.0	FED.	12S3	1	1200	7800
REMINGTON	209P	PB	22.5	FED.	12S3	1	1260	8500

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
WINCHESTER	209	PB	18.5	WIN.	WAA12	1	1100	5900
WINCHESTER	209	PB	19.5	WIN.	WAA12	1	1140	6500
WINCHESTER	209	PB	21.0	WIN.	WAA12	1	1195	7300
WINCHESTER	209	PB	22.5	WIN.	WAA12	1	1255	8100
WINCHESTER	209	PB	19.5	CB.	CB1100-12	1	1105	5400
WINCHESTER	209	PB	20.5	CB.	CB1100-12	1	1150	5900
WINCHESTER	209	PB	21.5	CB.	CB1100-12	1	1195	6400
WINCHESTER	209	PB	23.0	CB.	CB1100-12	1	1250	7100
WINCHESTER	209	PB	19.0	REM.	TGT12	1	1100	5700
WINCHESTER	209	PB	20.0	REM.	TGT12	1	1145	6300
WINCHESTER	209	PB	21.0	REM.	TGT12	1	1190	6800
WINCHESTER	209	PB	22.5	REM.	TGT12	1	1255	7700
WINCHESTER	209	PB	19.0	FED.	12S3	1	1110	6300
WINCHESTER	209	PB	20.0	FED.	12S3	1	1150	7000
WINCHESTER	209	PB	21.0	FED.	12S3	1	1195	7700
WINCHESTER	209	PB	22.5	FED.	12S3	1	1255	8700
FEDERAL	209A	SR7625	19.0	WIN.	WAA12SL	1	1095	4200
FEDERAL	209A	SR7625	20.5	WIN.	WAA12SL	1	1150	5700
FEDERAL	209A	SR7625	22.0	WIN.	WAA12SL	1	1205	7200
FEDERAL	209A	SR7625	23.5	WIN.	WAA12SL	1	1260	8500
FEDERAL	209A	SR7625	20.5	CB.	CB1100-12	1	1090	5000
FEDERAL	209A	SR7625	22.0	CB.	CB1100-12	1	1150	5900
FEDERAL	209A	SR7625	23.0	CB.	CB1100-12	1	1195	6500
FEDERAL	209A	SR7625	24.5	CB.	CB1100-12	1	1255	7400
FEDERAL	209A	SR7625	20.5	REM.	TGT12	1	1095	5300
FEDERAL	209A	SR7625	22.0	REM.	TGT12	1	1160	6300
FEDERAL	209A	SR7625	23.0	REM.	TGT12	1	1200	6900
FEDERAL	209A	SR7625	24.0	REM.	TGT12	1	1245	7400
FEDERAL	209A	SR7625	20.0	FED.	12S3	1	1095	6100
FEDERAL	209A	SR7625	21.0	FED.	12S3	1	1140	6700
FEDERAL	209A	SR7625	22.5	FED.	12S3	1	1205	7600
FEDERAL	209A	SR7625	23.5	FED.	12S3	1	1250	8300
REMINGTON	209P	SR7625	21.0	WIN.	WAA12SL	1	1100	5800
REMINGTON	209P	SR7625	22.0	WIN.	WAA12SL	1	1150	6200
REMINGTON	209P	SR7625	23.0	WIN.	WAA12SL	1	1195	6800
REMINGTON	209P	SR7625	24.5	WIN.	WAA12SL	1	1260	8100
REMINGTON	209P	SR7625	22.0	CB.	CB1100-12	1	1110	4700
REMINGTON	209P	SR7625	23.0	CB.	CB1100-12	1	1155	5100
REMINGTON	209P	SR7625	24.0	CB.	CB1100-12	1	1200	5500
REMINGTON	209P	SR7625	25.0	CB.	CB1100-12	1	1250	5900
REMINGTON	209P	SR7625	21.5	REM.	TGT12	1	1110	5100
REMINGTON	209P	SR7625	22.5	REM.	TGT12	1	1155	5700
REMINGTON	209P	SR7625	23.5	REM.	TGT12	1	1195	6200
REMINGTON	209P	SR7625	25.0	REM.	TGT12	1	1255	7000
REMINGTON	209P	SR7625	20.0	FED.	12S3	1	1105	6000
REMINGTON	209P	SR7625	21.0	FED.	12S3	1	1140	6300
REMINGTON	209P	SR7625	22.5	FED.	12S3	1	1190	6900
REMINGTON	209P	SR7625	24.0	FED.	12S3	1	1260	7800
WINCHESTER	209	SR7625	20.0	WIN.	WAA12SL	1	1105	5700
WINCHESTER	209	SR7625	21.5	WIN.	WAA12SL	1	1150	6100
WINCHESTER	209	SR7625	23.0	WIN.	WAA12SL	1	1200	6700
WINCHESTER	209	SR7625	24.0	WIN.	WAA12SL	1	1250	7200
WINCHESTER	209	SR7625	21.0	CB.	CB1100-12	1	1090	4600
WINCHESTER	209	SR7625	22.5	CB.	CB1100-12	1	1150	5100
WINCHESTER	209	SR7625	24.0	CB.	CB1100-12	1	1195	5500
WINCHESTER	209	SR7625	25.5	CB.	CB1100-12	1	1250	5900
WINCHESTER	209	SR7625	21.0	REM.	TGT12	1	1105	5300
WINCHESTER	209	SR7625	22.0	REM.	TGT12	1	1145	5700
WINCHESTER	209	SR7625	23.0	REM.	TGT12	1	1190	6300
WINCHESTER	209	SR7625	24.5	REM.	TGT12	1	1260	7100
WINCHESTER	209	SR7625	21.0	FED.	12S3	1	1100	5300
WINCHESTER	209	SR7625	22.0	FED.	12S3	1	1145	6000
WINCHESTER	209	SR7625	23.0	FED.	12S3	1	1195	6800
WINCHESTER	209	SR7625	24.0	FED.	12S3	1	1250	7900

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
FEDERAL	209A	"HI-SKOR" 700-X	15.0	WIN.	WAA12SL	1	1110	7300
FEDERAL	209A	"HI-SKOR" 700X	16.0	WIN.	WAA12SL	1	1155	8000
FEDERAL	209A	"HI-SKOR" 700-X	17.0	WIN.	WAA12SL	1	1195	8700
FEDERAL	209A	"HI-SKOR" 700-X	18.5	WIN.	WAA12SL	1	1255	9700
FEDERAL	209A	"HI-SKOR" 700-X	15.0	CB.	CB1100-12	1	1100	6300
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	1	1145	7000
FEDERAL	209A	"HI-SKOR" 700-X	17.5	CB.	CB1100-12	1	1205	8000
FEDERAL	209A	"HI-SKOR" 700-X	18.5	CB.	CB1100-12	1	1250	8700
FEDERAL	209A	"HI-SKOR" 700-X	15.0	REM.	TGT12	1	1110	6900
FEDERAL	209A	"HI-SKOR" 700-X	16.0	REM.	TGT12	1	1155	7500
FEDERAL	209A	"HI-SKOR" 700-X	17.0	REM.	TGT12	1	1195	8200
FEDERAL	209A	"HI-SKOR" 700-X	18.5	REM.	TGT12	1	1260	9400
FEDERAL	209A	"HI-SKOR" 700-X	14.5	FED.	12S3	1	1090	7900
FEDERAL	209A	"HI-SKOR" 700-X	15.5	FED.	12S3	1	1140	8700
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S3	1	1210	9900
FEDERAL	209A	"HI-SKOR" 700-X	18.0	FED.	12S3	1	1250	10700
REMINGTON	209P	"HI-SKOR" 700-X	15.0	WIN.	WAA12SL	1	1095	6400
REMINGTON	209P	"HI-SKOR" 700-X	16.5	WIN.	WAA12SL	1	1155	7000
REMINGTON	209P	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	1	1210	7600
REMINGTON	209P	"HI-SKOR" 700-X	19.0	WIN.	WAA12SL	1	1245	8000
REMINGTON	209P	"HI-SKOR" 700-X	16.0	CB.	CB1100-12	1	1110	5000
REMINGTON	209P	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	1	1150	5600
REMINGTON	209P	"HI-SKOR" 700-X	18.0	CB.	CB1100-12	1	1190	6100
REMINGTON	209P	"HI-SKOR" 700-X	19.5	CB.	CB1100-12	1	1250	7000
REMINGTON	209P	"HI-SKOR" 700-X	15.5	REM.	TGT12	1	1105	5800
REMINGTON	209P	"HI-SKOR" 700-X	16.5	REM.	TGT12	1	1140	6200
REMINGTON	209P	"HI-SKOR" 700-X	18.0	REM.	TGT12	1	1205	7100
REMINGTON	209P	"HI-SKOR" 700-X	19.0	REM.	TGT12	1	1250	7700
REMINGTON	209P	"HI-SKOR" 700-X	15.0	FED.	12S3	1	1105	7100
REMINGTON	209P	"HI-SKOR" 700-X	16.5	FED.	12S3	1	1160	7900
REMINGTON	209P	"HI-SKOR" 700-X	17.5	FED.	12S3	1	1200	8600
REMINGTON	209P	"HI-SKOR" 700-X	18.5	FED.	12S3	1	1250	9300
WINCHESTER	209	"HI-SKOR" 700-X	14.5	WIN.	WAA12SL	1	1105	7500
WINCHESTER	209	"HI-SKOR" 700-X	15.5	WIN.	WAA12SL	1	1145	8200
WINCHESTER	209	"HI-SKOR" 700-X	16.5	WIN.	WAA12SL	1	1195	9000
WINCHESTER	209	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	1	1250	10100
WINCHESTER	209	"HI-SKOR" 700-X	14.5	CB.	CB1100-12	1	1090	6500
WINCHESTER	209	"HI-SKOR" 700-X	15.5	CB.	CB1100-12	1	1140	7400
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB1100-12	1	1205	8500
WINCHESTER	209	"HI-SKOR" 700-X	18.0	CB.	CB1100-12	1	1245	9300
WINCHESTER	209	"HI-SKOR" 700-X	14.5	REM.	TGT12	1	1095	6700
WINCHESTER	209	"HI-SKOR" 700-X	15.5	REM.	TGT12	1	1140	7400
WINCHESTER	209	"HI-SKOR" 700-X	16.5	REM.	TGT12	1	1190	8200
WINCHESTER	209	"HI-SKOR" 700-X	18.0	REM.	TGT12	1	1250	9400
WINCHESTER	209	"HI-SKOR" 700-X	14.5	FED.	12S3	1	1100	8200
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S3	1	1140	8800
WINCHESTER	209	"HI-SKOR" 700-X	17.0	FED.	12S3	1	1205	9700
WINCHESTER	209	"HI-SKOR" 700-X	18.0	FED.	12S3	1	1250	10500
FEDERAL	209A	PB	18.5	WIN.	WAA12	1	1110	6200
FEDERAL	209A	PB	19.5	WIN.	WAA12	1	1150	6900
FEDERAL	209A	PB	21.0	WIN.	WAA12	1	1210	7900
FEDERAL	209A	PB	22.5	WIN.	WAA12	1	1260	8600
FEDERAL	209A	PB	18.5	CB.	CB1100-12	1	1095	5200
FEDERAL	209A	PB	20.0	CB.	CB1100-12	1	1145	5800
FEDERAL	209A	PB	21.5	CB.	CB1100-12	1	1200	6400
FEDERAL	209A	PB	23.0	CB.	CB1100-12	1	1260	7200
FEDERAL	209A	PB	18.5	REM.	FIG8	1	1095	5300
FEDERAL	209A	PB	20.0	REM.	FIG8	1	1150	6100
FEDERAL	209A	PB	21.0	REM.	FIG8	1	1190	6600
FEDERAL	209A	PB	22.5	REM.	FIG8	1	1250	7400
FEDERAL	209A	PB	18.0	FED.	12S3	1	1095	6100
FEDERAL	209A	PB	19.5	FED.	12S3	1	1155	7200
FEDERAL	209A	PB	20.5	FED.	12S3	1	1195	7900
FEDERAL	209A	PB	22.0	FED.	12S3	1	1255	8900
REMINGTON	209P	PB	19.0	WIN.	WAA12	1	1110	5700
REMINGTON	209P	PB	20.0	WIN.	WAA12	1	1145	6200
REMINGTON	209P	PB	21.5	WIN.	WAA12	1	1205	7100
REMINGTON	209P	PB	22.5	WIN.	WAA12	1	1250	7700
REMINGTON	209P	PB	19.0	CB.	CB1100-12	1	1100	4600
REMINGTON	209P	PB	20.5	CB.	CB1100-12	1	1150	5100
REMINGTON	209P	PB	22.0	CB.	CB1100-12	1	1200	5700
REMINGTON	209P	PB	23.5	CB.	CB1100-12	1	1260	6500

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
REMINGTON	209P	PB	19.0	REM.	FIG8	1	1085	4500
REMINGTON	209P	PB	21.0	REM.	FIG8	1	1150	5300
REMINGTON	209P	PB	22.0	REM.	FIG8	1	1190	5700
REMINGTON	209P	PB	23.5	REM.	FIG8	1	1255	6700
REMINGTON	209P	PB	19.0	FED.	12S3	1	1095	5100
REMINGTON	209P	PB	20.5	FED.	12S3	1	1150	6000
REMINGTON	209P	PB	22.0	FED.	12S3	1	1205	6900
REMINGTON	209P	PB	23.5	FED.	12S3	1	1260	7600
WINCHESTER	209	PB	18.5	WIN.	WAA12	1	1105	5900
WINCHESTER	209	PB	20.0	WIN.	WAA12	1	1150	6500
WINCHESTER	209	PB	21.5	WIN.	WAA12	1	1200	7100
WINCHESTER	209	PB	23.0	WIN.	WAA12	1	1260	7900
WINCHESTER	209	PB	19.0	CB.	CB1100-12	1	1110	5100
WINCHESTER	209	PB	20.5	CB.	CB1100-12	1	1140	5600
WINCHESTER	209	PB	22.0	CB.	CB1100-12	1	1190	6100
WINCHESTER	209	PB	23.5	CB.	CB1100-12	1	1255	6600
WINCHESTER	209	PB	18.0	REM.	TGT12	1	1095	4800
WINCHESTER	209	PB	19.5	REM.	TGT12	1	1140	5600
WINCHESTER	209	PB	21.5	REM.	TGT12	1	1200	6700
WINCHESTER	209	PB	23.0	REM.	TGT12	1	1260	7500
WINCHESTER	209	PB	19.0	REM.	FIG8	1	1100	5400
WINCHESTER	209	PB	20.0	REM.	FIG8	1	1140	5800
WINCHESTER	209	PB	21.5	REM.	FIG8	1	1195	6500
WINCHESTER	209	PB	23.0	REM.	FIG8	1	1255	7200
WINCHESTER	209	PB	19.0	FED.	12S3	1	1105	5900
WINCHESTER	209	PB	20.5	FED.	12S3	1	1160	6800
WINCHESTER	209	PB	21.5	FED.	12S3	1	1200	7400
WINCHESTER	209	PB	23.0	FED.	12S3	1	1250	8100
FEDERAL	209A	SR7625	20.0	WIN.	WAA12	1	1095	6000
FEDERAL	209A	SR7625	21.5	WIN.	WAA12	1	1145	6300
FEDERAL	209A	SR7625	23.5	WIN.	WAA12	1	1205	6900
FEDERAL	209A	SR7625	25.0	WIN.	WAA12	1	1260	7400
FEDERAL	209A	SR7625	21.0	CB.	CB1118-12	1	1100	4600
FEDERAL	209A	SR7625	22.0	CB.	CB1118-12	1	1145	5200
FEDERAL	209A	SR7625	23.5	CB.	CB1118-12	1	1210	6200
FEDERAL	209A	SR7625	24.5	CB.	CB1118-12	1	1250	6700
FEDERAL	209A	SR7625	21.5	REM.	RXP12	1	1110	5000
FEDERAL	209A	SR7625	22.5	REM.	RXP12	1	1150	5400
FEDERAL	209A	SR7625	23.5	REM.	RXP12	1	1190	5900
FEDERAL	209A	SR7625	25.0	REM.	RXP12	1	1250	6700
FEDERAL	209A	SR7625	20.5	FED.	12S3	1	1110	5400
FEDERAL	209A	SR7625	21.5	FED.	12S3	1	1145	5900
FEDERAL	209A	SR7625	23.0	FED.	12S3	1	1200	6600
FEDERAL	209A	SR7625	24.5	FED.	12S3	1	1255	7300
REMINGTON	209P	SR7625	21.5	WIN.	WAA12	1	1105	5000
REMINGTON	209P	SR7625	22.5	WIN.	WAA12	1	1150	5700
REMINGTON	209P	SR7625	23.5	WIN.	WAA12	1	1195	6200
REMINGTON	209P	SR7625	25.0	WIN.	WAA12	1	1255	7100
REMINGTON	209P	SR7625	22.5	CB.	CB1118-12	1	1110	4400
REMINGTON	209P	SR7625	23.5	CB.	CB1118-12	1	1145	4700
REMINGTON	209P	SR7625	24.5	CB.	CB1118-12	1	1190	5300
REMINGTON	209P	SR7625	26.0	CB.	CB1118-12	1	1265	6300
REMINGTON	209P	SR7625	22.5	REM.	RXP12	1	1100	4200
REMINGTON	209P	SR7625	23.5	REM.	RXP12	1	1145	4700
REMINGTON	209P	SR7625	24.5	REM.	RXP12	1	1190	5200
REMINGTON	209P	SR7625	25.5	REM.	RXP12	1	1245	6000
REMINGTON	209P	SR7625	22.0	FED.	12S3	1	1095	4500
REMINGTON	209P	SR7625	23.5	FED.	12S3	1	1160	5300
REMINGTON	209P	SR7625	24.5	FED.	12S3	1	1210	6000
REMINGTON	209P	SR7625	25.5	FED.	12S3	1	1265	6900
WINCHESTER	209	SR7625	21.5	WIN.	WAA12	1	1095	4900
WINCHESTER	209	SR7625	23.0	WIN.	WAA12	1	1150	5500
WINCHESTER	209	SR7625	24.0	WIN.	WAA12	1	1190	5800
WINCHESTER	209	SR7625	25.5	WIN.	WAA12	1	1255	6600
WINCHESTER	209	SR7625	22.0	CB.	CB1118-12	1	1095	4500
WINCHESTER	209	SR7625	23.5	CB.	CB1118-12	1	1150	5100

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
WINCHESTER	209	SR7625	25.0	CB.	CB1118-12	1	1210	5800
WINCHESTER	209	SR7625	26.0	CB.	CB1118-12	1	1250	6200
WINCHESTER	209	SR7625	22.0	REM.	RXP12	1	1095	4600
WINCHESTER	209	SR7625	23.5	REM.	RXP12	1	1140	5000
WINCHESTER	209	SR7625	25.0	REM.	RXP12	1	1200	5700
WINCHESTER	209	SR7625	26.0	REM.	RXP12	1	1245	6200
WINCHESTER	209	SR7625	22.0	FED.	12S3	1	1105	5300
WINCHESTER	209	SR7625	23.0	FED.	12S3	1	1155	5900
WINCHESTER	209	SR7625	24.0	FED.	12S3	1	1205	6500
WINCHESTER	209	SR7625	25.0	FED.	12S3	1	1250	7100

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
FEDERAL	209A	"HI-SKOR" 700-X	16.0	WIN.	WAA12SL	11/8	1110	7900
FEDERAL	209A	"HI-SKOR" 700-X	17.0	WIN.	WAA12SL	11/8	1150	8700
FEDERAL	209A	"HI-SKOR" 700-X	18.0	WIN.	WAA12SL	11/8	1190	9500
FEDERAL	209A	"HI-SKOR" 700-X	19.5	WIN.	WAA12SL	11/8	1250	10600
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB2118-12	11/8	1110	7900
FEDERAL	209A	"HI-SKOR" 700-X	17.0	CB.	CB2118-12	11/8	1155	8600
FEDERAL	209A	"HI-SKOR" 700-X	18.0	CB.	CB2118-12	11/8	1195	9500
FEDERAL	209A	"HI-SKOR" 700-X	19.5	CB.	CB2118-12	11/8	1260	10800
FEDERAL	209A	"HI-SKOR" 700-X	16.0	REM.	TGT12	11/8	1100	7400
FEDERAL	209A	"HI-SKOR" 700-X	17.0	REM.	TGT12	11/8	1145	8200
FEDERAL	209A	"HI-SKOR" 700-X	18.0	REM.	TGT12	11/8	1190	9100
FEDERAL	209A	"HI-SKOR" 700-X	19.5	REM.	TGT12	11/8	1250	10500
FEDERAL	209A	"HI-SKOR" 700-X	16.0	FED.	12S3	11/8	1105	7900
FEDERAL	209A	"HI-SKOR" 700-X	17.0	FED.	12S3	11/8	1145	8600
FEDERAL	209A	"HI-SKOR" 700-X	18.5	FED.	12S3	11/8	1205	9500
FEDERAL	209A	"HI-SKOR" 700-X	20.0	FED.	12S3	11/8	1260	10400
REMINGTON	209P	"HI-SKOR" 700-X	16.5	WIN.	WAA12SL	11/8	1110	7500
REMINGTON	209P	"HI-SKOR" 700-X	17.5	WIN.	WAA12SL	11/8	1155	8200
REMINGTON	209P	"HI-SKOR" 700-X	18.5	WIN.	WAA12SL	11/8	1195	8700
REMINGTON	209P	"HI-SKOR" 700-X	20.0	WIN.	WAA12SL	11/8	1255	9500
REMINGTON	209P	"HI-SKOR" 700-X	16.0	CB.	CB2118-12	11/8	1095	7200
REMINGTON	209P	"HI-SKOR" 700-X	17.0	CB.	CB2118-12	11/8	1140	7900
REMINGTON	209P	"HI-SKOR" 700-X	18.5	CB.	CB2118-12	11/8	1195	8700
REMINGTON	209P	"HI-SKOR" 700-X	20.0	CB.	CB2118-12	11/8	1250	9600
REMINGTON	209P	"HI-SKOR" 700-X	16.0	REM.	TGT12	11/8	1090	6900
REMINGTON	209P	"HI-SKOR" 700-X	17.5	REM.	TGT12	11/8	1150	7800
REMINGTON	209P	"HI-SKOR" 700-X	18.5	REM.	TGT12	11/8	1190	8500
REMINGTON	209P	"HI-SKOR" 700-X	20.0	REM.	TGT12	11/8	1250	9500
REMINGTON	209P	"HI-SKOR" 700-X	16.0	FED.	12S3	11/8	1095	7500
REMINGTON	209P	"HI-SKOR" 700-X	17.5	FED.	12S3	11/8	1155	8300
REMINGTON	209P	"HI-SKOR" 700-X	18.5	FED.	12S3	11/8	1190	8900
REMINGTON	209P	"HI-SKOR" 700-X	20.0	FED.	12S3	11/8	1250	9800
WINCHESTER	209	"HI-SKOR" 700-X	16.0	WIN.	WAA12SL	11/8	1100	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0	WIN.	WAA12SL	11/8	1145	7900
WINCHESTER	209	"HI-SKOR" 700-X	18.5	WIN.	WAA12SL	11/8	1205	9100
WINCHESTER	209	"HI-SKOR" 700-X	19.5	WIN.	WAA12SL	11/8	1245	9900
WINCHESTER	209	"HI-SKOR" 700-X	16.0	CB.	CB2118-12	11/8	1100	7200
WINCHESTER	209	"HI-SKOR" 700-X	17.0	CB.	CB2118-12	11/8	1145	7900
WINCHESTER	209	"HI-SKOR" 700-X	18.5	CB.	CB2118-12	11/8	1205	9200
WINCHESTER	209	"HI-SKOR" 700-X	19.5	CB.	CB2118-12	11/8	1245	10000
WINCHESTER	209	"HI-SKOR" 700-X	16.0	REM.	TGT12	11/8	1095	6800
WINCHESTER	209	"HI-SKOR" 700-X	17.0	REM.	TGT12	11/8	1140	7500
WINCHESTER	209	"HI-SKOR" 700-X	18.5	REM.	TGT12	11/8	1195	8600
WINCHESTER	209	"HI-SKOR" 700-X	20.0	REM.	TGT12	11/8	1255	9600
WINCHESTER	209	"HI-SKOR" 700-X	16.0	FED.	12S3	11/8	1105	7800
WINCHESTER	209	"HI-SKOR" 700-X	17.0	FED.	12S3	11/8	1150	8500
WINCHESTER	209	"HI-SKOR" 700-X	18.0	FED.	12S3	11/8	1190	9400
WINCHESTER	209	"HI-SKOR" 700-X	19.5	FED.	12S3	11/8	1255	10700
FEDERAL	209A	PB	19.5	WIN.	WAA12	11/8	1095	6100
FEDERAL	209A	PB	21.0	WIN.	WAA12	11/8	1150	7000
FEDERAL	209A	PB	22.5	WIN.	WAA12	11/8	1205	7900
FEDERAL	209A	PB	24.0	WIN.	WAA12	11/8	1260	8800
FEDERAL	209A	PB	20.5	WTW.	WINDJAMMER	11/8	1105	5900

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
FEDERAL	209A	PB	21.5	WTW.	WINDJAMMER	11/8	1145	6400
FEDERAL	209A	PB	23.0	WTW.	WINDJAMMER	11/8	1205	7200
FEDERAL	209A	PB	24.0	WTW.	WINDJAMMER	11/8	1250	7800
FEDERAL	209A	PB	20.0	CB.	CB1118-12	11/8	1105	6000
FEDERAL	209A	PB	21.0	CB.	CB1118-12	11/8	1140	6400
FEDERAL	209A	PB	22.5	CB.	CB1118-12	11/8	1195	7100
FEDERAL	209A	PB	24.0	CB.	CB1118-12	11/8	1250	8000
FEDERAL	209A	PB	20.0	REM.	FIG8	11/8	1095	6000
FEDERAL	209A	PB	21.5	REM.	FIG8	11/8	1145	6600
FEDERAL	209A	PB	23.0	REM.	FIG8	11/8	1200	7300
FEDERAL	209A	PB	24.5	REM.	FIG8	11/8	1255	8000
FEDERAL	209A	PB	19.5	FED.	12S3	11/8	1095	6600
FEDERAL	209A	PB	21.0	FED.	12S3	11/8	1140	7100
FEDERAL	209A	PB	22.5	FED.	12S3	11/8	1190	7600
FEDERAL	209A	PB	24.0	FED.	12S3	11/8	1255	8700
REMINGTON	209P	PB	20.5	WIN.	WAA12SL	11/8	1095	5700
REMINGTON	209P	PB	21.5	WIN.	WAA12SL	11/8	1140	6400
REMINGTON	209P	PB	23.0	WIN.	WAA12SL	11/8	1195	7300
REMINGTON	209P	PB	25.0	WIN.	WAA12SL	11/8	1260	8000
REMINGTON	209P	PB	21.0	WTW.	WINDJAMMER	11/8	1095	5000
REMINGTON	209P	PB	22.5	WTW.	WINDJAMMER	11/8	1155	5900
REMINGTON	209P	PB	24.0	WTW.	WINDJAMMER	11/8	1205	6400
REMINGTON	209P	PB	25.5	WTW.	WINDJAMMER	11/8	1250	6900
REMINGTON	209P	PB	21.0	CB.	CB1118-12	11/8	1105	5800
REMINGTON	209P	PB	22.5	CB.	CB1118-12	11/8	1150	6300
REMINGTON	209P	PB	23.5	CB.	CB1118-12	11/8	1200	7000
REMINGTON	209P	PB	25.0	CB.	CB1118-12	11/8	1265	8000
REMINGTON	209P	PB	21.0	REM.	FIG8	11/8	1100	5500
REMINGTON	209P	PB	22.5	REM.	FIG8	11/8	1155	6100
REMINGTON	209P	PB	23.5	REM.	FIG8	11/8	1190	6600
REMINGTON	209P	PB	25.0	REM.	FIG8	11/8	1245	7500
REMINGTON	209P	PB	20.5	FED.	12S3	11/8	1100	6000
REMINGTON	209P	PB	22.0	FED.	12S3	11/8	1155	6500
REMINGTON	209P	PB	23.0	FED.	12S3	11/8	1190	7000
REMINGTON	209P	PB	25.0	FED.	12S3	11/8	1265	8400
WINCHESTER	209	PB	21.0	WIN.	WAA12SL	11/8	1100	6000
WINCHESTER	209	PB	22.0	WIN.	WAA12SL	11/8	1140	6600
WINCHESTER	209	PB	23.5	WIN.	WAA12SL	11/8	1200	7500
WINCHESTER	209	PB	25.0	WIN.	WAA12SL	11/8	1255	8200
WINCHESTER	209	PB	21.0	WTW.	WINDJAMMER	11/8	1105	5500
WINCHESTER	209	PB	22.0	WTW.	WINDJAMMER	11/8	1145	6000
WINCHESTER	209	PB	23.5	WTW.	WINDJAMMER	11/8	1205	7000
WINCHESTER	209	PB	24.5	WTW.	WINDJAMMER	11/8	1250	7700
WINCHESTER	209	PB	20.5	CB.	CB1118-12	11/8	1100	5800
WINCHESTER	209	PB	22.0	CB.	CB1118-12	11/8	1150	6400
WINCHESTER	209	PB	23.5	CB.	CB1118-12	11/8	1200	7000
WINCHESTER	209	PB	25.0	CB.	CB1118-12	11/8	1245	7600
WINCHESTER	209	PB	21.0	REM.	FIG8	11/8	1105	5900
WINCHESTER	209	PB	22.0	REM.	FIG8	11/8	1140	6300
WINCHESTER	209	PB	23.5	REM.	FIG8	11/8	1200	7000
WINCHESTER	209	PB	25.0	REM.	FIG8	11/8	1255	7800
WINCHESTER	209	PB	20.5	FED.	12S3	11/8	1090	6100
WINCHESTER	209	PB	22.0	FED.	12S3	11/8	1150	7000
WINCHESTER	209	PB	23.0	FED.	12S3	11/8	1190	7600
WINCHESTER	209	PB	24.5	FED.	12S3	11/8	1250	8400
FEDERAL	209A	SR7625	21.5	WIN.	WAA12	11/8	1100	6100
FEDERAL	209A	SR7625	23.0	WIN.	WAA12	11/8	1155	6700
FEDERAL	209A	SR7625	24.5	WIN.	WAA12	11/8	1200	7400
FEDERAL	209A	SR7625	26.0	WIN.	WAA12	11/8	1265	8200
FEDERAL	209A	SR7625	23.0	WTW.	WINDJAMMER	11/8	1105	5100
FEDERAL	209A	SR7625	24.0	WTW.	WINDJAMMER	11/8	1140	5600
FEDERAL	209A	SR7625	25.5	WTW.	WINDJAMMER	11/8	1200	6400
FEDERAL	209A	SR7625	27.0	WTW.	WINDJAMMER	11/8	1265	7400

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
FEDERAL	209A	SR7625	22.0	CB.	CB2118-12	11/8	1095	5700
FEDERAL	209A	SR7625	23.5	CB.	CB2118-12	11/8	1150	6400
FEDERAL	209A	SR7625	24.5	CB.	CB2118-12	11/8	1195	6800
FEDERAL	209A	SR7625	26.0	CB.	CB2118-12	11/8	1250	7700
FEDERAL	209A	SR7625	22.5	REM.	FIG8	11/8	1090	5300
FEDERAL	209A	SR7625	24.0	REM.	FIG8	11/8	1140	5700
FEDERAL	209A	SR7625	25.5	REM.	FIG8	11/8	1205	6600
FEDERAL	209A	SR7625	26.5	REM.	FIG8	11/8	1245	7100
FEDERAL	209A	SR7625	22.0	FED.	12S3	11/8	1090	5600
FEDERAL	209A	SR7625	23.5	FED.	12S3	11/8	1150	6400
FEDERAL	209A	SR7625	24.5	FED.	12S3	11/8	1190	6900
FEDERAL	209A	SR7625	26.5	FED.	12S3	11/8	1260	7700
REMINGTON	209P	SR7625	22.0	WIN.	WAA12	11/8	1100	5600
REMINGTON	209P	SR7625	23.5	WIN.	WAA12	11/8	1145	6000
REMINGTON	209P	SR7625	25.5	WIN.	WAA12	11/8	1205	6600
REMINGTON	209P	SR7625	27.5	WIN.	WAA12	11/8	1255	7200
REMINGTON	209P	SR7625	24.0	WTW.	WINDJAMMER	11/8	1095	4300
REMINGTON	209P	SR7625	25.5	WTW.	WINDJAMMER	11/8	1140	4700
REMINGTON	209P	SR7625	27.0	WTW.	WINDJAMMER	11/8	1200	5400
REMINGTON	209P	SR7625	28.5	WTW.	WINDJAMMER	11/8	1265	6100
REMINGTON	209P	SR7625	22.5	CB.	CB2118-12	11/8	1105	5300
REMINGTON	209P	SR7625	24.5	CB.	CB2118-12	11/8	1150	5900
REMINGTON	209P	SR7625	26.0	CB.	CB2118-12	11/8	1205	6600
REMINGTON	209P	SR7625	27.0	CB.	CB2118-12	11/8	1250	7300
REMINGTON	209P	SR7625	24.0	REM.	FIG8	11/8	1100	5000
REMINGTON	209P	SR7625	25.5	REM.	FIG8	11/8	1155	5700
REMINGTON	209P	SR7625	27.0	REM.	FIG8	11/8	1205	6000
REMINGTON	209P	SR7625	28.5	REM.	FIG8	11/8	1260	6300
REMINGTON	209P	SR7625	23.0	FED.	12S3	11/8	1095	5200
REMINGTON	209P	SR7625	24.5	FED.	12S3	11/8	1155	6000
REMINGTON	209P	SR7625	25.5	FED.	12S3	11/8	1195	6400
REMINGTON	209P	SR7625	27.0	FED.	12S3	11/8	1255	7400
WINCHESTER	209	SR7625	22.5	WIN.	WAA12	11/8	1100	5600
WINCHESTER	209	SR7625	24.0	WIN.	WAA12	11/8	1155	6200
WINCHESTER	209	SR7625	25.0	WIN.	WAA12	11/8	1190	6600
WINCHESTER	209	SR7625	26.5	WIN.	WAA12	11/8	1250	7400
WINCHESTER	209	SR7625	23.0	WTW.	WINDJAMMER	11/8	1095	4900
WINCHESTER	209	SR7625	24.5	WTW.	WINDJAMMER	11/8	1140	5400
WINCHESTER	209	SR7625	26.0	WTW.	WINDJAMMER	11/8	1200	6200
WINCHESTER	209	SR7625	27.0	WTW.	WINDJAMMER	11/8	1245	6900
WINCHESTER	209	SR7625	22.5	CB.	CB2118-12	11/8	1095	5400
WINCHESTER	209	SR7625	24.0	CB.	CB2118-12	11/8	1150	6000
WINCHESTER	209	SR7625	25.5	CB.	CB2118-12	11/8	1200	6700
WINCHESTER	209	SR7625	27.0	CB.	CB2118-12	11/8	1250	7300
WINCHESTER	209	SR7625	23.0	REM.	FIG8	11/8	1095	5200
WINCHESTER	209	SR7625	24.5	REM.	FIG8	11/8	1150	5800
WINCHESTER	209	SR7625	25.5	REM.	FIG8	11/8	1190	6300
WINCHESTER	209	SR7625	27.0	REM.	FIG8	11/8	1250	7100
WINCHESTER	209	SR7625	23.0	FED.	12S3	11/8	1100	5400
WINCHESTER	209	SR7625	24.5	FED.	12S3	11/8	1155	6200
WINCHESTER	209	SR7625	25.5	FED.	12S3	11/8	1195	6700
WINCHESTER	209	SR7625	27.0	FED.	12S3	11/8	1255	7500
CCI	209	"HI-SKOR" 800-X	21.5	WIN.	WAA12	11/8	1105	5200
CCI	209	"HI-SKOR" 800-X	22.5	WIN.	WAA12	11/8	1145	5600
CCI	209	"HI-SKOR" 800-X	24.0	WIN.	WAA12	11/8	1200	6300
CCI	209	"HI-SKOR" 800-X	25.5	WIN.	WAA12	11/8	1265	7100
CCI	209	"HI-SKOR" 800-X	22.5	WTW.	WINDJAMMER	11/8	1100	4200
CCI	209	"HI-SKOR" 800-X	23.5	WTW.	WINDJAMMER	11/8	1145	4800
CCI	209	"HI-SKOR" 800-X	25.0	WTW.	WINDJAMMER	11/8	1205	5700
CCI	209	"HI-SKOR" 800-X	26.0	WTW.	WINDJAMMER	11/8	1250	6300
CCI	209	"HI-SKOR" 800-X	21.5	CB	CB2118-12	11/8	1095	5000
CCI	209	"HI-SKOR" 800-X	23.0	CB	CB2118-12	11/8	1145	5500
CCI	209	"HI-SKOR" 800-X	24.5	CB	CB2118-12	11/8	1205	6200
CCI	209	"HI-SKOR" 800-X	26.0	CB	CB2118-12	11/8	1265	6800
CCI	209	"HI-SKOR" 800-X	21.0	REM.	FIG 8	11/8	1105	5500
CCI	209	"HI-SKOR" 800-X	22.5	REM.	FIG 8	11/8	1150	5900
CCI	209	"HI-SKOR" 800-X	24.0	REM.	FIG 8	11/8	1200	6300
CCI	209	"HI-SKOR" 800-X	26.0	REM.	FIG 8	11/8	1260	6900
CCI	209	"HI-SKOR" 800-X	21.0	FED.	12S3	11/8	1095	5800
CCI	209	"HI-SKOR" 800-X	22.5	FED.	12S3	11/8	1155	6400
CCI	209	"HI-SKOR" 800-X	24.0	FED.	12S3	11/8	1200	6800
CCI	209	"HI-SKOR" 800-X	26.0	FED.	12S3	11/8	1260	7300

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC GOLD MEDAL								
FEDERAL	209A	"HI-SKOR" 800-X	20.5	WIN.	WAA12	11/8	1100	5800
FEDERAL	209A	"HI-SKOR" 800-X	21.5	WIN.	WAA12	11/8	1140	6300
FEDERAL	209A	"HI-SKOR" 800-X	23.0	WIN.	WAA12	11/8	1195	7000
FEDERAL	209A	"HI-SKOR" 800-X	24.5	WIN.	WAA12	11/8	1255	7700
FEDERAL	209A	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	11/8	1100	4900
FEDERAL	209A	"HI-SKOR" 800-X	23.0	WTW	WINDJAMMER	11/8	1145	5400
FEDERAL	209A	"HI-SKOR" 800-X	24.0	WTW	WINDJAMMER	11/8	1190	5900
FEDERAL	209A	"HI-SKOR" 800-X	25.5	WTW	WINDJAMMER	11/8	1260	6700
FEDERAL	209A	"HI-SKOR" 800-X	20.5	CB	CB2118-12	11/8	1090	5500
FEDERAL	209A	"HI-SKOR" 800-X	22.5	CB	CB2118-12	11/8	1150	6200
FEDERAL	209A	"HI-SKOR" 800-X	23.0	CB	CB2118-12	11/8	1195	6700
FEDERAL	209A	"HI-SKOR" 800-X	24.5	CB	CB2118-12	11/8	1250	7400
FEDERAL	209A	"HI-SKOR" 800-X	21.0	REM.	FIG8	11/8	1100	5400
FEDERAL	209A	"HI-SKOR" 800-X	22.5	REM.	FIG8	11/8	1155	6000
FEDERAL	209A	"HI-SKOR" 800-X	24.0	REM.	FIG8	11/8	1205	6600
FEDERAL	209A	"HI-SKOR" 800-X	25.5	REM.	FIG8	11/8	1255	7100
FEDERAL	209A	"HI-SKOR" 800-X	20.5	FED.	12S3	11/8	1090	5700
FEDERAL	209A	"HI-SKOR" 800-X	22.0	FED.	12S3	11/8	1155	6400
FEDERAL	209A	"HI-SKOR" 800-X	23.0	FED.	12S3	11/8	1195	6900
FEDERAL	209A	"HI-SKOR" 800-X	25.0	FED.	12S3	11/8	1265	7700
WINCHESTER	209	"HI-SKOR" 800-X	20.5	WIN.	WAA12	11/8	1100	5800
WINCHESTER	209	"HI-SKOR" 800-X	21.5	WIN.	WAA12	11/8	1140	6300
WINCHESTER	209	"HI-SKOR" 800-X	23.0	WIN.	WAA12	11/8	1195	7000
WINCHESTER	209	"HI-SKOR" 800-X	25.0	WIN.	WAA12	11/8	1265	7700
WINCHESTER	209	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	11/8	1105	4900
WINCHESTER	209	"HI-SKOR" 800-X	23.0	WTW	WINDJAMMER	11/8	1150	5400
WINCHESTER	209	"HI-SKOR" 800-X	24.0	WTW	WINDJAMMER	11/8	1190	5900
WINCHESTER	209	"HI-SKOR" 800-X	25.5	WTW	WINDJAMMER	11/8	1255	6700
WINCHESTER	209	"HI-SKOR" 800-X	20.5	CB	CB2118-12	11/8	1095	5500
WINCHESTER	209	"HI-SKOR" 800-X	22.0	CB	CB2118-12	11/8	1145	6000
WINCHESTER	209	"HI-SKOR" 800-X	23.5	CB	CB2118-12	11/8	1200	6700
WINCHESTER	209	"HI-SKOR" 800-X	25.0	CB	CB2118-12	11/8	1260	7400
WINCHESTER	209	"HI-SKOR" 800-X	21.0	REM.	FIG8	11/8	1100	5400
WINCHESTER	209	"HI-SKOR" 800-X	22.0	REM.	FIG8	11/8	1140	5900
WINCHESTER	209	"HI-SKOR" 800-X	23.5	REM.	FIG8	11/8	1200	6500
WINCHESTER	209	"HI-SKOR" 800-X	25.0	REM.	FIG8	11/8	1255	7100
WINCHESTER	209	"HI-SKOR" 800-X	20.5	FED.	12S3	11/8	1095	5700
WINCHESTER	209	"HI-SKOR" 800-X	22.0	FED.	12S3	11/8	1155	6300
WINCHESTER	209	"HI-SKOR" 800-X	23.0	FED.	12S3	11/8	1195	6800
WINCHESTER	209	"HI-SKOR" 800-X	24.5	FED.	12S3	11/8	1250	7500
SHELL: REMINGTON PREMIER (RTL)								
FEDERAL	209A	"HI-SKOR" 700-X	15.0	WIN.	WAA12	11/8	1100	9500
FEDERAL	209A	"HI-SKOR" 700-X	16.5	WIN.	WAA12	11/8	1160	10900
FEDERAL	209A	"HI-SKOR" 700-X	15.5	WTW	WINDJAMMER	11/8	1110	8400
FEDERAL	209A	"HI-SKOR" 700-X	16.5	WTW	WINDJAMMER	11/8	1155	9500
FEDERAL	209A	"HI-SKOR" 700-X	17.5	WTW	WINDJAMMER	11/8	1200	10400
FEDERAL	209A	"HI-SKOR" 700-X	18.5	WTW	WINDJAMMER	11/8	1240	11100
FEDERAL	209A	"HI-SKOR" 700-X	15.5	CB	CB1118-12	11/8	1110	8500
FEDERAL	209A	"HI-SKOR" 700-X	16.5	CB	CB1118-12	11/8	1160	9700
FEDERAL	209A	"HI-SKOR" 700-X	17.5	CB	CB1118-12	11/8	1200	10800
FEDERAL	209A	"HI-SKOR" 700-X	15.5	REM.	FIG8	11/8	1105	8900
FEDERAL	209A	"HI-SKOR" 700-X	16.5	REM.	FIG8	11/8	1150	10000
FEDERAL	209A	"HI-SKOR" 700-X	17.5	REM.	FIG8	11/8	1195	11000
FEDERAL	209A	"HI-SKOR" 700-X	15.0	FED.	12S3	11/8	1095	9300
FEDERAL	209A	"HI-SKOR" 700-X	16.0	FED.	12S3	11/8	1135	10200
FEDERAL	209A	"HI-SKOR" 700-X	17.5	FED.	12S3	11/8	1200	11500
REMINGTON	209P	"HI-SKOR" 700-X	15.0	WIN.	WAA12	11/8	1090	8500
REMINGTON	209P	"HI-SKOR" 700-X	16.0	WIN.	WAA12	11/8	1140	9600
REMINGTON	209P	"HI-SKOR" 700-X	17.5	WIN.	WAA12	11/8	1205	11200
REMINGTON	209P	"HI-SKOR" 700-X	15.5	WTW	WINDJAMMER	11/8	1090	7600
REMINGTON	209P	"HI-SKOR" 700-X	16.5	WTW	WINDJAMMER	11/8	1135	8400
REMINGTON	209P	"HI-SKOR" 700-X	18.0	WTW	WINDJAMMER	11/8	1200	9600
REMINGTON	209P	"HI-SKOR" 700-X	19.0	WTW	WINDJAMMER	11/8	1245	10500
REMINGTON	209P	"HI-SKOR" 700-X	15.5	CB	CB1118-12	11/8	1110	8000
REMINGTON	209P	"HI-SKOR" 700-X	16.5	CB	CB1118-12	11/8	1155	8900
REMINGTON	209P	"HI-SKOR" 700-X	17.5	CB	CB1118-12	11/8	1195	9800

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
REMINGTON	209P	"HI-SKOR" 700-X	19.0	CB.	CB1118-12	11/8	1250	11100
REMINGTON	209P	"HI-SKOR" 700-X	15.5	REM.	FIG8	11/8	1095	8100
REMINGTON	209P	"HI-SKOR" 700-X	16.5	REM.	FIG8	11/8	1140	9000
REMINGTON	209P	"HI-SKOR" 700-X	18.0	REM.	FIG8	11/8	1205	10400
REMINGTON	209P	"HI-SKOR" 700-X	19.0	REM.	FIG8	11/8	1250	11300
REMINGTON	209P	"HI-SKOR" 700-X	15.0	FED.	12S3	11/8	1095	8900
REMINGTON	209P	"HI-SKOR" 700-X	16.5	FED.	12S3	11/8	1150	10200
REMINGTON	209P	"HI-SKOR" 700-X	17.5	FED.	12S3	11/8	1195	11100
WINCHESTER	209	"HI-SKOR" 700-X	15.5	WIN.	WAA12	11/8	1105	9300
WINCHESTER	209	"HI-SKOR" 700-X	16.5	WIN.	WAA12	11/8	1145	10200
WINCHESTER	209	"HI-SKOR" 700-X	17.5	WIN.	WAA12	11/8	1190	11200
WINCHESTER	209	"HI-SKOR" 700-X	15.5	WTW.	WINDJAMMER	11/8	1100	8000
WINCHESTER	209	"HI-SKOR" 700-X	16.5	WTW.	WINDJAMMER	11/8	1150	8900
WINCHESTER	209	"HI-SKOR" 700-X	17.5	WTW.	WINDJAMMER	11/8	1190	9800
WINCHESTER	209	"HI-SKOR" 700-X	19.0	WTW.	WINDJAMMER	11/8	1255	11100
WINCHESTER	209	"HI-SKOR" 700-X	15.5	CB.	CB1118-12	11/8	1095	7700
WINCHESTER	209	"HI-SKOR" 700-X	16.5	CB.	CB1118-12	11/8	1145	8700
WINCHESTER	209	"HI-SKOR" 700-X	17.5	CB.	CB1118-12	11/8	1190	9800
WINCHESTER	209	"HI-SKOR" 700-X	19.0	CB.	CB1118-12	11/8	1250	11400
WINCHESTER	209	"HI-SKOR" 700-X	15.5	REM.	FIG8	11/8	1095	8500
WINCHESTER	209	"HI-SKOR" 700-X	16.5	REM.	FIG8	11/8	1140	9400
WINCHESTER	209	"HI-SKOR" 700-X	18.0	REM.	FIG8	11/8	1205	10800
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S3	11/8	1100	9000
WINCHESTER	209	"HI-SKOR" 700-X	16.5	FED.	12S3	11/8	1145	9800
WINCHESTER	209	"HI-SKOR" 700-X	17.5	FED.	12S3	11/8	1190	10900
FEDERAL	209A	PB	18.5	WIN.	WAA12	11/8	1100	8200
FEDERAL	209A	PB	20.0	WIN.	WAA12	11/8	1155	9200
FEDERAL	209A	PB	21.0	WIN.	WAA12	11/8	1190	9900
FEDERAL	209A	PB	23.0	WIN.	WAA12	11/8	1260	11000
FEDERAL	209A	PB	19.5	WTW.	WINDJAMMER	11/8	1100	6800
FEDERAL	209A	PB	20.5	WTW.	WINDJAMMER	11/8	1145	7500
FEDERAL	209A	PB	22.0	WTW.	WINDJAMMER	11/8	1200	8500
FEDERAL	209A	PB	23.5	WTW.	WINDJAMMER	11/8	1260	9500
FEDERAL	209A	PB	19.0	CB.	CB1118-12	11/8	1100	7300
FEDERAL	209A	PB	20.5	CB.	CB1118-12	11/8	1150	7900
FEDERAL	209A	PB	22.0	CB.	CB1118-12	11/8	1205	8700
FEDERAL	209A	PB	23.5	CB.	CB1118-12	11/8	1260	9500
FEDERAL	209A	PB	19.5	REM.	FIG8	11/8	1110	7500
FEDERAL	209A	PB	20.5	REM.	FIG8	11/8	1150	8100
FEDERAL	209A	PB	22.0	REM.	FIG8	11/8	1200	8900
FEDERAL	209A	PB	23.5	REM.	FIG8	11/8	1255	9600
FEDERAL	209A	PB	18.5	FED.	12S4	11/8	1105	8400
FEDERAL	209A	PB	19.5	FED.	12S4	11/8	1140	8800
FEDERAL	209A	PB	21.0	FED.	12S4	11/8	1190	9600
FEDERAL	209A	PB	23.0	FED.	12S4	11/8	1265	10900
REMINGTON	209P	PB	19.5	WIN.	WAA12	11/8	1105	7300
REMINGTON	209P	PB	20.5	WIN.	WAA12	11/8	1145	8000
REMINGTON	209P	PB	22.0	WIN.	WAA12	11/8	1200	8700
REMINGTON	209P	PB	23.5	WIN.	WAA12	11/8	1255	9500
REMINGTON	209P	PB	20.0	WTW.	WINDJAMMER	11/8	1100	6300
REMINGTON	209P	PB	21.0	WTW.	WINDJAMMER	11/8	1140	6900
REMINGTON	209P	PB	22.5	WTW.	WINDJAMMER	11/8	1205	7900
REMINGTON	209P	PB	24.0	WTW.	WINDJAMMER	11/8	1265	8900
REMINGTON	209P	PB	19.5	CB.	CB1118-12	11/8	1090	6400
REMINGTON	209P	PB	21.0	CB.	CB1118-12	11/8	1150	7400
REMINGTON	209P	PB	22.5	CB.	CB1118-12	11/8	1200	8000
REMINGTON	209P	PB	24.0	CB.	CB1118-12	11/8	1250	8600
REMINGTON	209P	PB	20.0	REM.	FIG8	11/8	1100	6800
REMINGTON	209P	PB	21.5	REM.	FIG8	11/8	1150	7500
REMINGTON	209P	PB	23.0	REM.	FIG8	11/8	1205	8400
REMINGTON	209P	PB	24.5	REM.	FIG8	11/8	1260	9300
REMINGTON	209P	PB	19.0	FED.	12S4	11/8	1100	7700
REMINGTON	209P	PB	20.0	FED.	12S4	11/8	1140	8400
REMINGTON	209P	PB	21.5	FED.	12S4	11/8	1195	9300
REMINGTON	209P	PB	23.0	FED.	12S4	11/8	1245	10000

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
WINCHESTER	209	PB	19.0	WIN.	WAA12	11/8	1100	7700
WINCHESTER	209	PB	20.0	WIN.	WAA12	11/8	1140	8400
WINCHESTER	209	PB	22.0	WIN.	WAA12	11/8	1205	9400
WINCHESTER	209	PB	23.5	WIN.	WAA12	11/8	1255	10200
WINCHESTER	209	PB	20.0	WTW.	WINDJAMMER	11/8	1105	6700
WINCHESTER	209	PB	21.0	WTW.	WINDJAMMER	11/8	1145	7300
WINCHESTER	209	PB	22.5	WTW.	WINDJAMMER	11/8	1205	8200
WINCHESTER	209	PB	24.0	WTW.	WINDJAMMER	11/8	1260	9100
WINCHESTER	209	PB	20.0	CB.	CB1118-12	11/8	1100	6700
WINCHESTER	209	PB	21.0	CB.	CB1118-12	11/8	1140	7200
WINCHESTER	209	PB	22.5	CB.	CB1118-12	11/8	1200	8000
WINCHESTER	209	PB	24.0	CB.	CB1118-12	11/8	1255	8800
WINCHESTER	209	PB	19.5	REM.	FIG8	11/8	1095	6900
WINCHESTER	209	PB	21.0	REM.	FIG8	11/8	1155	7900
WINCHESTER	209	PB	22.0	REM.	FIG8	11/8	1190	8400
WINCHESTER	209	PB	23.5	REM.	FIG8	11/8	1250	9300
WINCHESTER	209	PB	19.0	FED.	12S4	11/8	1095	7700
WINCHESTER	209	PB	20.5	FED.	12S4	11/8	1155	8500
WINCHESTER	209	PB	21.5	FED.	12S4	11/8	1190	9100
WINCHESTER	209	PB	23.5	FED.	12S4	11/8	1260	10400
FEDERAL	209A	SR7625	19.5	WIN.	WAA12	11/8	1100	7900
FEDERAL	209A	SR7625	20.5	WIN.	WAA12	11/8	1140	8500
FEDERAL	209A	SR7625	22.0	WIN.	WAA12	11/8	1205	9700
FEDERAL	209A	SR7625	23.0	WIN.	WAA12	11/8	1245	10500
FEDERAL	209A	SR7625	21.0	WTW.	WINDJAMMER	11/8	1105	6500
FEDERAL	209A	SR7625	22.0	WTW.	WINDJAMMER	11/8	1150	7200
FEDERAL	209A	SR7625	23.5	WTW.	WINDJAMMER	11/8	1205	7800
FEDERAL	209A	SR7625	25.0	WTW.	WINDJAMMER	11/8	1255	8400
FEDERAL	209A	SR7625	20.0	CB.	CB1118-12	11/8	1090	6900
FEDERAL	209A	SR7625	21.5	CB.	CB1118-12	11/8	1150	7900
FEDERAL	209A	SR7625	22.5	CB.	CB1118-12	11/8	1190	8400
FEDERAL	209A	SR7625	24.0	CB.	CB1118-12	11/8	1250	9200
FEDERAL	209A	SR7625	20.5	REM.	RXP12	11/8	1095	7200
FEDERAL	209A	SR7625	22.0	REM.	RXP12	11/8	1155	8000
FEDERAL	209A	SR7625	23.0	REM.	RXP12	11/8	1190	8600
FEDERAL	209A	SR7625	24.5	REM.	RXP12	11/8	1250	9400
FEDERAL	209A	SR7625	20.0	FED.	12S3	11/8	1095	7300
FEDERAL	209A	SR7625	21.0	FED.	12S3	11/8	1140	8100
FEDERAL	209A	SR7625	22.5	FED.	12S3	11/8	1195	9100
FEDERAL	209A	SR7625	24.0	FED.	12S3	11/8	1250	10000
REMINGTON	209P	SR7625	20.0	WIN.	WAA12	11/8	1090	7100
REMINGTON	209P	SR7625	21.5	WIN.	WAA12	11/8	1150	8000
REMINGTON	209P	SR7625	23.0	WIN.	WAA12	11/8	1200	8700
REMINGTON	209P	SR7625	24.5	WIN.	WAA12	11/8	1255	9400
REMINGTON	209P	SR7625	21.5	WTW.	WINDJAMMER	11/8	1095	6000
REMINGTON	209P	SR7625	23.0	WTW.	WINDJAMMER	11/8	1150	6700
REMINGTON	209P	SR7625	24.0	WTW.	WINDJAMMER	11/8	1195	7300
REMINGTON	209P	SR7625	25.5	WTW.	WINDJAMMER	11/8	1260	8400
REMINGTON	209P	SR7625	20.5	CB.	CB1118-12	11/8	1095	6400
REMINGTON	209P	SR7625	22.0	CB.	CB1118-12	11/8	1155	7400
REMINGTON	209P	SR7625	23.0	CB.	CB1118-12	11/8	1195	8000
REMINGTON	209P	SR7625	24.5	CB.	CB1118-12	11/8	1250	8800
REMINGTON	209P	SR7625	21.0	REM.	RXP12	11/8	1095	6500
REMINGTON	209P	SR7625	22.5	REM.	RXP12	11/8	1150	7400
REMINGTON	209P	SR7625	24.0	REM.	RXP12	11/8	1205	8200
REMINGTON	209P	SR7625	25.5	REM.	RXP12	11/8	1250	9000
REMINGTON	209P	SR7625	21.0	FED.	12S3	11/8	1110	7200
REMINGTON	209P	SR7625	22.0	FED.	12S3	11/8	1150	7800
REMINGTON	209P	SR7625	23.5	FED.	12S3	11/8	1210	8700
REMINGTON	209P	SR7625	24.5	FED.	12S3	11/8	1250	9500
WINCHESTER	209	SR7625	20.5	WIN.	WAA12	11/8	1090	7000
WINCHESTER	209	SR7625	22.0	WIN.	WAA12	11/8	1155	7900
WINCHESTER	209	SR7625	23.0	WIN.	WAA12	11/8	1195	8600

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
WINCHESTER	209	SR7625	24.5	WIN.	WAA12	11/8	1250	9500
WINCHESTER	209	SR7625	21.5	WTW.	WINDJAMMER	11/8	1095	5900
WINCHESTER	209	SR7625	22.5	WTW.	WINDJAMMER	11/8	1140	6500
WINCHESTER	209	SR7625	24.0	WTW.	WINDJAMMER	11/8	1205	7700
WINCHESTER	209	SR7625	25.0	WTW.	WINDJAMMER	11/8	1250	8500
WINCHESTER	209	SR7625	21.0	CB.	CB1118-12	11/8	1090	6200
WINCHESTER	209	SR7625	22.5	CB.	CB1118-12	11/8	1155	7200
WINCHESTER	209	SR7625	23.0	CB.	CB1118-12	11/8	1200	7600
WINCHESTER	209	SR7625	24.5	CB.	CB1118-12	11/8	1245	8600
WINCHESTER	209	SR7625	21.0	REM.	RXP12	11/8	1090	6200
WINCHESTER	209	SR7625	22.5	REM.	RXP12	11/8	1155	7400
WINCHESTER	209	SR7625	23.5	REM.	RXP12	11/8	1195	7900
WINCHESTER	209	SR7625	25.0	REM.	RXP12	11/8	1250	8800
WINCHESTER	209	SR7625	20.5	FED.	12S3	11/8	1090	6700
WINCHESTER	209	SR7625	22.0	FED.	12S3	11/8	1145	7800
WINCHESTER	209	SR7625	23.5	FED.	12S3	11/8	1205	8800
WINCHESTER	209	SR7625	24.5	FED.	12S3	11/8	1255	9600
CCI	209	"HI-SKOR" 800-X	19.5	WIN.	WAA12	11/8	1105	6900
CCI	209	"HI-SKOR" 800-X	20.5	WIN.	WAA12	11/8	1150	7500
CCI	209	"HI-SKOR" 800-X	21.5	WIN.	WAA12	11/8	1190	8200
CCI	209	"HI-SKOR" 800-X	23.0	WIN.	WAA12	11/8	1255	9100
CCI	209	"HI-SKOR" 800-X	20.0	WTW	WINDJAMMER	11/8	1095	6000
CCI	209	"HI-SKOR" 800-X	21.0	WTW	WINDJAMMER	11/8	1145	6700
CCI	209	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	11/8	1195	7300
CCI	209	"HI-SKOR" 800-X	23.5	WTW	WINDJAMMER	11/8	1250	8200
CCI	209	"HI-SKOR" 800-X	19.5	CB	CB1118-12	11/8	1095	6200
CCI	209	"HI-SKOR" 800-X	21.0	CB	CB1118-12	11/8	1155	7000
CCI	209	"HI-SKOR" 800-X	22.0	CB	CB1118-12	11/8	1195	7500
CCI	209	"HI-SKOR" 800-X	23.5	CB	CB1118-12	11/8	1255	8400
CCI	209	"HI-SKOR" 800-X	19.5	REM.	FIG8	11/8	1095	6500
CCI	209	"HI-SKOR" 800-X	21.0	REM.	FIG8	11/8	1155	7200
CCI	209	"HI-SKOR" 800-X	22.0	REM.	FIG8	11/8	1190	7600
CCI	209	"HI-SKOR" 800-X	24.0	REM.	FIG8	11/8	1265	8700
CCI	209	"HI-SKOR" 800-X	19.5	FED.	12S3	11/8	1100	7000
CCI	209	"HI-SKOR" 800-X	20.5	FED.	12S3	11/8	1140	7600
CCI	209	"HI-SKOR" 800-X	22.0	FED.	12S3	11/8	1200	8500
CCI	209	"HI-SKOR" 800-X	23.5	FED.	12S3	11/8	1260	9400
FEDERAL	209A	"HI-SKOR" 800-X	19.0	WIN.	WAA12	11/8	1095	7200
FEDERAL	209A	"HI-SKOR" 800-X	20.0	WIN.	WAA12	11/8	1145	8000
FEDERAL	209A	"HI-SKOR" 800-X	21.0	WIN.	WAA12	11/8	1190	8700
FEDERAL	209A	"HI-SKOR" 800-X	22.5	WIN.	WAA12	11/8	1250	9700
FEDERAL	209A	"HI-SKOR" 800-X	20.0	WTW	WINDJAMMER	11/8	1110	6500
FEDERAL	209A	"HI-SKOR" 800-X	21.0	WTW	WINDJAMMER	11/8	1160	7200
FEDERAL	209A	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	11/8	1205	7900
FEDERAL	209A	"HI-SKOR" 800-X	23.0	WTW	WINDJAMMER	11/8	1250	8600
FEDERAL	209A	"HI-SKOR" 800-X	19.5	CB	CB1118-12	11/8	1105	6800
FEDERAL	209A	"HI-SKOR" 800-X	20.5	CB	CB1118-12	11/8	1150	7500
FEDERAL	209A	"HI-SKOR" 800-X	21.5	CB	CB1118-12	11/8	1200	8200
FEDERAL	209A	"HI-SKOR" 800-X	23.0	CB	CB1118-12	11/8	1250	9000
FEDERAL	209A	"HI-SKOR" 800-X	19.5	REM.	FIG8	11/8	1100	6900
FEDERAL	209A	"HI-SKOR" 800-X	20.5	REM.	FIG8	11/8	1140	7500
FEDERAL	209A	"HI-SKOR" 800-X	22.0	REM.	FIG8	11/8	1200	8400
FEDERAL	209A	"HI-SKOR" 800-X	23.5	REM.	FIG8	11/8	1260	9200
FEDERAL	209A	"HI-SKOR" 800-X	19.0	FED.	12S3	11/8	1100	7300
FEDERAL	209A	"HI-SKOR" 800-X	20.0	FED.	12S3	11/8	1140	8000
FEDERAL	209A	"HI-SKOR" 800-X	21.5	FED.	12S3	11/8	1205	9000
FEDERAL	209A	"HI-SKOR" 800-X	23.0	FED.	12S3	11/8	1260	9900
WINCHESTER	209	"HI-SKOR" 800-X	19.0	WIN.	WAA12	11/8	1090	6900
WINCHESTER	209	"HI-SKOR" 800-X	20.0	WIN.	WAA12	11/8	1140	7800
WINCHESTER	209	"HI-SKOR" 800-X	21.0	WIN.	WAA12	11/8	1190	8600
WINCHESTER	209	"HI-SKOR" 800-X	22.5	WIN.	WAA12	11/8	1250	9600
WINCHESTER	209	"HI-SKOR" 800-X	20.0	WTW	WINDJAMMER	11/8	1095	6200
WINCHESTER	209	"HI-SKOR" 800-X	21.0	WTW	WINDJAMMER	11/8	1145	6900
WINCHESTER	209	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	11/8	1190	7500
WINCHESTER	209	"HI-SKOR" 800-X	23.5	WTW	WINDJAMMER	11/8	1250	8400
WINCHESTER	209	"HI-SKOR" 800-X	19.5	CB	CB1118-12	11/8	1100	6500
WINCHESTER	209	"HI-SKOR" 800-X	20.5	CB	CB1118-12	11/8	1145	7200
WINCHESTER	209	"HI-SKOR" 800-X	21.5	CB	CB1118-12	11/8	1190	7800
WINCHESTER	209	"HI-SKOR" 800-X	23.0	CB	CB1118-12	11/8	1250	8700
WINCHESTER	209	"HI-SKOR" 800-X	19.5	REM.	FIG8	11/8	1095	6500
WINCHESTER	209	"HI-SKOR" 800-X	20.5	REM.	FIG8	11/8	1140	7200
WINCHESTER	209	"HI-SKOR" 800-X	22.0	REM.	FIG8	11/8	1205	8100

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
WINCHESTER	209	"HI-SKOR" 800-X	23.5	REM.	FIG8	11/8	1265	8900
WINCHESTER	209	"HI-SKOR" 800-X	19.0	FED.	12S3	11/8	1090	6800
WINCHESTER	209	"HI-SKOR" 800-X	20.0	FED.	12S3	11/8	1135	7500
WINCHESTER	209	"HI-SKOR" 800-X	21.5	FED.	12S3	11/8	1205	8500
WINCHESTER	209	"HI-SKOR" 800-X	23.0	FED.	12S3	11/8	1260	9600
SHELL: WINCHESTER AA								
FEDERAL	209A	"HI-SKOR" 700-X	15.0	WIN.	WAA12	11/8	1090	9100
FEDERAL	209A	"HI-SKOR" 700-X	16.0	WIN.	WAA12	11/8	1135	10000
FEDERAL	209A	"HI-SKOR" 700-X	17.5	WIN.	WAA12	11/8	1200	11300
FEDERAL	209A	"HI-SKOR" 700-X	15.0	WTW.	WINDJAMMER	11/8	1095	8200
FEDERAL	209A	"HI-SKOR" 700-X	16.0	WTW.	WINDJAMMER	11/8	1140	9000
FEDERAL	209A	"HI-SKOR" 700-X	17.5	WTW.	WINDJAMMER	11/8	1200	10100
FEDERAL	209A	"HI-SKOR" 700-X	19.0	WTW.	WINDJAMMER	11/8	1255	11000
FEDERAL	209A	"HI-SKOR" 700-X	15.0	CB.	CB1118-12	11/8	1095	8500
FEDERAL	209A	"HI-SKOR" 700-X	16.0	CB.	CB1118-12	11/8	1140	9400
FEDERAL	209A	"HI-SKOR" 700-X	17.5	CB.	CB1118-12	11/8	1200	10700
FEDERAL	209A	"HI-SKOR" 700-X	18.5	CB.	CB1118-12	11/8	1245	11500
FEDERAL	209A	"HI-SKOR" 700-X	15.5	REM.	FIG8	11/8	1100	8900
FEDERAL	209A	"HI-SKOR" 700-X	16.5	REM.	FIG8	11/8	1145	9600
FEDERAL	209A	"HI-SKOR" 700-X	18.0	REM.	FIG8	11/8	1205	10600
FEDERAL	209A	"HI-SKOR" 700-X	19.0	REM.	FIG8	11/8	1240	11200
FEDERAL	209A	"HI-SKOR" 700-X	15.5	FED.	12S3	11/8	1100	9000
FEDERAL	209A	"HI-SKOR" 700-X	16.5	FED.	12S3	11/8	1145	9900
FEDERAL	209A	"HI-SKOR" 700-X	18.0	FED.	12S3	11/8	1205	11200
REMINGTON	209P	"HI-SKOR" 700-X	15.5	WIN.	WAA12	11/8	1095	8200
REMINGTON	209P	"HI-SKOR" 700-X	17.0	WIN.	WAA12	11/8	1150	9000
REMINGTON	209P	"HI-SKOR" 700-X	18.5	WIN.	WAA12	11/8	1205	9800
REMINGTON	209P	"HI-SKOR" 700-X	20.0	WIN.	WAA12	11/8	1260	10800
REMINGTON	209P	"HI-SKOR" 700-X	16.0	WTW.	WINDJAMMER	11/8	1090	6800
REMINGTON	209P	"HI-SKOR" 700-X	17.5	WTW.	WINDJAMMER	11/8	1145	7600
REMINGTON	209P	"HI-SKOR" 700-X	19.0	WTW.	WINDJAMMER	11/8	1195	8500
REMINGTON	209P	"HI-SKOR" 700-X	20.5	WTW.	WINDJAMMER	11/8	1245	9300
REMINGTON	209P	"HI-SKOR" 700-X	15.5	CB.	CB1118-12	11/8	1090	6900
REMINGTON	209P	"HI-SKOR" 700-X	17.0	CB.	CB1118-12	11/8	1150	7900
REMINGTON	209P	"HI-SKOR" 700-X	18.0	CB.	CB1118-12	11/8	1195	8900
REMINGTON	209P	"HI-SKOR" 700-X	19.5	CB.	CB1118-12	11/8	1255	10400
REMINGTON	209P	"HI-SKOR" 700-X	16.0	REM.	FIG8	11/8	1100	7900
REMINGTON	209P	"HI-SKOR" 700-X	17.0	REM.	FIG8	11/8	1145	8400
REMINGTON	209P	"HI-SKOR" 700-X	18.5	REM.	FIG8	11/8	1205	9500
REMINGTON	209P	"HI-SKOR" 700-X	19.5	REM.	FIG8	11/8	1250	10200
REMINGTON	209P	"HI-SKOR" 700-X	15.5	FED.	12S3	11/8	1090	7800
REMINGTON	209P	"HI-SKOR" 700-X	16.5	FED.	12S3	11/8	1135	8600
REMINGTON	209P	"HI-SKOR" 700-X	18.0	FED.	12S3	11/8	1190	9700
REMINGTON	209P	"HI-SKOR" 700-X	19.5	FED.	12S3	11/8	1250	10900
WINCHESTER	209	"HI-SKOR" 700-X	15.5	WIN.	WAA12	11/8	1105	9200
WINCHESTER	209	"HI-SKOR" 700-X	16.5	WIN.	WAA12	11/8	1150	10100
WINCHESTER	209	"HI-SKOR" 700-X	17.5	WIN.	WAA12	11/8	1190	10800
WINCHESTER	209	"HI-SKOR" 700-X	15.5	WTW.	WINDJAMMER	11/8	1110	8100
WINCHESTER	209	"HI-SKOR" 700-X	16.5	WTW.	WINDJAMMER	11/8	1150	8900
WINCHESTER	209	"HI-SKOR" 700-X	17.5	WTW.	WINDJAMMER	11/8	1195	9700
WINCHESTER	209	"HI-SKOR" 700-X	19.0	WTW.	WINDJAMMER	11/8	1250	11000
WINCHESTER	209	"HI-SKOR" 700-X	15.5	CB.	CB1118-12	11/8	1105	8600
WINCHESTER	209	"HI-SKOR" 700-X	16.5	CB.	CB1118-12	11/8	1150	9500
WINCHESTER	209	"HI-SKOR" 700-X	17.5	CB.	CB1118-12	11/8	1195	10200
WINCHESTER	209	"HI-SKOR" 700-X	19.0	CB.	CB1118-12	11/8	1255	11200
WINCHESTER	209	"HI-SKOR" 700-X	15.5	REM.	FIG8	11/8	1090	8300
WINCHESTER	209	"HI-SKOR" 700-X	16.5	REM.	FIG8	11/8	1135	9000
WINCHESTER	209	"HI-SKOR" 700-X	18.0	REM.	FIG8	11/8	1200	10200
WINCHESTER	209	"HI-SKOR" 700-X	19.5	REM.	FIG8	11/8	1255	11400
WINCHESTER	209	"HI-SKOR" 700-X	15.5	FED.	12S3	11/8	1100	9500
WINCHESTER	209	"HI-SKOR" 700-X	16.5	FED.	12S3	11/8	1150	10400
WINCHESTER	209	"HI-SKOR" 700-X	17.5	FED.	12S3	11/8	1190	11100
FEDERAL	209A	PB	19.0	WIN.	WAA12	11/8	1100	7500
FEDERAL	209A	PB	20.5	WIN.	WAA12	11/8	1150	8200
FEDERAL	209A	PB	22.0	WIN.	WAA12	11/8	1205	8900

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
FEDERAL	209A	PB	23.5	WIN.	WAA12	11/8	1260	9700
FEDERAL	209A	PB	19.5	WTW.	WINDJAMMER	11/8	1100	6400
FEDERAL	209A	PB	21.0	WTW.	WINDJAMMER	11/8	1155	7000
FEDERAL	209A	PB	22.5	WTW.	WINDJAMMER	11/8	1205	7800
FEDERAL	209A	PB	24.0	WTW.	WINDJAMMER	11/8	1260	8700
FEDERAL	209A	PB	19.5	CB.	CB1118-12	11/8	1105	6600
FEDERAL	209A	PB	21.0	CB.	CB1118-12	11/8	1155	7400
FEDERAL	209A	PB	22.5	CB.	CB1118-12	11/8	1205	7900
FEDERAL	209A	PB	24.0	CB.	CB1118-12	11/8	1255	8600
FEDERAL	209A	PB	19.5	REM.	RXP12	11/8	1105	7100
FEDERAL	209A	PB	20.5	REM.	RXP12	11/8	1140	7600
FEDERAL	209A	PB	22.0	REM.	RXP12	11/8	1195	8400
FEDERAL	209A	PB	23.5	REM.	RXP12	11/8	1250	9300
FEDERAL	209A	PB	19.0	FED.	12S4	11/8	1100	7600
FEDERAL	209A	PB	20.5	FED.	12S4	11/8	1150	8300
FEDERAL	209A	PB	22.0	FED.	12S4	11/8	1200	9100
FEDERAL	209A	PB	23.5	FED.	12S4	11/8	1255	10100
REMINGTON	209P	PB	20.0	WIN.	WAA12	11/8	1100	6500
REMINGTON	209P	PB	21.0	WIN.	WAA12	11/8	1140	7100
REMINGTON	209P	PB	23.0	WIN.	WAA12	11/8	1200	7700
REMINGTON	209P	PB	24.5	WIN.	WAA12	11/8	1260	8800
REMINGTON	209P	PB	20.0	WTW.	WINDJAMMER	11/8	1095	5700
REMINGTON	209P	PB	21.5	WTW.	WINDJAMMER	11/8	1145	6400
REMINGTON	209P	PB	23.0	WTW.	WINDJAMMER	11/8	1205	7300
REMINGTON	209P	PB	24.5	WTW.	WINDJAMMER	11/8	1255	7900
REMINGTON	209P	PB	20.5	CB.	CB1118-12	11/8	1100	5500
REMINGTON	209P	PB	21.5	CB.	CB1118-12	11/8	1140	6100
REMINGTON	209P	PB	23.0	CB.	CB1118-12	11/8	1200	7100
REMINGTON	209P	PB	24.5	CB.	CB1118-12	11/8	1250	7700
REMINGTON	209P	PB	20.0	REM.	RXP12	11/8	1100	6400
REMINGTON	209P	PB	21.0	REM.	RXP12	11/8	1140	7000
REMINGTON	209P	PB	22.5	REM.	RXP12	11/8	1200	8000
REMINGTON	209P	PB	24.0	REM.	RXP12	11/8	1255	8900
REMINGTON	209P	PB	19.5	FED.	12S4	11/8	1095	6900
REMINGTON	209P	PB	20.5	FED.	12S4	11/8	1140	7700
REMINGTON	209P	PB	22.0	FED.	12S4	11/8	1195	8600
REMINGTON	209P	PB	24.0	FED.	12S4	11/8	1260	9600
WINCHESTER	209	PB	19.5	WIN.	WAA12	11/8	1095	6900
WINCHESTER	209	PB	21.0	WIN.	WAA12	11/8	1150	7700
WINCHESTER	209	PB	22.5	WIN.	WAA12	11/8	1205	8600
WINCHESTER	209	PB	24.0	WIN.	WAA12	11/8	1265	9400
WINCHESTER	209	PB	20.0	WTW.	WINDJAMMER	11/8	1100	6200
WINCHESTER	209	PB	21.5	WTW.	WINDJAMMER	11/8	1155	6900
WINCHESTER	209	PB	23.0	WTW.	WINDJAMMER	11/8	1205	7400
WINCHESTER	209	PB	24.5	WTW.	WINDJAMMER	11/8	1260	8400
WINCHESTER	209	PB	20.0	CB.	CB1118-12	11/8	1100	6300
WINCHESTER	209	PB	21.5	CB.	CB1118-12	11/8	1155	7000
WINCHESTER	209	PB	23.0	CB.	CB1118-12	11/8	1210	7900
WINCHESTER	209	PB	24.0	CB.	CB1118-12	11/8	1250	8500
WINCHESTER	209	PB	20.0	REM.	RXP12	11/8	1110	6900
WINCHESTER	209	PB	21.0	REM.	RXP12	11/8	1155	7500
WINCHESTER	209	PB	22.5	REM.	RXP12	11/8	1205	8500
WINCHESTER	209	PB	24.0	REM.	RXP12	11/8	1265	9500
WINCHESTER	209	PB	19.5	FED.	12S4	11/8	1105	7400
WINCHESTER	209	PB	20.5	FED.	12S4	11/8	1145	8000
WINCHESTER	209	PB	22.0	FED.	12S4	11/8	1200	8900
WINCHESTER	209	PB	23.5	FED.	12S4	11/8	1255	9900
FEDERAL	209A	SR7625	21.0	WIN.	WAA12	11/8	1100	6800
FEDERAL	209A	SR7625	22.5	WIN.	WAA12	11/8	1155	7400
FEDERAL	209A	SR7625	23.5	WIN.	WAA12	11/8	1190	7900
FEDERAL	209A	SR7625	25.5	WIN.	WAA12	11/8	1260	9100
FEDERAL	209A	SR7625	22.0	WTW.	WINDJAMMER	11/8	1095	5400
FEDERAL	209A	SR7625	23.5	WTW.	WINDJAMMER	11/8	1155	6400
FEDERAL	209A	SR7625	24.5	WTW.	WINDJAMMER	11/8	1200	7200
FEDERAL	209A	SR7625	25.5	WTW.	WINDJAMMER	11/8	1245	7900
FEDERAL	209A	SR7625	21.5	CB.	CB1118-12	11/8	1105	6300
FEDERAL	209A	SR7625	22.5	CB.	CB1118-12	11/8	1145	6800
FEDERAL	209A	SR7625	24.0	CB.	CB1118-12	11/8	1195	7600
FEDERAL	209A	SR7625	25.5	CB.	CB1118-12	11/8	1250	8400
FEDERAL	209A	SR7625	21.5	REM.	RXP12	11/8	1095	6100
FEDERAL	209A	SR7625	22.5	REM.	RXP12	11/8	1140	6800
FEDERAL	209A	SR7625	24.0	REM.	RXP12	11/8	1195	7700
FEDERAL	209A	SR7625	25.5	REM.	RXP12	11/8	1250	8600

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
FEDERAL	209A	SR7625	21.0	FED.	12S4	11/8	1100	6800
FEDERAL	209A	SR7625	22.5	FED.	12S4	11/8	1155	7600
FEDERAL	209A	SR7625	23.5	FED.	12S4	11/8	1195	8300
FEDERAL	209A	SR7625	25.0	FED.	12S4	11/8	1255	9300
REMINGTON	209P	SR7625	22.0	WIN.	WAA12	11/8	1110	6000
REMINGTON	209P	SR7625	23.0	WIN.	WAA12	11/8	1145	6400
REMINGTON	209P	SR7625	24.5	WIN.	WAA12	11/8	1195	7200
REMINGTON	209P	SR7625	26.0	WIN.	WAA12	11/8	1255	8000
REMINGTON	209P	SR7625	22.0	WTW.	WINDJAMMER	11/8	1095	5100
REMINGTON	209P	SR7625	23.5	WTW.	WINDJAMMER	11/8	1150	5900
REMINGTON	209P	SR7625	24.5	WTW.	WINDJAMMER	11/8	1190	6400
REMINGTON	209P	SR7625	26.0	WTW.	WINDJAMMER	11/8	1250	7200
REMINGTON	209P	SR7625	22.0	CB.	CB1118-12	11/8	1105	5600
REMINGTON	209P	SR7625	23.0	CB.	CB1118-12	11/8	1145	6300
REMINGTON	209P	SR7625	24.5	CB.	CB1118-12	11/8	1205	7300
REMINGTON	209P	SR7625	25.5	CB.	CB1118-12	11/8	1250	8000
REMINGTON	209P	SR7625	22.0	REM.	RXP12	11/8	1105	5800
REMINGTON	209P	SR7625	23.0	REM.	RXP12	11/8	1145	6300
REMINGTON	209P	SR7625	24.5	REM.	RXP12	11/8	1205	7400
REMINGTON	209P	SR7625	25.5	REM.	RXP12	11/8	1250	8200
REMINGTON	209P	SR7625	21.5	FED.	12S4	11/8	1100	6500
REMINGTON	209P	SR7625	22.5	FED.	12S4	11/8	1145	7200
REMINGTON	209P	SR7625	24.0	FED.	12S4	11/8	1205	8100
REMINGTON	209P	SR7625	25.5	FED.	12S4	11/8	1255	9100
WINCHESTER	209	SR7625	21.0	WIN.	WAA12	1 1/8	1090	6400
WINCHESTER	209	SR7625	22.5	WIN.	WAA12	1 1/8	1150	7300
WINCHESTER	209	SR7625	23.5	WIN.	WAA12	1 1/8	1190	7900
WINCHESTER	209	SR7625	25.5	WIN.	WAA12	1 1/8	1265	9600
WINCHESTER	209	SR7625	22.0	WTW.	WINDJAMMER	1 1/8	1105	5700
WINCHESTER	209	SR7625	23.0	WTW.	WINDJAMMER	1 1/8	1140	6200
WINCHESTER	209	SR7625	24.5	WTW.	WINDJAMMER	1 1/8	1200	6900
WINCHESTER	209	SR7625	26.0	WTW.	WINDJAMMER	1 1/8	1255	7900
WINCHESTER	209	SR7625	21.5	CB.	CB1118-12	1 1/8	1100	6000
WINCHESTER	209	SR7625	22.5	CB.	CB1118-12	1 1/8	1145	6500
WINCHESTER	209	SR7625	24.0	CB.	CB1118-12	1 1/8	1195	7300
WINCHESTER	209	SR7625	26.0	CB.	CB1118-12	1 1/8	1265	8200
WINCHESTER	209	SR7625	22.0	REM.	RXP12	1 1/8	1105	6200
WINCHESTER	209	SR7625	23.0	REM.	RXP12	1 1/8	1145	6600
WINCHESTER	209	SR7625	24.5	REM.	RXP12	1 1/8	1200	7500
WINCHESTER	209	SR7625	26.0	REM.	RXP12	1 1/8	1255	8300
WINCHESTER	209	SR7625	21.0	FED.	12S4	1 1/8	1095	6700
WINCHESTER	209	SR7625	22.5	FED.	12S4	1 1/8	1145	7500
WINCHESTER	209	SR7625	24.0	FED.	12S4	1 1/8	1200	8400
WINCHESTER	209	SR7625	25.5	FED.	12S4	1 1/8	1260	9200
CCI	209	"HI-SKOR" 800-X	20.5	WIN.	WAA12	1 1/8	1095	5800
CCI	209	"HI-SKOR" 800-X	22.0	WIN.	WAA12	1 1/8	1155	6500
CCI	209	"HI-SKOR" 800-X	23.0	WIN.	WAA12	1 1/8	1195	7000
CCI	209	"HI-SKOR" 800-X	24.5	WIN.	WAA12	1 1/8	1250	7700
CCI	209	"HI-SKOR" 800-X	21.5	WTW.	WINDJAMMER	1 1/8	1100	4800
CCI	209	"HI-SKOR" 800-X	22.5	WTW.	WINDJAMMER	1 1/8	1150	5400
CCI	209	"HI-SKOR" 800-X	24.0	WTW.	WINDJAMMER	1 1/8	1195	5800
CCI	209	"HI-SKOR" 800-X	26.0	WTW.	WINDJAMMER	1 1/8	1260	6200
CCI	209	"HI-SKOR" 800-X	21.0	CB.	CB1118-12	1 1/8	1095	5000
CCI	209	"HI-SKOR" 800-X	22.5	CB.	CB1118-12	1 1/8	1150	5400
CCI	209	"HI-SKOR" 800-X	24.0	CB.	CB1118-12	1 1/8	1200	6100
CCI	209	"HI-SKOR" 800-X	25.5	CB.	CB1118-12	1 1/8	1250	6700
CCI	209	"HI-SKOR" 800-X	21.0	REM.	FIG8	1 1/8	1095	5200
CCI	209	"HI-SKOR" 800-X	22.0	REM.	FIG8	1 1/8	1135	5700
CCI	209	"HI-SKOR" 800-X	23.5	REM.	FIG8	1 1/8	1195	6300
CCI	209	"HI-SKOR" 800-X	25.5	REM.	FIG8	1 1/8	1260	6900
CCI	209	"HI-SKOR" 800-X	20.5	FED.	12S3	1 1/8	1090	5800
CCI	209	"HI-SKOR" 800-X	22.0	FED.	12S3	1 1/8	1150	6400
CCI	209	"HI-SKOR" 800-X	23.0	FED.	12S3	1 1/8	1190	6800
CCI	209	"HI-SKOR" 800-X	24.5	FED.	12S3	1 1/8	1255	7800

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE 2¾ INCH 1 1/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
FEDERAL	209A	"HI-SKOR" 800-X	20.0	WIN.	WAA12	1 1/8	1105	6600
FEDERAL	209A	"HI-SKOR" 800-X	21.0	WIN.	WAA12	1 1/8	1140	7000
FEDERAL	209A	"HI-SKOR" 800-X	22.5	WIN.	WAA12	1 1/8	1200	7800
FEDERAL	209A	"HI-SKOR" 800-X	24.0	WIN.	WAA12	1 1/8	1260	8600
FEDERAL	209A	"HI-SKOR" 800-X	21.0	WTW	WINDJAMMER	1 1/8	1105	5100
FEDERAL	209A	"HI-SKOR" 800-X	22.0	WTW	WINDJAMMER	1 1/8	1150	5800
FEDERAL	209A	"HI-SKOR" 800-X	23.0	WTW	WINDJAMMER	1 1/8	1195	6500
FEDERAL	209A	"HI-SKOR" 800-X	24.5	WTW	WINDJAMMER	1 1/8	1265	7600
FEDERAL	209A	"HI-SKOR" 800-X	20.5	CB	CB1118-2	1 1/8	1095	5600
FEDERAL	209A	"HI-SKOR" 800-X	22.0	CB	CB1118-2	1 1/8	1155	6300
FEDERAL	209A	"HI-SKOR" 800-X	23.0	CB	CB1118-2	1 1/8	1195	6800
FEDERAL	209A	"HI-SKOR" 800-X	24.5	CB	CB1118-2	1 1/8	1250	7500
FEDERAL	209A	"HI-SKOR" 800-X	20.5	REM.	FIG8	1 1/8	1090	5200
FEDERAL	209A	"HI-SKOR" 800-X	21.5	REM.	FIG8	1 1/8	1135	5700
FEDERAL	209A	"HI-SKOR" 800-X	23.0	REM.	FIG8	1 1/8	1200	6700
FEDERAL	209A	"HI-SKOR" 800-X	24.5	REM.	RIG8	1 1/8	1260	7700
FEDERAL	209A	"HI-SKOR" 800-X	19.5	FED.	12S3	1 1/8	1095	6400
FEDERAL	209A	"HI-SKOR" 800-X	21.0	FED.	12S3	1 1/8	1150	7100
FEDERAL	209A	"HI-SKOR" 800-X	22.5	FED.	12S3	1 1/8	1200	7800
FEDERAL	209A	"HI-SKOR" 800-X	24.0	FED.	12S3	1 1/8	1255	8500
WINCHESTER	209	"HI-SKOR" 800-X	20.0	WIN.	WAA12	1 1/8	1100	6600
WINCHESTER	209	"HI-SKOR" 800-X	21.0	WIN.	WAA12	1 1/8	1145	7200
WINCHESTER	209	"HI-SKOR" 800-X	22.0	WIN.	WAA12	1 1/8	1190	7800
WINCHESTER	209	"HI-SKOR" 800-X	24.0	WIN.	WAA12	1 1/8	1265	8800
WINCHESTER	209	"HI-SKOR" 800-X	20.5	WTW	WINDJAMMER	1 1/8	1095	5400
WINCHESTER	209	"HI-SKOR" 800-X	21.5	WTW	WINDJAMMER	1 1/8	1145	6000
WINCHESTER	209	"HI-SKOR" 800-X	22.5	WTW	WINDJAMMER	1 1/8	1190	6700
WINCHESTER	209	"HI-SKOR" 800-X	24.0	WTW	WINDJAMMER	1 1/8	1260	7700
WINCHESTER	209	"HI-SKOR" 800-X	20.0	CB	CB1118-12	1 1/8	1095	5800
WINCHESTER	209	"HI-SKOR" 800-X	21.5	CB	CB1118-12	1 1/8	1150	6500
WINCHESTER	209	"HI-SKOR" 800-X	23.0	CB	CB1118-12	1 1/8	1205	7100
WINCHESTER	209	"HI-SKOR" 800-X	24.5	CB	CB1118-12	1 1/8	1260	7800
WINCHESTER	209	"HI-SKOR" 800-X	20.0	REM.	FIG8	1 1/8	1105	6100
WINCHESTER	209	"HI-SKOR" 800-X	21.0	REM.	FIG8	1 1/8	1150	6600
WINCHESTER	209	"HI-SKOR" 800-X	22.5	REM.	FIG8	1 1/8	1195	7000
WINCHESTER	209	"HI-SKOR" 800-X	24.5	REM.	FIG8	1 1/8	1255	7700
WINCHESTER	209	"HI-SKOR" 800-X	20.0	FED.	12S3	1 1/8	1100	6500
WINCHESTER	209	"HI-SKOR" 800-X	21.5	FED.	12S3	1 1/8	1155	7100
WINCHESTER	209	"HI-SKOR" 800-X	22.5	FED.	12S3	1 1/8	1195	7600
WINCHESTER	209	"HI-SKOR" 800-X	24.0	FED.	12S3	1 1/8	1250	8400

20 GAUGE 2¾ INCH 7/8 OUNCE LOADS

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC TARGET/HUNTING								
FEDERAL	209A	"HI-SKOR" 700-X	14.5	WIN.	WAA20	7/8	1210	11700
FEDERAL	209A	"HI-SKOR" 700-X	14.5	WTW	WINDJAMMER	7/8	1210	11800
FEDERAL	209A	"HI-SKOR" 700-X	14.0	CB.	CB1078-20	7/8	1190	11400
FEDERAL	209A	"HI-SKOR" 700-X	14.5	REM.	RXP 20	7/8	1210	11500
FEDERAL	209A	"HI-SKOR" 700-X	14.0	FED.	20S1	7/8	1190	11900
REMINGTON	209P	"HI-SKOR" 700-X	14.5	WIN.	WAA20	7/8	1210	11200
REMINGTON	209P	"HI-SKOR" 700-X	14.5	WTW	WINDJAMMER	7/8	1205	11400
REMINGTON	209P	"HI-SKOR" 700-X	14.5	CB.	CB1078-20	7/8	1205	11300
REMINGTON	209P	"HI-SKOR" 700-X	15.0	REM.	RXP 20	7/8	1215	11100
REMINGTON	209P	"HI-SKOR" 700-X	14.5	FED.	20S1	7/8	1205	11600
WINCHESTER	209	"HI-SKOR" 700-X	14.5	WIN.	WAA20	7/8	1210	11200
WINCHESTER	209	"HI-SKOR" 700-X	14.5	WTW	WINDJAMMER	7/8	1205	11200
WINCHESTER	209	"HI-SKOR" 700-X	14.0	CB.	CB1078-20	7/8	1190	11000
WINCHESTER	209	"HI-SKOR" 700-X	14.5	REM.	RXP 20	7/8	1205	11000
WINCHESTER	209	"HI-SKOR" 700-X	14.5	FED.	20S1	7/8	1210	11800
FEDERAL	209A	PB	17.5	WIN.	WAA20	7/8	1200	9400
FEDERAL	209A	PB	17.5	WTW	WINDJAMMER	7/8	1200	9500
FEDERAL	209A	PB	17.0	CB.	CB1078-20	7/8	1195	9800
FEDERAL	209A	PB	17.5	REM.	RXP 20	7/8	1205	9300
FEDERAL	209A	PB	17.5	FED.	20S1	7/8	1210	10000

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

20 GAUGE 2¾ INCH 7/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC TARGET/HUNTING								
REMINGTON	209P	PB	17.5	WIN.	WAA20	7/8	1200	9300
REMINGTON	209P	PB	18.0	WTW	WINDJAMMER	7/8	1210	9500
REMINGTON	209P	PB	17.5	CB.	CB1078-20	7/8	1200	9300
REMINGTON	209P	PB	17.5	REM.	RXP 20	7/8	1200	8900
REMINGTON	209P	PB	17.5	FED.	20S1	7/8	1200	9400
WINCHESTER	209	PB	17.5	WIN.	WAA20	7/8	1200	9400
WINCHESTER	209	PB	17.5	WTW	WINDJAMMER	7/8	1195	9500
WINCHESTER	209	PB	17.5	CB.	CB1078-20	7/8	1200	9500
WINCHESTER	209	PB	18.0	REM.	RXP 20	7/8	1195	9000
WINCHESTER	209	PB	17.5	FED.	20S1	7/8	1210	10100
FEDERAL	209A	SR7625	18.5	WIN.	WAA20	7/8	1210	9200
FEDERAL	209A	SR7625	18.5	WTW	WINDJAMMER	7/8	1190	8600
FEDERAL	209A	SR7625	18.5	CB.	CB1078-20	7/8	1210	9500
FEDERAL	209A	SR7625	19.0	REM.	RXP 20	7/8	1210	8700
FEDERAL	209A	SR7625	18.5	FED.	20S1	7/8	1195	8700
REMINGTON	209P	SR7625	18.5	WIN.	WAA20	7/8	1195	8500
REMINGTON	209P	SR7625	19.0	WTW	WINDJAMMER	7/8	1200	8300
REMINGTON	209P	SR7625	18.5	CB.	CB1078-20	7/8	1195	8600
REMINGTON	209P	SR7625	19.5	REM.	RXP 20	7/8	1205	8300
REMINGTON	209P	SR7625	19.0	FED.	20S1	7/8	1200	8300
WINCHESTER	209	SR7625	18.5	WIN.	WAA20	7/8	1195	8400
WINCHESTER	209	SR7625	19.0	WTW	WINDJAMMER	7/8	1200	9100
WINCHESTER	209	SR7625	18.5	CB.	CB1078-20	7/8	1210	9000
WINCHESTER	209	SR7625	18.5	REM.	RXP 20	7/8	1195	8500
WINCHESTER	209	SR7625	18.5	FED.	20S1	7/8	1195	8600
FEDERAL	209A	"HI-SKOR" 800-X	17.5	WIN.	WAA20	7/8	1205	8000
FEDERAL	209A	"HI-SKOR" 800-X	17.5	WTW	WINDJAMMER	7/8	1205	8000
FEDERAL	209A	"HI-SKOR" 800-X	17.0	CB.	CB1078-20	7/8	1190	7800
FEDERAL	209A	"HI-SKOR" 800-X	17.5	REM.	RXP 20	7/8	1200	7600
FEDERAL	209A	"HI-SKOR" 800-X	17.0	FED.	20S1	7/8	1190	8200
REMINGTON	209P	"HI-SKOR" 800-X	17.5	WIN.	WAA20	7/8	1200	7600
REMINGTON	209P	"HI-SKOR" 800-X	17.0	WTW	WINDJAMMER	7/8	1195	7300
REMINGTON	209P	"HI-SKOR" 800-X	17.5	CB.	CB1078-20	7/8	1205	7900
REMINGTON	209P	"HI-SKOR" 800-X	18.0	REM.	RXP 20	7/8	1210	7600
REMINGTON	209P	"HI-SKOR" 800-X	17.5	FED.	20S1	7/8	1195	7900
WINCHESTER	209	"HI-SKOR" 800-X	17.5	WIN.	WAA20	7/8	1210	8100
WINCHESTER	209	"HI-SKOR" 800-X	17.5	WTW	WINDJAMMER	7/8	1200	8000
WINCHESTER	209	"HI-SKOR" 800-X	17.0	CB.	CB1078-20	7/8	1195	8100
WINCHESTER	209	"HI-SKOR" 800-X	17.5	REM.	RXP 20	7/8	1210	8000
WINCHESTER	209	"HI-SKOR" 800-X	17.5	FED.	20S1	7/8	1200	8300
FEDERAL	209A	SR4756	20.5	WIN.	WAA20F1	7/8	1205	8500
FEDERAL	209A	SR4756	20.5	WTW	WINDJAMMER	7/8	1210	8700
FEDERAL	209A	SR4756	21.0	REM.	RXP 20	7/8	1200	7800
FEDERAL	209A	SR4756	20.5	FED.	20S1	7/8	1210	8700
REMINGTON	209P	SR4756	21.5	WIN.	WAA20F1	7/8	1200	7900
REMINGTON	209P	SR4756	21.5	WTW	WINDJAMMER	7/8	1200	7900
REMINGTON	209P	SR4756	21.5	REM.	RXP 20	7/8	1180	7000
REMINGTON	209P	SR4756	21.5	FED.	20S1	7/8	1205	7600
WINCHESTER	209	SR4756	20.5	WIN.	WAA20F1	7/8	1195	8200
WINCHESTER	209	SR4756	20.5	WTW	WINDJAMMER	7/8	1195	8300
WINCHESTER	209	SR4756	21.0	REM.	RXP 20	7/8	1205	7900
WINCHESTER	209	SR4756	20.5	FED.	20S1	7/8	1205	8500
SHELL: REMINGTON PREMIER (RTL)								
FEDERAL	209A	PB	15.5	WTW	WINDJAMMER	7/8	1185	11900
FEDERAL	209A	PB	16.0	REM.	RXP 20	7/8	1195	11600
FEDERAL	209A	PB	15.0	REM.	20S1	7/8	1160	11900
FEDERAL	209A	PB	16.0	WIN.	WAA20F1	7/8	1210	11900

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

20 GAUGE 2¾ INCH 7/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
REMINGTON	209P	PB	16.0	WTW	WINDJAMMER	7/8	1210	11700
REMINGTON	209P	PB	16.0	CB.	CB1078-20	7/8	1195	11800
REMINGTON	209P	PB	16.0	REM.	RXP 20	7/8	1195	11000
REMINGTON	209P	PB	15.5	FED.	20S1	7/8	1185	11800
REMINGTON	209P	PB	16.0	WIN.	WAA20F1	7/8	1195	11400
WINCHESTER	209	PB	16.0	WTW	WINDJAMMER	7/8	1200	11700
WINCHESTER	209	PB	16.0	CB.	CB1078-20	7/8	1195	11700
WINCHESTER	209	PB	16.0	REM.	RXP 20	7/8	1190	11100
WINCHESTER	209	PB	16.0	WIN.	WAA20F1	7/8	1190	11100
FEDERAL	209A	SR7625	16.5	WIN.	WAA20	7/8	1205	12000
FEDERAL	209A	SR7625	16.5	WTW	WINDJAMMER	7/8	1200	11400
FEDERAL	209A	SR7625	16.5	CB.	CB1078-20	7/8	1195	11400
FEDERAL	209A	SR7625	17.0	REM.	RXP 20	7/8	1210	11000
FEDERAL	209A	SR7625	16.5	FED.	20S1	7/8	1190	12000
REMINGTON	209P	SR7625	17.0	WIN.	WAA20	7/8	1205	11000
REMINGTON	209P	SR7625	17.0	WTW	WINDJAMMER	7/8	1210	11000
REMINGTON	209P	SR7625	17.0	CB.	CB1078-20	7/8	1205	11000
REMINGTON	209P	SR7625	17.0	REM.	RXP 20	7/8	1190	10100
REMINGTON	209P	SR7625	17.0	FED.	20S1	7/8	1195	11100
WINCHESTER	209	SR7625	17.0	WIN.	WAA20	7/8	1200	10900
WINCHESTER	209	SR7625	17.0	WTW	WINDJAMMER	7/8	1200	10800
WINCHESTER	209	SR7625	17.0	CB.	CB1078-20	7/8	1205	11100
WINCHESTER	209	SR7625	17.0	REM.	RXP 20	7/8	1195	10300
WINCHESTER	209	SR7625	17.0	FED.	20S1	7/8	1210	11800
FEDERAL	209A	"HI-SKOR" 800-X	16.0	WIN.	WAA20	7/8	1195	9300
FEDERAL	209A	"HI-SKOR" 800-X	16.0	WTW	WINDJAMMER	7/8	1200	9500
FEDERAL	209A	"HI-SKOR" 800-X	16.0	CB.	CB1078-20	7/8	1215	9900
FEDERAL	209A	"HI-SKOR" 800-X	16.0	REM.	RXP 20	7/8	1190	9100
FEDERAL	209A	"HI-SKOR" 800-X	16.0	FED.	20S1	7/8	1210	10000
REMINGTON	209P	"HI-SKOR" 800-X	16.5	WIN.	WAA20	7/8	1205	9100
REMINGTON	209P	"HI-SKOR" 800-X	16.5	WTW	WINDJAMMER	7/8	1210	9500
REMINGTON	209P	"HI-SKOR" 800-X	16.0	CB.	CB1078-20	7/8	1205	9500
REMINGTON	209P	"HI-SKOR" 800-X	16.5	REM.	RXP 20	7/8	1200	9100
REMINGTON	209P	"HI-SKOR" 800-X	16.0	FED.	20S1	7/8	1195	9600
WINCHESTER	209	"HI-SKOR" 800-X	16.0	WIN.	WAA20	7/8	1190	9300
WINCHESTER	209	"HI-SKOR" 800-X	16.0	WTW	WINDJAMMER	7/8	1190	9500
WINCHESTER	209	"HI-SKOR" 800-X	16.0	CB.	CB1078-20	7/8	1205	9600
WINCHESTER	209	"HI-SKOR" 800-X	16.5	REM.	RXP 20	7/8	1210	9500
WINCHESTER	209	"HI-SKOR" 800-X	16.0	FED.	20S1	7/8	1200	9600
FEDERAL	209A	SR4756	17.5	WIN.	WAA20F1	7/8	1190	10200
FEDERAL	209A	SR4756	17.5	REM.	SP20	7/8	1195	10600
REMINGTON	209P	SR4756	18.5	WIN.	WAA20F1	7/8	1195	9500
REMINGTON	209P	SR4756	18.5	REM.	SP20	7/8	1205	10200
WINCHESTER	209	SR4756	19.0	WIN.	WAA20F1	7/8	1205	9600
WINCHESTER	209	SR4756	18.5	REM.	SP20	7/8	1205	10300
SHELL: WINCHESTER AA								
REMINGTON	209P	"HI-SKOR" 700-X	13.0	REM.	RXP 20	7/8	1160	11800
FEDERAL	209A	PB	15.5	WIN.	WAA20	7/8	1180	11700
FEDERAL	209A	PB	15.5	WTW	WINDJAMMER	7/8	1185	11900
FEDERAL	209A	PB	16.0	REM.	RXP 20	7/8	1205	11900
FEDERAL	209A	PB	15.0	FED.	20S1	7/8	1160	11900
REMINGTON	209P	PB	16.0	WIN.	WAA20	7/8	1200	11600
REMINGTON	209P	PB	16.0	WTW	WINDJAMMER	7/8	1200	11300
REMINGTON	209P	PB	16.0	CB.	CB1078-20	7/8	1200	11900
REMINGTON	209P	PB	16.0	REM.	RXP 20	7/8	1195	10900
REMINGTON	209P	PB	15.5	FED.	20S1	7/8	1175	11600
WINCHESTER	209	PB	16.0	WIN.	WAA20	7/8	1195	11700
WINCHESTER	209	PB	16.5	WTW	WINDJAMMER	7/8	1200	11800
WINCHESTER	209	PB	16.0	REM.	RXP 20	7/8	1195	11400
WINCHESTER	209	PB	15.5	FED.	20S1	7/8	1175	11800

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

20 GAUGE 2¾ INCH 7/8 OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER AA								
FEDERAL	209A	SR7625	16.5	WIN.	WAA20	7/8	1205	11700
FEDERAL	209A	SR7625	16.5	WTW	WINDJAMMER	7/8	1200	11900
FEDERAL	209A	SR7625	16.5	CB.	CB1078-20	7/8	1195	11700
FEDERAL	209A	SR7625	17.0	REM.	RXP 20	7/8	1200	10800
FEDERAL	209A	SR7625	16.5	FED.	20S1	7/8	1190	11700
REMINGTON	209P	SR7625	17.0	WIN.	WAA20	7/8	1200	10900
REMINGTON	209P	SR7625	17.5	WTW	WINDJAMMER	7/8	1210	10300
REMINGTON	209P	SR7625	17.0	CB.	CB1078-20	7/8	1210	11300
REMINGTON	209P	SR7625	17.0	REM.	RXP 20	7/8	1190	10100
REMINGTON	209P	SR7625	16.5	FED.	20S1	7/8	1185	11100
WINCHESTER	209	SR7625	17.0	WIN.	WAA20	7/8	1205	10600
WINCHESTER	209	SR7625	17.0	WTW	WINDJAMMER	7/8	1205	10900
WINCHESTER	209	SR7625	16.5	CB.	CB1078-20	7/8	1190	10800
WINCHESTER	209	SR7625	17.0	REM.	RXP 20	7/8	1210	10600
WINCHESTER	209	SR7625	16.5	FED.	20S1	7/8	1195	11700
FEDERAL	209A	"HI-SKOR" 800-X	16.5	WIN.	WAA20	7/8	1205	9400
FEDERAL	209A	"HI-SKOR" 800-X	16.5	WTW	WINDJAMMER	7/8	1215	10100
FEDERAL	209A	"HI-SKOR" 800-X	16.0	CB.	CB1078-20	7/8	1190	9400
FEDERAL	209A	"HI-SKOR" 800-X	16.5	REM.	RXP 20	7/8	1200	8800
FEDERAL	209A	"HI-SKOR" 800-X	16.0	FED.	20S1	7/8	1190	9700
REMINGTON	209P	"HI-SKOR" 800-X	16.5	WIN.	WAA20	7/8	1210	9300
REMINGTON	209P	"HI-SKOR" 800-X	16.5	WTW	WINDJAMMER	7/8	1190	8400
REMINGTON	209P	"HI-SKOR" 800-X	16.5	CB.	CB1078-20	7/8	1195	8400
REMINGTON	209P	"HI-SKOR" 800-X	16.5	REM.	RXP 20	7/8	1190	7500
REMINGTON	209P	"HI-SKOR" 800-X	16.5	FED.	20S1	7/8	1190	8200
WINCHESTER	209	"HI-SKOR" 800-X	16.5	WIN.	WAA20	7/8	1205	9900
WINCHESTER	209	"HI-SKOR" 800-X	16.5	WTW	WINDJAMMER	7/8	1200	10300
WINCHESTER	209	"HI-SKOR" 800-X	16.0	CB.	CB1078-20	7/8	1190	9600
WINCHESTER	209	"HI-SKOR" 800-X	16.5	REM.	RXP 20	7/8	1210	9400
WINCHESTER	209	"HI-SKOR" 800-X	16.0	FED.	20S1	7/8	1190	9600
FEDERAL	209A	SR4756	18.0	WIN.	WAA20F1	7/8	1190	10000
FEDERAL	209A	SR4756	18.5	WTW	WINDJAMMER	7/8	1185	10000
FEDERAL	209A	SR4756	18.0	CB.	CB1078-20	7/8	1195	10300
FEDERAL	209A	SR4756	18.5	REM.	SP20	7/8	1215	10700
FEDERAL	209A	SR4756	18.0	FED.	20S1	7/8	1190	10600
REMINGTON	209P	SR4756	18.5	WIN.	WAA20F1	7/8	1200	9800
REMINGTON	209P	SR4756	18.5	CB.	CB1078-20	7/8	1200	10000
REMINGTON	209P	SR4756	19.0	REM.	SP20	7/8	1210	9700
REMINGTON	209P	SR4756	18.5	FED.	20S1	7/8	1190	10100
WINCHESTER	209	SR4756	18.5	WIN.	WAA20F1	7/8	1200	9900
WINCHESTER	209	SR4756	18.5	WTW	WINDJAMMER	7/8	1195	9900
WINCHESTER	209	SR4756	18.0	CB.	CB1078-20	7/8	1180	9700
WINCHESTER	209	SR4756	18.5	REM.	SP20	7/8	1200	9900
WINCHESTER	209	SR4756	18.0	FED.	20S1	7/8	1205	10700

28 GAUGE 2¾ INCH ¾ OUNCE LOADS

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC TARGET/HUNTING								
FEDERAL	209A	PB	13.0	WIN.	WAA28	3/4	1165	12400
FEDERAL	209A	PB	13.0	CB.	CB-1034-28	3/4	1165	12100
FEDERAL	209A	PB	13.0	REM.	PT28	3/4	1160	12300
REMINGTON	209P	PB	14.5	WIN.	WAA28	3/4	1205	11400
REMINGTON	209P	PB	14.5	PATCTL.	PC-28	3/4	1200	11500
REMINGTON	209P	PB	14.5	REM.	PT28	3/4	1200	11700
REMINGTON	209P	PB	14.0	FED.	28S1	3/4	1190	12200

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

28 GAUGE 2¾ INCH ¾ OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL PLASTIC TARGET/HUNTING								
WINCHESTER	209	PB	14.5	WIN.	WAA28	3/4	1215	11900
WINCHESTER	209	PB	14.5	PATCTL.	PC-28	3/4	1210	12000
WINCHESTER	209	PB	14.5	REM.	PT28	3/4	1205	12100
WINCHESTER	209	PB	14.0	FED.	28S1	3/4	1185	12500
FEDERAL	209A	SR7625	14.5	WIN.	WAA28	3/4	1215	12300
FEDERAL	209A	SR7625	14.0	PATCTL.	PC-28	3/4	1195	11900
FEDERAL	209A	SR7625	14.0	CB.	CB-1034-28	3/4	1195	12000
FEDERAL	209A	SR7625	15.5	REM.	PT28	3/4	1195	11800
FEDERAL	209A	SR7625	14.0	FED.	28S1	3/4	1185	12000
REMINGTON	209P	SR7625	14.5	WIN.	WAA28	3/4	1185	10500
REMINGTON	209P	SR7625	15.0	PATCTL.	PC-28	3/4	1205	10100
REMINGTON	209P	SR7625	15.0	REM.	PT28	3/4	1190	10200
REMINGTON	209P	SR7625	14.5	FED.	28S1	3/4	1190	10800
WINCHESTER	209	SR7625	14.5	WIN.	WAA28	3/4	1185	10800
WINCHESTER	209	SR7625	15.0	PATCTL.	PC-28	3/4	1205	10900
WINCHESTER	209	SR7625	15.0	REM.	PT28	3/4	1200	11100
WINCHESTER	209	SR7625	15.0	FED.	28S1	3/4	1205	11200
FEDERAL	209A	"HI-SKOR" 800-X	13.5	WIN.	WAA28	3/4	1195	10100
FEDERAL	209A	"HI-SKOR" 800-X	13.5	PATCTL.	PC-28	3/4	1215	10600
FEDERAL	209A	"HI-SKOR" 800-X	13.5	CB.	CB1034-28	3/4	1200	10000
FEDERAL	209A	"HI-SKOR" 800-X	13.5	REM.	PT28	3/4	1205	10700
FEDERAL	209A	"HI-SKOR" 800-X	13.5	FED.	28S1	3/4	1205	11000
REMINGTON	209P	"HI-SKOR" 800-X	14.5	WIN.	WAA28	3/4	1210	9500
REMINGTON	209P	"HI-SKOR" 800-X	14.0	PATCTL.	PC-28	3/4	1200	9600
REMINGTON	209P	"HI-SKOR" 800-X	14.0	CB.	CB1034-28	3/4	1205	9800
REMINGTON	209P	"HI-SKOR" 800-X	14.0	REM.	PT28	3/4	1195	9900
REMINGTON	209P	"HI-SKOR" 800-X	14.0	FED.	28S1	3/4	1210	10400
WINCHESTER	209	"HI-SKOR" 800-X	14.0	WIN.	WAA28	3/4	1210	10000
WINCHESTER	209	"HI-SKOR" 800-X	13.5	PATCTL.	PC-28	3/4	1190	9900
WINCHESTER	209	"HI-SKOR" 800-X	13.5	CB.	CB1034-28	3/4	1190	9800
WINCHESTER	209	"HI-SKOR" 800-X	13.5	REM.	PT28	3/4	1190	10100
WINCHESTER	209	"HI-SKOR" 800-X	13.5	FED.	28S1	3/4	1200	10500
FEDERAL	209A	SR4756	15.5	PATCTL.	PC-28	3/4	1210	11400
FEDERAL	209A	SR4756	15.5	REM.	PT28	3/4	1200	11400
FEDERAL	209A	SR4756	15.5	FED.	28S1	3/4	1205	11900
REMINGTON	209P	SR4756	16.0	PATCTL.	PC-28	3/4	1185	9600
REMINGTON	209P	SR4756	17.0	REM.	PT28	3/4	1170	10300
REMINGTON	209P	SR4756	16.5	FED.	28S1	3/4	1195	9800
WINCHESTER	209	SR4756	16.0	PATCTL.	PC-28	3/4	1200	10300
WINCHESTER	209	SR4756	16.0	REM.	PT28	3/4	1190	10500
WINCHESTER	209	SR4756	16.0	FED.	28S1	3/4	1195	10600
SHELL: REMINGTON PREMIER (RTL)								
REMINGTON	209P	PB	13.5	WIN.	WAA28	3/4	1205	12300
REMINGTON	209P	PB	13.0	PATCTL.	PC-28	3/4	1185	12100
REMINGTON	209P	PB	13.0	REM.	PT28	3/4	1175	12500
REMINGTON	209P	SR7625	14.0	WIN.	WAA28	3/4	1205	11800
REMINGTON	209P	SR7625	14.0	PATCTL.	PC-28	3/4	1200	11700
REMINGTON	209P	SR7625	13.5	REM.	PT28	3/4	1190	12400
REMINGTON	209P	SR7625	13.5	FED.	28S1	3/4	1185	12400
WINCHESTER	209	SR7625	14.0	WIN.	WAA28	3/4	1210	12200
WINCHESTER	209	SR7625	14.0	PATCTL.	PC-28	3/4	1210	12200
WINCHESTER	209	SR7625	14.0	REM.	PT28	3/4	1200	12500
FEDERAL	209A	"HI-SKOR" 800-X	13.0	WIN.	WAA28	3/4	1195	11000
FEDERAL	209A	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1210	11400
FEDERAL	209A	"HI-SKOR" 800-X	13.0	CB.	CB1034-28	3/4	1200	10800
FEDERAL	209A	"HI-SKOR" 800-X	13.0	REM.	PT28	3/4	1205	11400
FEDERAL	209A	"HI-SKOR" 800-X	13.0	FED.	28S1	3/4	1205	11700
REMINGTON	209P	"HI-SKOR" 800-X	13.5	WIN.	WAA28	3/4	1205	10300
REMINGTON	209P	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1190	10300
REMINGTON	209P	"HI-SKOR" 800-X	13.5	CB.	CB1034-28	3/4	1205	10300
REMINGTON	209P	"HI-SKOR" 800-X	13.5	REM.	PT28	3/4	1205	10700
REMINGTON	209P	"HI-SKOR" 800-X	13.5	FED.	28S1	3/4	1215	11600

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

28 GAUGE 2¾ INCH ¾ OUNCE LOADS (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON PREMIER (RTL)								
WINCHESTER	209	"HI-SKOR" 800-X	13.0	WIN.	WAA28	3/4	1185	10400
WINCHESTER	209	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1185	10300
WINCHESTER	209	"HI-SKOR" 800-X	13.5	CB.	CB1034-28	3/4	1215	10800
WINCHESTER	209	"HI-SKOR" 800-X	13.5	REM.	PT28	3/4	1210	11100
WINCHESTER	209	"HI-SKOR" 800-X	13.0	FED.	28S1	3/4	1195	11300
FEDERAL	209A	SR4756	14.5	PATCTL.	PC-28	3/4	1200	12200
FEDERAL	209A	SR4756	14.0	REM.	PT28	3/4	1185	12500
FEDERAL	209A	SR4756	14.0	FED.	28S1	3/4	1175	12300
REMINGTON	209P	SR4756	15.0	PATCTL.	PC-28	3/4	1165	9900
REMINGTON	209P	SR4756	14.0	FED.	28S1	3/4	1140	10300
WINCHESTER	209	SR4756	15.0	PATCTL.	PC-28	3/4	1200	11200
WINCHESTER	209	SR4756	14.0	REM.	PT28	3/4	1155	11000
WINCHESTER	209	SR4756	14.0	FED.	28S1	3/4	1160	11500
SHELL: WINCHESTER COMPRESSION FORMED "DOUBLE-A" & "SUPER-X"								
REMINGTON	209P	SR7625	14.0	WIN.	WAA28	3/4	1205	12300
REMINGTON	209P	SR7625	13.5	PATCTL.	PC-28	3/4	1170	12000
REMINGTON	209P	SR7625	14.0	CB.	CB1034-28	3/4	1190	12300
REMINGTON	209P	SR7625	13.5	FED.	28S1	3/4	1170	12400
FEDERAL	209A	"HI-SKOR" 800-X	12.5	WIN.	WAA28	3/4	1185	11600
FEDERAL	209A	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1210	12300
FEDERAL	209A	"HI-SKOR" 800-X	12.5	CB.	CB1034-28	3/4	1185	11700
FEDERAL	209A	"HI-SKOR" 800-X	12.0	FED.	28S1	3/4	1150	12000
REMINGTON	209P	"HI-SKOR" 800-X	14.0	WIN.	WAA28	3/4	1200	9700
REMINGTON	209P	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1200	11400
REMINGTON	209P	"HI-SKOR" 800-X	13.5	CB.	CB1034-28	3/4	1200	10200
REMINGTON	209P	"HI-SKOR" 800-X	13.5	FED.	28S1	3/4	1205	11500
WINCHESTER	209	"HI-SKOR" 800-X	13.0	WIN.	WAA28	3/4	1195	11400
WINCHESTER	209	"HI-SKOR" 800-X	13.0	PATCTL.	PC-28	3/4	1205	12000
WINCHESTER	209	"HI-SKOR" 800-X	13.0	CB.	CB1034-28	3/4	1190	11200
WINCHESTER	209	"HI-SKOR" 800-X	12.5	FED.	28S1	3/4	1175	12200
REMINGTON	209P	SR4756	14.0	WIN.	WAA28	3/4	1150	11500
REMINGTON	209P	SR4756	14.5	PATCTL.	PC-28	3/4	1185	12200
REMINGTON	209P	SR4756	14.0	CB.	CB1034-28	3/4	1165	12000
WINCHESTER	209	SR4756	14.0	WIN.	WAA28	3/4	1150	11400
WINCHESTER	209	SR4756	14.5	PATCTL.	PC-28	3/4	1190	12000
WINCHESTER	209	SR4756	14.0	CB.	CB1034-28	3/4	1170	12200
WINCHESTER	209	SR4756	14.0	FED.	28S1	3/4	1155	12500

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

.410 BORE 2½ INCH ½ OUNCE LOADS

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 2 1/2" PLASTIC TARGET/HUNTING								
FEDERAL	209A	IMR4227	17.0	TRICO	NO. 4*	1/2	1165	12000
FEDERAL	209A	IMR4227	17.0	PATCTL.	PC-410	1/2	1170	12500
FEDERAL	209A	IMR4227	17.0	REM.	SP410	1/2	1155	12000
FEDERAL	209A	IMR4227	17.5	CB.	CB1050-41	1/2	1190	12200
FEDERAL	209A	IMR4227	17.5	FED.	410SC	1/2	1195	12200
REMINGTON	209P	IMR4227	18.5	REM.	SP410	1/2	1180	10700
WINCHESTER	209	IMR4227	18.0	TRICO	NO. 4*	1/2	1170	11400
WINCHESTER	209	IMR4227	18.5	PATCTL.	PC-410	1/2	1215	11800
WINCHESTER	209	IMR4227	18.0	REM.	SP410	1/2	1200	12000
WINCHESTER	209	IMR4227	18.0	CB.	CB1050-41	1/2	1165	11300
SHELL: REMINGTON 2 1/2" EXPRESS								
FEDERAL	209A	IMR4227	17.0	TRICO	NO. 4*	1/2	1160	11900
FEDERAL	209A	IMR4227	17.5	PATCTL.	PC-410	1/2	1195	12500
FEDERAL	209A	IMR4227	18.0	CB.	CB1050-41	1/2	1210	12500
FEDERAL	209A	IMR4227	17.5	FED.	410SC	1/2	1195	12400
WINCHESTER	209	IMR4227	17.5	PATCTL.	PC-410	1/2	1160	11200
WINCHESTER	209	IMR4227	18.0	CB.	CB1050-41	1/2	1160	11000
SHELL: WINCHESTER COMPRESSION FORMED "DOUBLE-A" & "SUPER-X"								
REMINGTON	209P	IMR4227	17.0	TRICO	NO. 4*	1/2	1145	11600
WINCHESTER	209	IMR4227	17.0	TRICO	NO. 4*	1/2	1160	12400
WINCHESTER	209	IMR4227	16.5	PATCTL.	PC-410	1/2	1140	12300

SHOTSHELL FIELD 10 GAUGE 3½ INCH RELOADING DATA

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 3 1/2" MAGNUM PAPER BASEWAD								
FEDERAL	209A	"HI-SKOR" 800-X	29.0	REM	SP10+(2) 20GA 0.125" CARDS	2 1/4	1085	10700
FEDERAL	209A	SR4756	33.0	REM	SP10	2 1/4	1065	10600
FEDERAL	209A	"HI-SKOR" 800-X	32.0	REM	SP10+(4)20GA 0.125" CARDS	2	1180	10900
FEDERAL	209A	SR4756	37.0	REM	SP10+(2)20GA 0.125" CARDS	2	1175	10800
REMINGTON	209PSTS	SR4756	41.5	REM	SP10+(2)20GA 0.125" CARDS	2	1230	10800
SHELL: REMINGTON 3 1/2" NITRO MAGNUM PLASTIC BASEWAD								
REMINGTON	209PSTS	"HI-SKOR" 800-X	28.0	REM	SP10+(3)20GA 0.125" CARDS	2 1/4	1055	10800
REMINGTON	209PSTS	SR4756	34.5	REM	SP10	2 1/4	1095	10900
REMINGTON	209PSTS	SR7625	32.5	REM	SP10+(3)20GA 0.125" CARDS	2	1115	10800
REMINGTON	209PSTS	"HI-SKOR" 800-X	30.0	REM	SP10+(4)20GA 0.125" CARDS	2	1145	10900
REMINGTON	209PSTS	SR4756	39.5	REM	SP10+(2)20GA 0.125" CARDS	2	1210	10800
SHELL: WINCHESTER 3 1/2" SUPER MAGNUM PLASTIC BASEWAD								
WINCHESTER	209	"HI-SKOR" 800-X	32.0	REM	SP10	2 1/4	1135	10900
WINCHESTER	209	SR4756	37.0	REM	SP10	2 1/4	1130	11000
WINCHESTER	209	"HI-SKOR" 800-X	35.0	REM	SP10+(2)20 GA 0.125" CARDS	2	1230	10800
WINCHESTER	209	SR4756	42.0	REM	SP10+(1)20GA 0.125" CARD	2	1245	10700

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE BUCKSHOT RELOADING DATA

PRIMER		IMR POWDER		WAD COLUMN		BP	BUCKSHOT		MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SDC BUFFER (GRAINS)	NO.	SIZE OF PELLETS	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC GOLD MEDAL										
FEDERAL	209A	"HI-SKOR" 700-X	17.5	FED	12S3	20	8	00	1230	10900
FEDERAL	209A	PB	25.0	FED	12S4	20	8	00	1340	10900
FEDERAL	209A	SR7625	30.0	FED	12S4	20	8	00	1410	10800
FEDERAL	209A	"HI-SKOR" 800-X	29.0	FED	12S4	20	8	00	1465	10800
FEDERAL	209A	SR4756	37.0	WIN	WAA12R	18	8	00	1545	10900
SHELL: REMINGTON 2 3/4" NITRO 27										
REMINGTON	209PSTS	"HI-SKOR" 700-X	17.5	REM	FIG8	20	8	00	1225	10700
FEDERAL	209A	"HI-SKOR" 700-X	17.0	REM	FIG8	20	8	00	1210	10800
REMINGTON	209PSTS	PB	25.0	REM	SP12	20	8	00	1340	10600
REMINGTON	209PSTS	SR7625	30.5	REM	SP12	20	8	00	1425	10800
FEDERAL	209A	SR7625	27.0	REM	SP12	20	8	00	1360	10800
REMINGTON	209PSTS	"HI-SKOR" 800-X	30.0	REM	SP12	20	8	00	1475	10900
REMINGTON	209PSTS	SR4756	37.0	WIN	WAA12R	18	8	00	1545	11000
SHELL: WINCHESTER 2 3/4" AA										
WINCHESTER	209	"HI-SKOR" 700-X	18.0	WIN	WAA12R	20	8	00	1245	10800
WINCHESTER	209	PB	27.5	WIN	WAA12R	20	8	00	1410	10800
WINCHESTER	209	SR7625	33.0	WIN	WAA12R	20	8	00	1495	10600
FEDERAL	209A	SR7625	29.5	WIN	WAA12R	20	8	00	1430	11000
WINCHESTER	209	"HI-SKOR" 800-X	32.0	WIN	WAA12R	20	8	00	1545	10700
WINCHESTER	209	SR4756	39.5	WIN	WAA12R	18	8	00	1595	10800

12 GAUGE FIELD RELOADING DATA

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC GOLD MEDAL								
FEDERAL	209A	"HI-SKOR" 700-X	18.0	FED.	12S4	1 1/4	1165	11500
FEDERAL	209A	"HI-SKOR" 700-X	20.0	WINJ.	WINDJAMMER	1 1/4	1230	11300
FEDERAL	209A	"HI-SKOR" 700-X	19.0	REM.	FIG8	1 1/4	1200	11300
FEDERAL	209A	"HI-SKOR" 700-X	18.0	WIN.	WAA12	1 1/4	1180	11500
REMINGTON	209P	"HI-SKOR" 700-X	19.5	FED.	12S3	1 1/4	1205	11500
REMINGTON	209P	"HI-SKOR" 700-X	21.0	WINJ.	WINDJAMMER	1 1/4	1260	11500
REMINGTON	209P	"HI-SKOR" 700-X	21.0	REM.	FIG8	1 1/4	1255	11500
REMINGTON	209P	"HI-SKOR" 700-X	19.5	WIN.	WAA12	1 1/4	1215	11400
WINCHESTER	209	"HI-SKOR" 700-X	19.0	FED.	12S3	1 1/4	1195	11500
WINCHESTER	209	"HI-SKOR" 700-X	21.0	WINJ.	WINDJAMMER	1 1/4	1250	11500
WINCHESTER	209	"HI-SKOR" 700-X	19.5	REM.	FIG8	1 1/4	1210	11100
WINCHESTER	209	"HI-SKOR" 700-X	19.0	WIN.	WAA12	1 1/4	1200	11500
FEDERAL	209A	PB	23.5	FED.	12S4	1 1/4	1225	10500
FEDERAL	209A	PB	25.0	FED.	12S4	1 1/4	1270	11300
FEDERAL	209A	PB	25.5	REM.	FIG8	1 1/4	1270	10500
FEDERAL	209A	PB	27.0	REM.	FIG8	1 1/4	1315	11500
FEDERAL	209A	PB	25.5	CLAYB.	CB3118-12AR	1 1/4	1275	11100
FEDERAL	209A	PB	26.0	CLAYB.	CB3118-12AR	1 1/4	1295	11500
REMINGTON	209P	PB	26.5	FED.	12S4	1 1/4	1295	10000
REMINGTON	209P	PB	28.0	FED.	12S4	1 1/4	1325	11100
REMINGTON	209P	PB	27.5	REM.	SP12	1 1/4	1270	9200
REMINGTON	209P	PB	29.0	REM.	SP12	1 1/4	1330	10500
REMINGTON	209P	PB	26.5	CLAYB.	CB3118-12AR	1 1/4	1275	9600
REMINGTON	209P	PB	28.0	CLAYB.	CB3118-12AR	1 1/4	1305	10200
WINCHESTER	209	PB	26.0	FED.	12S4	1 1/4	1275	10800
WINCHESTER	209	PB	27.5	FED.	12S4	1 1/4	1320	11500
WINCHESTER	209	PB	26.5	REM.	SP12	1 1/4	1280	9800
WINCHESTER	209	PB	28.0	REM.	SP12	1 1/4	1320	10600
WINCHESTER	209	PB	26.5	CLAYB.	CB3118-12AR	1 1/4	1270	10000
WINCHESTER	209	PB	28.0	CLAYB.	CB3118-12AR	1 1/4	1330	11400

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC GOLD MEDAL								
FEDERAL	209A	SR7625	27.0	FED.	12S3	1 1/4	1270	10100
FEDERAL	209A	SR7625	29.0	FED.	12S3	1 1/4	1325	11000
FEDERAL	209A	SR2725	27.0	WIN.	WAA12	1 1/4	1275	10100
FEDERAL	209A	SR7625	28.5	WIN.	WAA12	1 1/4	1330	11400
FEDERAL	209A	SR7625	27.0	REM.	SP12	1 1/4	1280	10000
FEDERAL	209A	SR7625	28.5	REM.	SP12	1 1/4	1330	11000
FEDERAL	209A	SR7625	26.5	CLAYB.	CB3118-12AR	1 1/4	1270	10100
FEDERAL	209A	SR7625	28.0	CLAYB.	CB3118-12AR	1 1/4	1320	10800
REMINGTON	209P	SR7625	28.0	FED.	12S3	1 1/4	1270	8900
REMINGTON	209P	SR7625	30.0	FED.	12S3	1 1/4	1330	9700
REMINGTON	209P	SR7625	29.0	DINJ.	WINDJAMMER	1 1/4	1280	8300
REMINGTON	209P	SR7625	30.5	WINJ.	WINDJAMMER	1 1/4	1325	9000
REMINGTON	209P	SR7625	29.0	REM.	SP12	1 1/4	1270	8200
REMINGTON	209P	SR7625	30.5	REM.	SP12	1 1/4	1315	8900
WINCHESTER	209	SR7625	28.0	FED.	12S3	1 1/4	1270	9200
WINCHESTER	209	SR7625	30.0	FED.	12S3	1 1/4	1330	10300
WINCHESTER	209	SR7625	28.5	WINJ.	WINDJAMMER	1 1/4	1270	8300
WINCHESTER	209	SR7625	30.0	WINJ.	WINDJAMMER	1 1/4	1315	9000
WINCHESTER	209	SR7625	28.0	WIN.	WAA12	1 1/4	1270	9100
WINCHESTER	209	SR7625	29.5	WIN.	WAA12	1 1/4	1325	10200
FEDERAL	209A	SR4756	30.0	FED.	12S4	1 1/4	1285	9700
FEDERAL	209A	SR4756	31.5	FED.	12S4	1 1/4	1330	10400
FEDERAL	209A	SR4756	30.5	WIN.	WAA12R	1 1/4	1285	8900
FEDERAL	209A	SR4756	31.5	WIN.	WAA12R	1 1/4	1325	9700
FEDERAL	209A	SR4756	30.0	REM.	SP12	1 1/4	1270	9000
FEDERAL	209A	SR4756	31.5	REM.	SP12	1 1/4	1325	9800
REMINGTON	209P	SR4756	31.5	FED.	12S4	1 1/4	1220	7100
REMINGTON	209P	SR4756	33.0	FED.	12S4	1 1/4	1265	7600
REMINGTON	209P	SR4756	33.0	WIN.	WAA12R	1 1/4	1285	8000
REMINGTON	209P	SR4756	34.0	WIN.	WAA12R	1 1/4	1325	8900
REMINGTON	209P	SR4756	33.0	REM.	SP12	1 1/4	1315	7400
REMINGTON	209P	SR4756	35.0	REM.	SP12	1 1/4	1335	8300
WINCHESTER	209	SR4756	31.0	FED.	12S4	1 1/4	1280	9100
WINCHESTER	209	SR4756	32.0	FED.	12S4	1 1/4	1325	9800
WINCHESTER	209	SR4756	30.5	WIN.	WAA12R	1 1/4	1275	8400
WINCHESTER	209	SR4756	32.0	WIN.	WAA12R	1 1/4	1315	8900
WINCHESTER	209	SR4756	32.0	REM.	RP12	1 1/4	1290	8800
WINCHESTER	209	SR4756	33.0	REM.	RP12	1 1/4	1330	9400
FEDERAL	209A	"HI-SKOR" 800-X	25.0	FED.	12S4	1 1/4	1280	9500
FEDERAL	209A	"HI-SKOR" 800-X	26.5	FED.	12S4	1 1/4	1335	10400
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WIN.	WAA12	1 1/4	1285	9200
FEDERAL	209A	"HI-SKOR" 800-X	27.5	WIN.	WAA12	1 1/4	1335	10100
FEDERAL	209A	"HI-SKOR" 800-X	25.5	REM.	SP12	1 1/4	1280	9100
FEDERAL	209A	"HI-SKOR" 800-X	27.0	REM.	SP12	1 1/4	1335	9900
FEDERAL	209A	"HI-SKOR" 800-X	26.0	CLAYB.	CB3118-12AR	1 1/4	1280	8900
FEDERAL	209A	"HI-SKOR" 800-X	27.5	CLAYB.	CB3118-12AR	1 1/4	1335	9800
REMINGTON	209P	"HI-SKOR" 800-X	26.5	FED.	12S4	1 1/4	1285	8900
REMINGTON	209P	"HI-SKOR" 800-X	28.0	FED.	12S4	1 1/4	1335	9700
REMINGTON	209P	"HI-SKOR" 800-X	27.0	WIN.	WAA12	1 1/4	1275	7900
REMINGTON	209P	"HI-SKOR" 800-X	28.5	WIN.	WAA12	1 1/4	1335	9000
REMINGTON	209P	"HI-SKOR" 800-X	27.0	REM.	SP12	1 1/4	1270	7700
REMINGTON	209P	"HI-SKOR" 800-X	29.0	REM.	SP12	1 1/4	1335	8500
REMINGTON	209P	"HI-SKOR" 800-X	27.0	CLAYB.	CB3118-12AR	1 1/4	1275	7700
REMINGTON	209P	"HI-SKOR" 800-X	29.0	CLAYB.	CB3118-12AR	1 1/4	1330	8500
WINCHESTER	209	"HI-SKOR" 800-X	26.0	FED.	12S3	1 1/4	1280	8800
WINCHESTER	209	"HI-SKOR" 800-X	27.5	FED.	12S3	1 1/4	1330	9700
WINCHESTER	209	"HI-SKOR" 800-X	25.5	WIN.	WAA12	1 1/4	1265	8600
WINCHESTER	209	"HI-SKOR" 800-X	27.5	WIN.	WAA12	1 1/4	1330	9600
WINCHESTER	209	"HI-SKOR" 800-X	26.0	REM.	SP12	1 1/4	1275	8200
WINCHESTER	209	"HI-SKOR" 800-X	27.5	REM.	SP12	1 1/4	1330	9100
WINCHESTER	209	"HI-SKOR" 800-X	26.0	CLAYB.	CB3118-12AR	1 1/4	1270	8100
WINCHESTER	209	"HI-SKOR" 800-X	28.0	CLAYB.	CB3118-12AR	1 1/4	1335	9300

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC GOLD MEDAL								
FEDERAL	209A	PB	22.5	WIN.	WAA12R	1 3/8	1170	10800
FEDERAL	209A	PB	22.5	REM.	SP12	1 3/8	1160	10900
REMINGTON	209P	PB	26.5	WIN.	WAA12R	1 3/8	1255	11000
REMINGTON	209P	PB	24.5	REM.	SP12	1 3/8	1205	11000
WINCHESTER	209	PB	24.0	WIN.	WAA12R	1 3/8	1200	11000
WINCHESTER	209	PB	23.5	REM.	SP12	1 3/8	1185	11100
FEDERAL	209A	SR7625	26.0	WIN.	WAA12R	1 3/8	1210	11000
FEDERAL	209A	SR7625	25.0	REM.	SP12	1 3/8	1180	11200
REMINGTON	209P	SR7625	28.5	WIN.	WAA12R	1 3/8	1255	11000
REMINGTON	209P	SR7625	28.0	REM.	RP12	1 3/8	1240	11100
WINCHESTER	209	SR7625	27.0	WIN.	WAA12R	1 3/8	1225	11000
WINCHESTER	209	SR7625	26.5	REM.	SP12	13/8	1210	11200
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WIN.	WAA12R	1 3/8	1280	11000
FEDERAL	209A	"HI-SKOR" 800-X	26.5	REM.	SP12	1 3/8	1285	11000
FEDERAL	209A	"HI-SKOR" 800-X	25.0	FED.	12S4	1 3/8	1240	10900
REMINGTON	209P	"HI-SKOR" 800-X	30.5	WIN.	WAA12R	1 3/8	1375	11000
REMINGTON	209P	"HI-SKOR" 800-X	32.0	REM.	SP12	1 3/8	1390	11000
REMINGTON	209P	"HI-SKOR" 800-X	27.0	FED.	12S4	1 3/8	1260	9700
WINCHESTER	209	"HI-SKOR" 800-X	27.5	WIN.	WAA12R	1 3/8	1310	11000
WINCHESTER	209	"HI-SKOR" 800-X	29.0	REM.	SP12	1 3/8	1335	10900
WINCHESTER	209	"HI-SKOR" 800-X	26.0	FED.	12S4	1 3/8	1270	11000
FEDERAL	209A	SR4756	31.5	WIN.	WAA12R	1 3/8	1305	11000
FEDERAL	209A	SR4756	30.0	REM.	RP12	1 3/8	1265	10900
REMINGTON	209P	SR4756	35.0	WIN.	WA12R	1 3/8	1365	10500
REMINGTON	209P	SR4756	34.5	REM.	RP12	1 3/8	1350	10900
WINCHESTER	209	SR4756	34.0	WIN.	WAA12R	1 3/8	1335	11000
WINCHESTER	209	SR4756	33.0	REM.	RP12	1 3/8	1320	11200
FEDERAL	209A	SR7625	25.0	REM.	RP12	1 1/2	1140	11400
FEDERAL	209A	SR7625	25.5	WIN.	WAA12R	1 1/2	1150	11200
REMINGTON	209P	SR7625	27.5	REM.	RP12	1 1/2	1185	11100
REMINGTON	209P	SR7625	28.0	WIN.	WAA12R	1 1/2	1170	11000
WINCHESTER	209	SR7625	25.5	REM.	RP12	1 1/2	1140	11000
WINCHESTER	209	SR7625	26.5	WIN.	WAA12R	1 1/2	1160	11000
FEDERAL	209A	"HI-SKOR" 800-X	26.5	REM.	SP12	1 1/2	1220	11000
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WIN.	WAA12R	1 1/2	1215	11200
FEDERAL	209A	"HI-SKOR" 800-X	24.5	FED.	12S4	1 1/2	1180	11200
REMINGTON	209P	"HI-SKOR" 800-X	28.5	REM.	RP12	1 1/2	1265	11000
REMINGTON	209P	"HI-SKOR" 800-X	26.0	RED.	12S4	1 1/2	1190	10400
WINCHESTER	209	"HI-SKOR" 800-X	27.0	REM.	SP12	1 1/2	1225	11100
WINCHESTER	209	"HI-SKOR" 800-X	27.0	WIN.	WAA12R	1 1/2	1245	11000
WINCHESTER	209	"HI-SKOR" 800-X	25.0	FED.	12S4	1 1/2	1170	11000
FEDERAL	209A	SR4756	27.5	REM.	RP12	1 1/2	1160	11000
FEDERAL	209A	SR4756	28.0	WIN.	WAA12R	1 1/2	1175	11100
REMINGTON	209P	SR4756	30.5	REM.	RP12	1 1/2	1220	11100
REMINGTON	209P	SR4756	30.0	WIN.	WAA12R	1 1/2	1165	9000
WINCHESTER	209	SR4756	28.5	REM.	RP12	1 1/2	1175	11000
WINCHESTER	209	SR4756	30.0	WIN.	WAA12R	1 1/2	1205	10800

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 3" PLASTIC HUNTING CASE PAPER BASEWAD								
FEDERAL	209A	"HI-SKOR" 800-X	29.0	REM.	R12H	1 1/2	1270	10700
FEDERAL	209A	"HI-SKOR" 800-X	27.5	FED.	12S4	1 1/2	1230	10800
REMINGTON	209P	"HI-SKOR" 800-X	33.0	REM.	R12H	1 1/2	1335	10600
REMINGTON	209P	"HI-SKOR" 800-X	31.0	FED.	12S4	1 1/2	1290	10600
WINCHESTER	209	"HI-SKOR" 800-X	30.0	REM.	R12H	1 1/2	1290	10500
WINCHESTER	209	"HI-SKOR" 800-X	29.0	FED.	12S4	1 1/2	1260	10600
FEDERAL	209A	SR4756	33.0	WIN.	WAA12R	1 1/2	1255	10700
FEDERAL	209A	SR4756	33.5	REM.	RP12	1 1/2	1285	10800
REMINGTON	209P	SR4756	37.0	WIN.	WAA12R	1 1/2	1305	9600
REMINGTON	209P	SR4756	37.0	REM.	RP12	1 1/2	1295	9100
WINCHESTER	209	SR4756	37.0	WIN.	WAA12R	1 1/2	1315	10400
WINCHESTER	209	SR4756	37.0	REM.	RP12	1 1/2	1305	9900
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WIN.	WAA12R	1 5/8	1175	10800
FEDERAL	209A	"HI-SKOR" 800-X	26.0	REM.	SP12	1 5/8	1175	10800
REMINGTON	209PSTS	"HI-SKOR" 800-X	27.5	WIN.	WAA12R	1 5/8	1200	10900
REMINGTON	209PSTS	"HI-SKOR" 800-X	28.0	REM.	SP12	1 5/8	1200	10800
WINCHESTER	209	"HI-SKOR" 800-X	28.5	WIN.	WAA12R	1 5/8	1230	11000
WINCHESTER	209	"HI-SKOR" 800-X	29.0	REM.	SP12	1 5/8	1230	10900
FEDERAL	209A	SR4756	31.0	WIN.	WAA12R	1 5/8	1185	10800
FEDERAL	209A	SR4756	31.0	REM.	RP12	1 5/8	1185	11000
REMINGTON	209PSTS	SR4756	35.5	WIN.	WAA12R	1 5/8	1250	10900
REMINGTON	209PSTS	SR4756	34.5	REM.	RP12	1 5/8	1235	10800
WINCHESTER	209	SR4756	35.5	WIN.	WAA12R	1 5/8	1260	10800
WINCHESTER	209	SR4756	36.0	REM.	RP12	1 5/8	1260	10800
FEDERAL	209A	"HI-SKOR" 800-X	25.5	WIN.	WAA12R	1 3/4	1130	10700
FEDERAL	209A	"HI-SKOR" 800-X	25.0	REM.	RP12	1 3/4	1115	10800
REMINGTON	209P	"HI-SKOR" 800-X	28.0	WIN.	WAA12R	1 3/4	1175	10600
REMINGTON	209P	"HI-SKOR" 800-X	28.0	REM.	RP12	1 3/4	1170	10500
WINCHESTER	209	"HI-SKOR" 800-X	27.5	WIN.	WAA12R	1 3/4	1165	10800
WINCHESTER	209	"HI-SKOR" 800-X	27.5	REM.	RP12	1 3/4	1155	10600
SHELL: REMINGTON 2 3/4" PREMIER RTL								
REMINGTON	209P	PB	23.0	REM.	SP12	1 1/4	1215	10600
REMINGTON	209P	PB	24.5	REM.	SP12	1 1/4	1270	11500
FEDERAL	209A	SR7625	24.0	REM.	SP12	1 1/4	1215	10600
FEDERAL	209A	SR7625	25.5	REM.	SP12	1 1/4	1265	11500
FEDERAL	209A	SR7625	24.0	WIN.	WAA12R	1 1/4	1210	9900
FEDERAL	209A	SR7625	26.0	WIN.	WAA12R	1 1/4	1280	11300
REMINGTON	209P	SR7625	27.5	REM.	SP12	1 1/4	1280	10600
REMINGTON	209P	SR7625	28.5	REM.	SP12	1 1/4	1330	11500
REMINGTON	209P	SR7625	27.0	WIN.	WAA12R	1 1/4	1280	10300
REMINGTON	209P	SR7625	28.5	WIN.	WAA12R	1 1/4	1335	11400
WINCHESTER	209	SR7625	26.5	REM.	SP12	1 1/4	1280	10800
WINCHESTER	209	SR7625	27.5	REM.	SP12	1 1/4	1315	11500
WINCHESTER	209	SR7625	27.0	WIN.	WAA12R	1 1/4	1280	10200
WINCHESTER	209	SR7625	29.0	WIN.	WAA12R	1 1/4	1340	11500
FEDERAL	209A	SR4756	26.5	REM.	RP12	1 1/4	1235	10500
FEDERAL	209A	SR4756	28.0	REM.	RP12	1 1/4	1300	11500
FEDERAL	209A	SR4756	28.0	WIN.	WAA12R	1 1/4	1270	10600
FEDERAL	209A	SR4756	29.0	WIN.	WAA12R	1 1/4	1315	11400
FEDERAL	209A	SR4756	26.5	FED.	12S4	1 1/4	1230	10700
FEDERAL	209A	SR4756	27.5	FED.	12S4	1 1/4	1270	11400
REMINGTON	209P	SR4756	30.0	REM.	SP12	1 1/4	1275	9300
REMINGTON	209P	SR4756	31.5	REM.	SP12	1 1/4	1335	10400

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: REMINGTON 2 3/4" PREMIER RTL								
FEDERAL	209A	"HI-SKOR" 800-X	24.0	REM.	FIG8	1 1/4	1270	10200
FEDERAL	209A	"HI-SKOR" 800-X	25.5	REM.	FIG8	1 1/4	1325	11100
FEDERAL	209A	"HI-SKOR" 800-X	24.0	WINJ.	WINDJAMMER	1 1/4	1275	9900
FEDERAL	209A	"HI-SKOR" 800-X	25.5	WINJ.	WINDJAMMER	1 1/4	1330	10900
FEDERAL	209A	"HI-SKOR" 800-X	24.0	WIN.	WAA12	1 1/4	1275	11400
FEDERAL	209A	"HI-SKOR" 800-X	24.0	FED.	12S3	1 1/4	1275	11200
REMINGTON	209P	"HI-SKOR" 800-X	24.5	REM.	SP12	1 1/4	1265	9500
REMINGTON	209P	"HI-SKOR" 800-X	26.0	REM.	SP12	1 1/4	1320	10200
REMINGTON	209P	"HI-SKOR" 800-X	25.0	WINJ.	WINDJAMMER	1 1/4	1265	9000
REMINGTON	209P	"HI-SKOR" 800-X	26.5	WINJ.	WINDJAMMER	1 1/4	1325	10000
REMINGTON	209P	"HI-SKOR" 800-X	24.5	WIN.	WAA12	1 1/4	1275	10300
REMINGTON	209P	"HI-SKOR" 800-X	26.0	WIN.	WAA12	1 1/4	1325	11100
REMINGTON	209P	"HI-SKOR" 800-X	24.5	FED.	12S3	1 1/4	1270	10500
REMINGTON	209P	"HI-SKOR" 800-X	26.0	FED.	12S3	1 1/4	1320	11400
WINCHESTER	209	"HI-SKOR" 800-X	24.5	REM.	SP12	1 1/4	1280	10100
WINCHESTER	209	"HI-SKOR" 800-X	26.0	REM.	SP12	1 1/4	1335	11000
WINCHESTER	209	"HI-SKOR" 800-X	24.5	WINJ.	WINDJAMMER	1 1/4	1275	9700
WINCHESTER	209	"HI-SKOR" 800-X	24.5	WIN.	WAA12	1 1/4	1285	11000
WINCHESTER	209	"HI-SKOR" 800-X	25.5	WIN.	WAA12	1 1/4	1320	11500
WINCHESTER	209	"HI-SKOR" 800-X	24.5	FED.	12S4	1 1/4	1275	10600
WINCHESTER	209	"HI-SKOR" 800-X	26.0	FED.	12S4	1 1/4	1330	11500
FEDERAL	209A	PB	19.5	WIN.	WAA12R	1 3/8	1105	10900
FEDERAL	209A	PB	19.5	REM.	SP12	1 3/8	1090	11000
REMINGTON	209P	PB	21.5	WIN.	WAA12R	1 3/8	1150	10900
REMINGTON	209P	PB	21.0	REM.	SP12	1 3/8	1130	11000
WINCHESTER	209	PB	21.5	WIN.	WAA12R	1 3/8	1145	11000
WINCHESTER	209	PB	20.5	REM.	RP12	1 3/8	1120	11100
FEDERAL	209A	SR7625	21.5	WIN.	WAA12R	1 3/8	1100	10800
FEDERAL	209A	SR7625	22.0	REM.	SP12	1 3/8	1110	11200
REMINGTON	209P	SR7625	25.0	WIN.	WAA12R	1 3/8	1185	11000
REMINGTON	209P	SR7625	24.5	REM.	RP12	1 3/8	1165	10800
WINCHESTER	209	SR7625	23.5	WIN.	WAA12R	1 3/8	1145	10900
WINCHESTER	209	SR7625	23.0	REM.	RP12	1 3/8	1140	11100
FEDERAL	209A	"HI-SKOR" 800-X	23.0	WIN.	WAA12R	1 3/8	1215	11000
FEDERAL	209A	"HI-SKOR" 800-X	22.5	REM.	RP12	1 3/8	1205	11000
FEDERAL	209A	"HI-SKOR" 800-X	21.5	FED.	12S4	1 3/8	1155	10900
REMINGTON	209P	"HI-SKOR" 800-X	25.5	WIN.	WAA12R	1 3/8	1270	11100
REMINGTON	209P	"HI-SKOR" 800-X	26.5	REM.	SP12	1 3/8	1275	11000
REMINGTON	209P	"HI-SKOR" 800-X	24.0	FED.	12S4	1 3/8	1225	11100
WINCHESTER	209	"HI-SKOR" 800-X	24.5	WIN.	WAA12R	1 3/8	1240	10900
WINCHESTER	209	"HI-SKOR" 800-X	24.0	REM.	SP12	1 3/8	1230	11000
WINCHESTER	209	"HI-SKOR" 800-X	22.5	FED.	12S3	1 3/8	1180	11100
FEDERAL	209A	SR4756	26.0	WIN.	WAA12R	1 3/8	1205	11100
FEDERAL	209A	SR4756	26.0	REM.	SP12	1 3/8	1175	11000
REMINGTON	209P	SR4756	30.5	WIN.	WAA12R	1 3/8	1290	11100
REMINGTON	209P	SR4756	30.0	REM.	SP12	1 3/8	1260	10900
WINCHESTER	209	SR4756	28.5	WIN.	WAA12R	1 3/8	1230	10900
WINCHESTER	209	SR4756	29.0	REM.	RP12	1 3/8	1250	11100
FEDERAL	209A	SR7625	21.0	REM.	RP12	1 1/2	1040	11000
FEDERAL	209A	SR7625	21.5	WIN.	WAA12R	1 1/2	1055	11000
REMINGTON	209P	SR7625	23.5	REM.	RP12	1 1/2	1090	11200
REMINGTON	209P	SR7625	23.5	WIN.	WAA12R	1 1/2	1085	11000
WINCHESTER	209	SR7625	22.5	REM.	RP12	1 1/2	1080	11200
WINCHESTER	209	SR7625	23.0	WIN.	WAA12R	1 1/2	1080	11000

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: REMINGTON 2 3/4" PREMIER RTL								
FEDERAL	209A	"HI-SKOR" 800-X	22.0	REM.	RP12	1 1/2	1130	11200
FEDERAL	209A	"HI-SKOR" 800-X	22.5	WIN.	WAA12R	1 1/2	1140	11300
REMINGTON	209P	"HI-SKOR" 800-X	23.0	REM.	RP12	1 1/2	1155	11200
REMINGTON	209P	"HI-SKOR" 800-X	23.5	WIN.	WAA12R	1 1/2	1170	11200
WINCHESTER	209	"HI-SKOR" 800-X	22.5	REM.	RP12	1 1/2	1140	11300
WINCHESTER	209	"HI-SKOR" 800-X	23.0	WIN.	WAA12R	1 1/2	1150	11200
FEDERAL	209A	SR4756	23.5	REM.	RP12	1 1/2	1075	11000
FEDERAL	209A	SR4756	24.0	WIN.	WAA12R	1 1/2	1090	11000
REMINGTON	209P	SR4756	27.0	REM.	RP12	1 1/2	1150	11200
REMINGTON	209P	SR4756	27.5	WIN.	WAA12R	1 1/2	1160	11000
WINCHESTER	209	SR4756	25.5	REM.	RP12	1 1/2	1115	11000
WINCHESTER	209	SR4756	26.5	WIN.	WAA12R	1 1/2	1130	11200
SHELL: REMINGTON 3" NITRO PLASTIC BASEWAD								
WINCHESTER	209	SR7625	33.5	REM.	SP12	1 1/2	1280	10700
WINCHESTER	209	SR7625	34.0	REM.	RXP12	1 1/2	1285	10600
WINCHESTER	209	SR4756	38.5	REM.	SP12	1 1/2	1345	10500
WINCHESTER	209	"HI-SKOR" 800-X	29.5	WIN.	WAA12	1 1/2	1285	10800
WINCHESTER	209	"HI-SKOR" 800-X	30.5	REM.	SP12	1 1/2	1300	10600
FEDERAL	209A	"HI-SKOR" 800-X	25.5	WIN.	WAA12	1 5/8	1160	10900
FEDERAL	209A	"HI-SKOR" 800-X	25.5	REM.	R12H	1 5/8	1160	10900
REMINGTON	209PSTS	"HI-SKOR" 800-X	27.5	WIN.	WAA12	1 5/8	1205	10800
REMINGTON	209PSTS	"HI-SKOR" 800-X	28.0	REM.	SP12	1 5/8	1210	10900
WINCHESTER	209	"HI-SKOR" 800-X	28.0	WIN.	WAA12	1 5/8	1210	10800
WINCHESTER	209	"HI-SKOR" 800-X	28.0	REM.	SP12	1 5/8	1210	10800
FEDERAL	209A	SR4756	30.0	WIN.	WAA12R	1 5/8	1180	11000
FEDERAL	209A	SR4756	30.5	REM.	RP12	1 5/8	1175	10900
REMINGTON	209PSTS	SR4756	34.0	WIN.	WAA12R	1 5/8	1240	10900
REMINGTON	209PSTS	SR4756	34.0	REM.	RP12	1 5/8	1235	10900
WINCHESTER	209	SR4756	35.0	WIN.	WAA12R	1 5/8	1250	11000
WINCHESTER	209	SR4756	33.5	REM.	RP12	1 5/8	1230	10800
SHELL: WINCHESTER 2 3/4" AA								
FEDERAL	209A	"HI-SKOR" 700-X	17.0	WINJ.	WINDJAMMER	1 1/4	1140	11500
REMINGTON	209P	"HI-SKOR" 700-X	19.0	WINJ.	WINDJAMMER	1 1/4	1200	11200
WINCHESTER	209	"HI-SKOR" 700-X	17.5	WINJ.	WINDJAMMER	1 1/4	1150	11400
WINCHESTER	209	PB	23.5	WIN.	WAA12R	1 1/4	1220	10500
WINCHESTER	209	PB	25.0	WIN.	WAA12R	1 1/4	1270	11500
FEDERAL	209A	SR7625	26.5	WIN.	WAA12R	1 1/4	1285	10900
FEDERAL	209A	SR7625	27.5	WIN.	WAA12R	1 1/4	1320	11500
FEDERAL	209A	SR7625	26.0	REM.	SP12	1 1/4	1275	11000
FEDERAL	209A	SR7625	27.0	REM.	SP12	1 1/4	1310	11500
REMINGTON	209P	SR7625	28.0	WIN.	WAA12R	1 1/4	1270	9100
REMINGTON	209P	SR7625	29.5	WIN.	WAA12R	1 1/4	1325	10300
REMINGTON	209P	SR7625	28.0	REM.	SP12	1 1/4	1290	10200
REMINGTON	209P	SR7625	29.0	REM.	SP12	1 1/4	1325	10900
REMINGTON	209P	SR7625	26.5	FED.	12S4	1 1/4	1265	10700
REMINGTON	209P	SR7625	28.0	FED.	12S4	1 1/4	1315	11500
WINCHESTER	209	SR7625	27.0	WIN.	WAA12	1 1/4	1275	11000
WINCHESTER	209	SR7625	28.0	WIN.	WAA12	1 1/4	1310	11500
WINCHESTER	209	SR7625	27.5	REM.	SP12	1 1/4	1275	10300
WINCHESTER	209	SR7625	29.0	REM.	SP12	1 1/4	1325	11400
WINCHESTER	209	SR7625	25.0	FED.	12S4	1 1/4	1215	10200
WINCHESTER	209	SR7625	26.5	FED.	12S4	1 1/4	1270	11400
FEDERAL	209A	SR4756	28.5	WIN.	WAA12R	1 1/4	1280	10600
FEDERAL	209A	SR4756	30.0	WIN.	WAA12R	1 1/4	1330	11500
FEDERAL	209A	SR4756	26.0	FED.	12S4	1 1/4	1225	10700
FEDERAL	209A	SR4756	27.5	FED.	12S4	1 1/4	1270	11500
FEDERAL	209A	SR4756	28.5	REM.	SP12	1 1/4	1285	10800
FEDERAL	209A	SR4756	29.5	REM.	SP12	1 1/4	1325	11500

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: WINCHESTER 2 3/4" AA								
REMINGTON	209P	SR4756	31.5	WIN.	WAA12R	1 1/4	1270	8200
REMINGTON	209P	SR4756	33.0	WIN.	WAA12R	1 1/4	1330	9000
REMINGTON	209P	SR4756	29.5	FED.	12S4	1 1/4	1230	8400
REMINGTON	209P	SR4756	30.5	REM.	RP12	1 1/4	1275	9600
REMINGTON	209P	SR4756	31.5	REM.	RP12	1 1/4	1330	10600
WINCHESTER	209	SR4756	30.5	WIN.	WAA12R	1 1/4	1280	9400
WINCHESTER	209	SR4756	32.0	WIN.	WAA12R	1 1/4	1335	10300
WINCHESTER	209	SR4756	26.5	FED.	12S4	1 1/4	1180	9000
WINCHESTER	209	SR4756	27.5	FED.	12S4	1 1/4	1220	9500
WINCHESTER	209	SR4756	30.0	REM.	SP12	1 1/4	1285	10000
WINCHESTER	209	SR4756	31.5	REM.	SP12	1 1/4	1340	11000
FEDERAL	209A	"HI-SKOR" 800-X	24.5	WIN.	WAA12	1 1/4	1270	10400
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WIN.	WAA12	1 1/4	1325	11400
FEDERAL	209A	"HI-SKOR" 800-X	24.5	WINJ.	WINDJAMMER	1 1/4	1270	9300
FEDERAL	209A	"HI-SKOR" 800-X	26.0	WINJ.	WINDJAMMER	1 1/4	1320	10000
FEDERAL	209A	"HI-SKOR" 800-X	25.0	REM.	SP12	1 1/4	1275	9800
FEDERAL	209A	"HI-SKOR" 800-X	26.5	REM.	SP12	1 1/4	1325	10700
FEDERAL	209A	"HI-SKOR" 800-X	24.5	FED.	12S4	1 1/4	1270	10600
FEDERAL	209A	"HI-SKOR" 800-X	26.0	FED.	12S4	1 1/4	1325	11500
REMINGTON	209P	"HI-SKOR" 800-X	27.0	WIN.	WAA12	1 1/4	1275	8200
REMINGTON	209P	"HI-SKOR" 800-X	28.5	WIN.	WAA12	1 1/4	1335	9600
REMINGTON	209P	"HI-SKOR" 800-X	26.0	WINJ.	WINDJAMMER	1 1/4	1270	8100
REMINGTON	209P	"HI-SKOR" 800-X	28.5	WINJ.	WINDJAMMER	1 1/4	1325	9000
REMINGTON	209P	"HI-SKOR" 800-X	27.5	REM.	SP12	1 1/4	1280	7800
REMINGTON	209P	"HI-SKOR" 800-X	29.0	REM.	SP12	1 1/4	1325	8500
REMINGTON	209P	"HI-SKOR" 800-X	26.0	FED.	12S4	1 1/4	1265	8600
REMINGTON	209P	"HI-SKOR" 800-X	27.5	FED.	12S4	1 1/4	1320	9600
WINCHESTER	209	"HI-SKOR" 800-X	25.0	WIN.	WAA12	1 1/4	1270	9900
WINCHESTER	209	"HI-SKOR" 800-X	26.5	WIN.	WAA12	1 1/4	1320	10700
WINCHESTER	209	"HI-SKOR" 800-S	25.5	WINJ.	WINDJAMMER	1 1/4	1275	9000
WINCHESTER	209	"HI-SKOR" 800-X	27.0	WINJ.	WINDJAMMER	1 1/4	1330	10000
WINCHESTER	209	"HI-SKOR" 800-X	25.0	REM.	SP12	1 1/4	1270	9400
WINCHESTER	209	"HI-SKOR" 800-X	26.5	REM.	SP12	1 1/4	1325	10200
WINCHESTER	209	"HI-SKOR" 800-X	25.0	FED.	12S3	1 1/4	1275	10000
WINCHESTER	209	"HI-SKOR" 800-X	26.5	FED.	12S3	1 1/4	1330	10900
FEDERAL	209A	PB	20.0	WIN.	WAA12R	1 3/8	1105	11200
FEDERAL	209A	PB	19.5	REM.	RP12	1 3/8	1090	11100
REMINGTON	209P	PB	22.5	WIN.	WAA12R	1 3/8	1165	11100
REMINGTON	209P	PB	22.0	REM.	RP12	1 3/8	1150	11200
WINCHESTER	209	PB	21.0	WIN.	WAA12R	1 3/8	1125	10900
WINCHESTER	209	PB	20.5	REM.	SP12	1 3/8	1115	11100
FEDERAL	209A	SR7625	22.5	WIN.	WAA12R	1 3/8	1130	11000
FEDERAL	209A	SR7625	23.0	REM.	SP12	1 3/8	1130	11100
REMINGTON	209P	SR7625	26.0	WIN.	WAA12R	1 3/8	1190	11000
REMINGTON	209P	SR7625	24.5	REM.	SP12	1 3/8	1155	10900
WINCHESTER	209	SR7625	24.0	WIN.	WAA12R	1 3/8	1155	11200
WINCHESTER	209	SR7625	24.0	REM.	SP12	1 3/8	1150	10900
FEDERAL	209A	"HI-SKOR" 800-X	25.5	WIN.	WAA12R	1 3/8	1260	11000
FEDERAL	209A	"HI-SKOR" 800-X	25.0	REM.	SP12	1 3/8	1245	11100
FEDERAL	209A	"HI-SKOR" 800-X	22.5	FED.	12S4	1 3/8	1180	11100
REMINGTON	209P	"HI-SKOR" 800-X	29.0	WIN.	WAA12R	1 3/8	1320	10100
REMINGTON	209P	"HI-SKOR" 800-X	30.0	REM.	RP12	1 3/8	1345	11200
REMINGTON	209P	"HI-SKOR" 800-X	27.0	FED.	12S4	1 3/8	1280	11100
WINCHESTER	209	"HI-SKOR" 800-X	26.0	WIN.	WAA12R	1 3/8	1275	11000
WINCHESTER	209	"HI-SKOR" 800-X	26.0	REM.	SP12	1 3/8	1270	11100
WINCHESTER	209	"HI-SKOR" 800-X	23.5	FED.	12S4	1 3/8	1200	11100

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

12 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: WINCHESTER 2 3/4" AA								
FEDERAL	209A	SR4756	27.0	WIN.	WAA12R	1 3/8	1185	10900
FEDERAL	209A	SR4756	27.5	REM.	SP12	1 3/8	1210	11200
REMINGTON	209P	SR4756	32.0	WIN.	WAA12R	1 3/8	1290	10600
REMINGTON	209P	SR4756	31.0	REM.	RP12	1 3/8	1265	10900
WINCHESTER	209	SR4756	30.0	WIN.	WAA12R	1 3/8	1265	11200
WINCHESTER	209	SR4756	28.5	REM.	SP12	1 3/8	1230	11000
SHELL: WINCHESTER 3" AA PLASTIC BASEWAD								
FEDERAL	209A	"HI-SKOR" 800-X	28.0	WIN.	WAA12	1 5/8	1210	10800
FEDERAL	209A	"HI-SKOR" 800-X	28.5	REM.	RXP12	1 5/8	1220	11000
REMINGTON	209PSTS	"HI-SKOR" 800-X	30.0	WIN.	WAA12	1 5/8	1250	10900
REMINGTON	209PSTS	"HI-SKOR" 800-X	31.5	REM.	RXP12	1 5/8	1265	11000
WINCHESTER	209	"HI-SKOR" 800-X	30.5	WIN.	WAA12	1 5/8	1260	11000
WINCHESTER	209	"HI-SKOR" 800-X	30.5	REM.	RXP12	1 5/8	1255	11000
FEDERAL	209A	SR4756	31.0	WIN.	WAA12F114	1 5/8	1180	10800
FEDERAL	209A	SR4756	33.0	REM.	SP12	1 5/8	1225	10900
REMINGTON	209PSTS	SR4756	37.5	2IN.	WAA12R	1 5/8	1290	11000
REMINGTON	209PSTS	SR4756	35.5	REM.	RP12	1 5/8	1265	10900
WINCHESTER	209	SR4756	38.5	WIN.	WAA12R	1 5/8	1295	10900
WINCHESTER	209	SR4756	37.5	REM.	RP12	1 5/8	1290	11000

16 GAUGE FIELD RELOADING DATA

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" GAME								
FEDERAL	209A	"HI-SKOR" 700-X	15.5	WIN.	WAA16	1	1175	11000
REMINGTON	209P	"HI-SKOR" 700-X	16.5	WIN.	WAA16	1	1210	11200
WINCHESTER	209	"HI-SKOR" 700-X	16.0	WIN.	WAA16	1	1195	11200
FEDERAL	209A	PB	21.5	WIN.	WAA16	1	1280	11000
REMINGTON	209P	PB	25.0	REM.	SP16	1	1360	11200
WINCHESTER	209	PB	23.5	WIN.	WAA16	1	1330	11200
FEDERAL	209A	SR7625	24.5	WIN.	WAA16	1	1340	11000
REMINGTON	209P	SR7625	26.5	REM.	SP16	1	1375	10400
WINCHESTER	209	SR7625	25.0	WIN.	WAA16	1	1330	9900
FEDERAL	209A	"HI-SKOR" 800-X	24.0	REM.	SP16	1	1385	10400
REMINGTON	209P	"HI-SKOR" 800-X	25.0	REM.	SP16	1	1350	8300
WINCHESTER	209	"HI-SKOR" 800-X	24.5	WIN.	WAA16	1	1390	10200
FEDERAL	209A	SR4756	25.0	WIN.	WAA16	1	1240	8500
REMINGTON	209P	SR4756	27.0	REM.	SP16	1	1210	6400
WINCHESTER	209	SR4756	25.0	WIN.	WAA16	1	1210	7200
FEDERAL	209A	PB	19.0	REM.	SP16	1 1/8	1145	10800
REMINGTON	209P	PB	21.0	REM.	SP16	1 1/8	1205	10500
WINCHESTER	209	PB	20.5	REM.	SP16	1 1/8	1195	11000
FEDERAL	209A	SR7625	22.0	REM.	SP16	1 1/8	1220	11000
REMINGTON	209P	SR7625	23.0	REM.	SP16	1 1/8	1200	9000
WINCHESTER	209	SR7625	23.0	REM.	SP16	1 1/8	1240	10800
FEDERAL	209A	"HI-SKOR" 800-X	22.5	REM.	SP16	1 1/8	1285	11000
REMINGTON	209P	"HI-SKOR" 800-X	24.5	REM.	SP16	1 1/8	1310	10100
WINCHESTER	209	"HI-SKOR" 800-X	22.5	REM.	SP16	1 1/8	1285	10800
FEDERAL	209A	SR4756	23.0	REM.	SP16	1 1/8	1150	8400
REMINGTON	209P	SR4756	23.0	REM.	SP16	1 1/8	1045	6200
WINCHESTER	209	SR4756	23.0	REM.	SP16	1 1/8	1120	7700

16 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: REMINGTON 2 3/4" GAME (BLACK)								
FEDERAL	209A	"HI-SKOR" 700-X	13.0	WIN.	WAA16	1	1095	11000
REMINGTON	209P	"HI-SKOR" 700-X	14.5	WIN.	WAA16	1	1150	11000
WINCHESTER	209	"HI-SKOR" 700-X	13.5	WIN.	WAA16	1	1120	11200
FEDERAL	209A	PB	17.5	REM.	SP16	1	1180	11200
REMINGTON	209P	PB	20.0	REM.	SP16	1	1240	10700
WINCHESTER	209	PB	19.0	WIN.	WAA16	1	1210	11000
FEDERAL	209A	SR7625	21.0	REM.	SP16	1	1250	11200
REMINGTON	209P	SR7625	23.5	REM.	SP16	1	1310	11200
WINCHESTER	209	SR7625	22.5	WIN.	WAA16	1	1285	11200
FEDERAL	209A	"HI-SKOR" 800-X	20.5	REM.	SP16	1	1295	11200
REMINGTON	209P	"HI-SKOR" 800-X	24.0	REM.	SP16	1	1390	11100
WINCHESTER	209	"HI-SKOR" 800-X	21.5	WIN.	WAA16	1	1315	11000
FEDERAL	209A	SR4756	23.5	REM.	SP16	1	1280	11000
REMINGTON	209P	SR4756	29.0	REM.	SP16	1	1380	10100
WINCHESTER	209	SR4756	22.0	WIN.	WAA16	1	1160	8200
FEDERAL	209A	PB	16.5	REM.	SP16	1 1/8	1090	11000
REMINGTON	209P	PB	18.5	REM.	SP16	1 1/8	1140	11000
WINCHESTER	209	PB	18.0	REM.	SP16	1 1/8	1120	11100
FEDERAL	209A	SR7625	19.5	REM.	SP16	1 1/8	1140	11000
REMINGTON	209P	SR7625	22.0	REM.	SP16	1 1/8	1210	11000
WINCHESTER	209	SR7625	21.0	REM.	SP16	1 1/8	1180	10900
FEDERAL	209A	"HI-SKOR" 800-X	19.0	REM.	SP16	1 1/8	1195	10800
REMINGTON	209P	"HI-SKOR" 800-X	21.0	REM.	SP16	1 1/8	1240	10800
WINCHESTER	209	"HI-SKOR" 800-X	19.5	REM.	SP16	1 1/8	1220	10900
FEDERAL	209A	SR4756	22.0	REM.	SP16	1 1/8	1185	10900
REMINGTON	209P	SR4756	24.0	REM.	SP16	1 1/8	1175	9500
WINCHESTER	209	SR4756	23.5	REM.	SP16	1 1/8	1220	11000
SHELL: WINCHESTER 2 3/4" X-PERT								
FEDERAL	209A	"HI-SKOR" 700-X	12.5	WIN.	WAA16	1	1085	11000
REMINGTON	209P	"HI-SKOR" 700-X	14.5	WIN.	WAA16	1	1145	11000
WINCHESTER	209	"HI-SKOR" 700-X	13.0	WIN.	WAA16	1	1105	11000
FEDERAL	209A	PB	19.5	WIN.	WAA16	1	1240	11200
REMINGTON	209P	PB	21.0	REM.	SP16	1	1265	10800
WINCHESTER	209	PB	19.0	WIN.	WAA16	1	1220	10900
FEDERAL	209A	SR7625	20.5	WIN.	WAA16	1	1230	10900
REMINGTON	209P	SR7625	23.0	REM.	SP16	1	1290	11200
WINCHESTER	209	SR7625	22.0	WIN.	WAA16	1	1270	11000
FEDERAL	209A	"HI-SKOR" 800-X	22.5	WIN.	WAA16	1	1350	10800
REMINGTON	209P	"HI-SKOR" 800-X	24.0	REM.	SP16	1	1350	9000
WINCHESTER	209	"HI-SKOR" 800-X	23.0	WIN.	WAA16	1	1360	11200
FEDERAL	209A	SR4756	22.5	REM.	SP16	1	1245	10900
REMINGTON	209P	SR4756	27.0	REM.	SP16	1	1335	9900
WINCHESTER	209	SR4756	21.0	WIN.	WAA16	1	1130	7800
FEDERAL	209A	PB	16.0	REM.	SP16	1 1/8	1075	11100
REMINGTON	209P	PB	18.5	REM.	SP16	1 1/8	1145	11100
WINCHESTER	209	PB	17.0	REM.	SP16	1 1/8	1100	10800
FEDERAL	209A	SR7625	18.0	REM.	SP16	1 1/8	1100	10800
REMINGTON	209P	SR7625	19.5	REM.	SP16	1 1/8	1160	10900
WINCHESTER	209	SR7625	19.0	REM.	SP16	1 1/8	1140	10900
FEDERAL	209A	"HI-SKOR" 800-X	19.0	REM.	SP16	1 1/8	1180	10900
REMINGTON	209P	"HI-SKOR" 800-X	22.0	REM.	SP16	1 1/8	1245	10100
WINCHESTER	209	"HI-SKOR" 800-X	20.0	REM.	SP16	1 1/8	1210	11000
FEDERAL	209A	SR4756	20.5	REM.	SP16	1 1/8	1150	10800
REMINGTON	209P	SR4756	23.0	REM.	SP16	1 1/8	1150	8900
WINCHESTER	209	SR4756	22.5	REM.	SP16	1 1/8	1200	11100

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

20 GAUGE FIELD RELOADING DATA

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: FEDERAL 2 3/4" PLASTIC TARGET/HUNTING								
FEDERAL	209A	SR7625	19.0	WIN.	WAA20F1	1	1205	11700
REMINGTON	209P	SR7625	21.0	REM.	SP20	1	1240	11400
WINCHESTER	209	SR7625	20.5	WIN.	WAA20F1	1	1235	11600
FEDERAL	209A	"HI-SKOR" 800-X	19.0	FED.	20S1	1	1255	11500
FEDERAL	209A	"HI-SKOR" 800-X	18.5	REM.	SP20	1	1245	11600
FEDERAL	209A	"HI-SKOR" 800-X	19.0	WIN.	WAA20F1	1	1270	11800
REMINGTON	209P	"HI-SKOR" 800-X	20.0	FED.	20S1	1	1275	11100
REMINGTON	209P	"HI-SKOR" 800-X	21.0	REM.	SP20	1	1320	11400
REMINGTON	209P	"HI-SKOR" 800-X	21.0	WIN.	WAA20F1	1	1330	11600
WINCHESTER	209	"HI-SKOR" 800-X	19.5	FED.	20S1	1	1270	11600
WINCHESTER	209	"HI-SKOR" 800-X	20.0	REM.	SP20	1	1290	11700
WINCHESTER	209	"HI-SKOR" 800-X	19.5	WIN.	WAA20F1	1	1285	11500
SHELL: FEDERAL 3" MAGNUM PAPER BASE WAD								
FEDERAL	209A	PB	17.0	FED.	20S1	1 1/8	1080	11300
FEDERAL	209A	PB	18.0	REM.	RXP20	1 1/8	1130	11500
FEDERAL	209A	PB	17.5	2IN.	WAA20	1 1/8	1110	11600
REMINGTON	209P	PB	19.0	FED.	20S1	1 1/8	1140	11600
REMINGTON	209P	PB	20.0	REM.	RXP20	1 1/8	1175	11400
WINCHESTER	209	PB	19.0	FED.	20S1	1 1/8	1160	11700
WINCHESTER	209	PB	18.0	REM.	RXP20	1 1/8	1120	11400
WINCHESTER	209	PB	17.0	WIN.	WAA20	1 1/8	1090	11400
FEDERAL	209A	"HI-SKOR" 800-X	19.0	FED.	20S1	1 1/8	1200	11600
FEDERAL	209A	"HI-SKOR" 800-X	19.5	REM.	RXP20	1 1/8	1215	11500
FEDERAL	209A	"HI-SKOR" 800-X	19.5	WIN.	WAA20	1 1/8	1210	11500
REMINGTON	209P	"HI-SKOR" 800-X	22.0	FED.	20S1	1 1/8	1275	11700
REMINGTON	209P	"HI-SKOR" 800-X	21.0	REM.	SP20	1 1/8	1255	11600
REMINGTON	209P	"HI-SKOR" 800-X	22.0	WIN.	WAA20	1 1/8	1275	11400
WINCHESTER	209	"HI-SKOR" 800-X	19.5	FED.	20S1	1 1/8	1210	11600
WINCHESTER	209	"HI-SKOR" 800-X	19.5	REM.	SP20	1 1/8	1210	11500
WINCHESTER	209	"HI-SKOR" 800-X	19.0	WIN.	WAA20	1 1/8	1200	11400
FEDERAL	209A	SR4756	21.0	FED.	20S1	1 1/8	1165	11400
FEDERAL	209A	SR4756	21.5	REM.	SP20	1 1/8	1190	11700
FEDERAL	209A	SR4756	20.5	WIN.	WAA20	1 1/8	1160	11700
REMINGTON	209P	SR4756	24.0	FED.	20S1	1 1/8	1235	11200
REMINGTON	209P	SR4756	24.5	REM.	SP20	1 1/8	1250	11200
REMINGTON	209P	SR4756	24.0	WIN.	WAA20	1 1/8	1240	11000
WINCHESTER	209	SR4756	21.5	FED.	20S1	1 1/8	1185	11300
WINCHESTER	209	SR4756	23.0	REM.	SP20	1 1/8	1215	11500
WINCHESTER	209	SR4756	22.5	WIN.	WAA20	1 1/8	1215	11700
FEDERAL	209A	"HI-SKOR" 800-X	17.5	REM.	SP20	1 1/4	1095	11500
FEDERAL	209A	"HI-SKOR" 800-X	18.0	WIN.	WAA20F1	1 1/4	1115	11700
REMINGTON	209P	"HI-SKOR" 800-X	19.5	REM.	SP20	1 1/4	1155	11400
REMINGTON	209P	"HI-SKOR" 800-X	20.0	WIN.	WAA20F1	1 1/4	1170	11000
WINCHESTER	209	"HI-SKOR" 800-X	18.0	REM.	SP20	1 1/4	1105	11400
WINCHESTER	209	"HI-SKOR" 800-X	18.5	WIN.	WAA20F1	1 1/4	1130	11400
SHELL: REMINGTON 2 3/4" PREMIER (RTL)								
FEDERAL	209A	SR7625	14.5	WIN.	WAA20F1	1	1060	11400
FEDERAL	209A	SR7625	14.5	REM.	SP20	1	1055	11500
REMINGTON	209P	SR7625	16.5	WIN.	WAA20F1	1	1125	11800
REMINGTON	209P	SR7625	16.0	REM.	SP20	1	1105	11600
WINCHESTER	209	SR7626	16.0	WIN.	WAA20F1	1	1110	11800
WINCHESTER	209	SR7625	16.0	REM.	SP20	1	1105	11400
FEDERAL	209A	"HI-SKOR" 800-X	15.0	FED.	20S1	1	1115	11400
FEDERAL	209A	"HI-SKOR" 800-X	16.0	REM.	SP20	1	1170	11800
FEDERAL	209A	"HI-SKOR" 800-X	15.5	WIN.	WAA20F1	1	1150	11800
REMINGTON	209P	"HI-SKOR" 800-X	16.0	FED.	20S1	1	1160	11200
REMINGTON	209P	"HI-SKOR" 800-X	17.5	REM.	SP20	1	1220	11900
REMINGTON	209P	"HI-SKOR" 800-X	17.0	WIN.	WAA20F1	1	1205	11700

20 GAUGE FIELD RELOADING DATA (Cont'd)

PRIMER		IMR POWDER		WAD COLUMN		LEAD	MUZZLE	CHAMBER
MFR.	NO.	DESIGNATION	GRAINS	MFR.	DESIGNATION	SHOT (OZ.)	VELOCITY (FT/SEC)	PRESSURE (PSI)
SHELL: REMINGTON 2 3/4" PREMIER (RTL)								
WINCHESTER	209	"HI-SKOR" 800-X	16.0	FED.	20S1	1	1160	11700
WINCHESTER	209	"HI-SKOR" 800-X	17.0	REM.	RXP20	1	1200	11800
WINCHESTER	209	"HI-SKOR" 800-X	16.5	WIN.	WAA20F1	1	1185	11800
FEDERAL	209A	SR4756	17.0	REM.	SP20	1	1125	11800
REMINGTON	209P	SR4756	19.5	REM.	SP20	1	1185	11500
WINCHESTER	209	SR4756	18.5	REM.	SP20	1	1160	11700
SHELL: REMINGTON 3" UNIBODY								
FEDERAL	209A	"HI-SKOR" 800-X	15.5	FED.	20C1	1 1/8	1095	11600
FEDERAL	209A	"HI-SKOR" 800-X	15.5	REM.	SP20	1 1/8	1105	11800
FEDERAL	209A	"HI-SKOR" 800-X	15.5	WIN.	WAA20	1 1/8	1095	11600
REMINGTON	209P	"HI-SKOR" 800-X	17.0	FED.	20C1	1 1/8	1145	11600
REMINGTON	209P	"HI-SKOR" 800-X	17.0	REM.	SP20	1 1/8	1150	11700
REMINGTON	209P	"HI-SKOR" 800-X	16.0	WIN.	WAA20	1 1/8	1110	11100
WINCHESTER	209	"HI-SKOR" 800-X	16.5	FED.	20C1	1 1/8	1120	11500
WINCHESTER	209	"HI-SKOR" 800-X	16.0	REM.	SP20	1 1/8	1100	11600
WINCHESTER	209	"HI-SKOR" 800-X	16.0	WIN.	WAA20	1 1/8	1110	11600
SHELL: REMINGTON 3" UNIBODY								
FEDERAL	209A	"HI-SKOR" 800-X	14.5	REM.	SP20	1 1/4	1020	11700
REMINGTON	209P	"HI-SKOR" 800-X	16.0	REM.	SP20	1 1/4	1070	11700
WINCHESTER	209	"HI-SKOR" 800-X	15.0	REM.	SP20	1 1/4	1035	11600
SHELL: WINCHESTER 2 3/4" SUPER-X								
FEDERAL	209A	SR7625	14.0	WIN.	WAA20F1	1	1040	11400
FEDERAL	209A	SR7625	14.5	REM.	RXP20	1	1060	11600
REMINGTON	209P	SR7625	15.0	WIN.	WAA20F1	1	1065	10900
REMINGTON	209P	SR7625	15.0	REM.	RXP20	1	1050	9800
WINCHESTER	209	SR7625	14.5	WIN.	WAA20F1	1	1060	11400
WINCHESTER	209	SR7625	15.0	REM.	RXP20	1	1065	11300
FEDERAL	209A	"HI-SKOR" 800-X	14.5	WIN.	WAA20F1	1	1130	11800
FEDERAL	209A	"HI-SKOR" 800-X	15.0	REM.	RXP20	1	1135	11700
REMINGTON	209P	"HI-SKOR" 800-X	17.0	WIN.	WAA20F1	1	1200	11500
REMINGTON	209P	"HI-SKOR" 800-X	17.0	REM.	RXP20	1	1185	10800
WINCHESTER	209	"HI-SKOR" 800-X	15.5	WIN.	WAA20F1	1	1150	11500
WINCHESTER	209	"HI-SKOR" 800-X	16.0	REM.	RXP20	1	1160	11600
WINCHESTER	209	SR4756	17.0	WIN.	WAA20F1	1	1105	11100
WINCHESTER	209	SR4756	17.0	REM.	RXP20	1	1100	10700

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. DO NOT ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

Data shown were obtained under controlled conditions: to achieve the ballistic results as listed in this Guide, you must comply, exactly, with each and every listed condition that produced these results. In effect, these data as presented in the shotshell section are a "recipe," to be followed without deviation to achieve the stated ballistic level. The values shown may vary substantially if different component combinations and/or techniques are employed.

.410 BORE FIELD RELOADING DATA

PRIMER MFR.	NO.	IMR POWDER DESIGNATION	GRAINS	WAD COLUMN MFR.	DESIGNATION	LEAD SHOT (OZ.)	MUZZLE VELOCITY (FT/SEC)	CHAMBER PRESSURE (PSI)
SHELL: REMINGTON 3" SP "EXPRESS"								
REMINGTON	209PSTS	IMR4198	26.5	REM.	SP410	1/2	1455	11100
FEDERAL	209A	IMR4227	19.0	REM.	SP410	11/16	1175	13300
REMINGTON	209P	IMR4227	19.0	REM.	SP410	11/16	1115	10900
WINCHESTER	209	IMR4227	19.0	REM.	SP410	11/16	1120	11600
SHELL: WINCHESTER 3" COMPRESSION-FORMED "SUPER-X"								
WINCHESTER	209	IMR4198	22.0	WIN.	WAA41	1/2	1260	9100
FEDERAL	209A	IMR4227	16.5	WIN.	WAA41	5/8	1055	10700
WINCHESTER	209	IMR4227	16.5	WIN.	WAA41	5/8	1015	9200

NOTE - ALL DATA SHOWN IS FOR LEAD SHOT. **DO NOT** ATTEMPT TO LOAD WITH STEEL SHOT AS DANGEROUS LOADS MAY RESULT.

ABBREVIATIONS AND MANUFACTURERS' TRADEMARKS

FEDERAL

Shotgun Shells: Hi-Power*, Gold Medal*, Paper Champion*.

Abbreviations Used

FC

SC

Trade Names

Fiber Cushion Wad

Shot Cup

*Registered trademarks of Federal Cartridge Co., Minneapolis, MN

WINCHESTER*

Shotgun Shells: Double A*, Super-X*, Upland*.

*Registered trademarks of Olin Corp., East Alton, IL

BALLISTIC PRODUCTS, INC.

20015 75 Ave. No.
Corcoran, MN 55340

Abbreviations Used

BP

BPGS

BPSB

Trade Names

Ballistic Products

Ballistic Products

Gas Seal Wad

Ballistic Products

Shot Buffer Material

DANGER! Smokeless powder is an extremely flammable solid and can be dangerous if improperly handled. It should not be exposed to heat, sparks, or open flame. In accordance with good handloading practices, all reloading components including smokeless powder should be kept out of reach of children at all times.

REFERENCE TABLES

POWDER TABLE

GRAINS PER LOAD	LOADS PER POUND	GRAINS PER LOAD	LOADS PER POUND	GRAINS PER LOAD	LOADS PER POUND
12	583	23	304	34	205
13	538	24	291	35	200
14	500	25	280	36	194
15	466	26	269	37	189
16	437	27	259	38	184
17	411	28	250	39	179
18	388	29	241	40	175
19	368	30	233	41	170
20	350	31	225	42	166
21	333	32	218	43	162
22	318	33	212		

CHILLED SHOT TABLE

Weight Ounces	1/2	5/8	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2	1 5/8	1 3/4	1 7/8	2	2 1/8	
Weight Grains	219	273	328	383	438	492	547	602	656	711	766	820	875	930	
Loads per Lb.	32	26	21	18	16	14	13	12	11	10	9	9	8	8	
Size	Dia. In.	Approximate No. of Pellets per load													
BB	.18	25	31	38	44	50	56	63	69	75	81	88	94	100	106
2	.15	44	55	66	77	88	99	110	121	132	143	154	165	176	187
4	.13	68	85	102	119	136	153	170	187	204	221	238	255	271	289
2	.12	86	108	129	151	172	194	215	237	258	280	301	323	344	366
6	.11	112	139	167	195	223	251	279	307	335	362	390	418	446	474
7	.10	150	187	224	262	299	336	374	411	449	486	523	561	598	635
7 1/2	.095	173	216	259	302	345	388	431	474	518	564	604	647	690	733
8	.085	240	300	360	420	480	540	600	660	720	780	840	900	960	1020
9	.08	293	366	439	512	585	658	731	804	878	951	1024	1097	1170	1243

RIFLE

IMPORTANT: Recommended uses of IMR powder relate only to the appropriate IMR powder and not to those available from other firms. Although the four digit numerical designations of other manufacturers' products may be identical to those preceded by the IMR prefix, the powders are different. To avoid potential confusion, gun damage and personal injury, therefore, handloaders should be careful to note the prefix of recommended powder designations.

KEY TO ABBREVIATIONS FOR RIFLE DATA

BP	Bronze Point	IMR	Improved Military Rifle	PTD	Pointed
BR	Bench Rest	M	Magnum	RN	Round Nose
BT	Boat Tail	PL	"Power-Lokt"	SP	Soft Point
C	Compressed Charge	PR	Primer	SPCL	Soft Point "Core-Lokt"
C.O.L.	Cartridge Overall Length	PSP	Pointed Soft Point		
HP	Hollow Point	PSPCL	Pointed Soft Point "Core-Lokt"		

IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)
.17 REMINGTON				.222 REMINGTON				.22-250 REMINGTON				.223 REMINGTON			
REM. CASE; REM. 7 1/2 PR REM. 25 GR. PL HP				REM. CASE; REM. 7 1/2 PR HORNADY 45 GR.				REM. CASE; REM. 9 1/2 PR REM. 55 GR. PTD. SP				REM. CASE; REM. 7 1/2 PR HORNADY 55 GR. SPIRE PT. SX			
.1722" DIA.; 24" BBL.; 2.100" C.O.L.				.224" DIA.; 25" BBL.; 2.130" C.O.L.				.224" DIA.; 24" BBL.; 2.350" C.O.L.				.224" DIA.; 24" BBL.; 2.260" C.O.L.			
SR 4759	16.0	3505	50100	SR 4759	16.5	2925	44000	SR 4759	22.0	3100	53000	SR 4759	16.5	2745	50100
IMR 4227	16.5	3600	50500	IMR 4227	17.5	3055	44000	IMR 4227	21.5	3030	42300	IMR 4227	17.0	2810	51200
IMR 4198	19.5	3840	51000	IMR 4198	21.5	3315	45000	IMR 4198	27.5	3375	52200	IMR 4198	21.5	3100	52000
IMR 3031	22.5	4015	51700	IMR 3031	24.0C	3065	33100	IMR 3031	34.0	3640	53000	IMR 3031	25.0C	3165	50900
IMR 4064	24.0C	4005	50700	IMR 4064	24.0C	2910	31700	IMR 4064	35.5	3625	52500	IMR 4064	25.5C	3090	49200
IMR 4895	23.5	3995	51400	IMR 4895	25.5C	3165	39500	IMR 4895	35.5	3645	53000	IMR 4895	26.0	3120	21100
IMR 4320	25.0	3965	51300	IMR 4320	26.0C	3115	39700	IMR 4320	36.0	3540	51500	IMR 4320	27.0C	3075	50300
IMR 4350	24.5C	3470	39000	IMR 4350	25.0C	2545	24700	IMR 4350	39.5C	3495	47700	IMR 4350	26.0C	2605	34800
IMR 4831	25.0C	3330	33500	IMR 4831	25.0C	2375	22300	IMR 4831	39.5C	3320	42500	IMR 4831	26.0C	2415	31300
.22 HORNET				.222 REMINGTON				.223 REMINGTON				.243 WINCHESTER			
REM. CASE; REM. 6 1/2 PR HORNADY 45 GR.				REM. CASE; REM. 7 1/2 PR HORNADY 50 GR. SPIRE PT. SX				REM. CASE; REM. 7 1/2 PR SIERRA 45 GR. SPITZER				REM. CASE; REM. 9 1/2 PR REM. 80 GR. PTD. SP			
.224" DIA.; 25" BBL.; 1.720" C.O.L.				.224" DIA.; 25" BBL.; 2.130" C.O.L.				.224" DIA.; 24" BBL.; 2.190" C.O.L.				.243" DIA.; 22" BBL.; 2.640" C.O.L.			
SR 4759	8.0C	2000	24700	SR 4759	16.5	2845	45000	SR 4759	17.5	3040	51000	SR 4759	25.5	2710	51300
IMR 4227	11.5C	2515	38900	IMR 4227	17.5	2965	45500	IMR 4227	17.5	3085	51400	IMR 4227	25.0	2695	51000
IMR 4198	10.5C	2010	20100	IMR 4198	20.5	3130	44500	IMR 4198	22.0	3360	50300	IMR 4198	32.0	3035	51300
IMR 3031	11.0C	1675	14100	IMR 3031	23.5C	3045	38400	IMR 3031	25.5C	3300	42200	IMR 3031	39.5	3260	51100
IMR 4064	11.0C	1545	13100	IMR 4064	23.5C	2875	34200	IMR 4064	25.5C	3180	42500	IMR 4064	42.5	3360	52000
IMR 4895	12.0C	1735	15500	IMR 4895	25.0C	3085	43100	IMR 4895	26.5C	3280	45900	IMR 4895	41.0	3305	52000
IMR 4320	12.0C	1650	14900	IMR 4320	26.0C	3065	40800	IMR 4320	27.5C	3200	45100	IMR 4320	42.5	3280	51700
IMR 4350	11.5C	1280	11700	IMR 4350	24.5C	2495	23400	IMR 4350	26.0C	2675	30500	IMR 4350	48.0C	3345	51700
IMR 4831	11.5C	1085	10700	IMR 4831	24.5C	2320	21500	IMR 4831	26.0C	2475	26800	IMR 4831	48.5C	3265	46900
.220 SWIFT				.222 REMINGTON				.223 REMINGTON				.243 WINCHESTER			
REM. CASE; REM. 9 1/2 PR SIERRA 50 GR. SPITZER				REM. CASE; REM. 7 1/2 PR REM. 55 GR. PTD. SP				REM. CASE; REM. 7 1/2 PR SIERRA 50 GR. SPITZER				REM. CASE; REM. 9 1/2 PR REM. 100 GR. PTD. SPCL			
.224" DIA.; 24" BBL.; 2.680" C.O.L.				.224" DIA.; 25" BBL.; 2.130" C.O.L.				.224" DIA.; 24" BBL.; 2.260" C.O.L.				.243" DIA.; 22" BBL.; 2.710" C.O.L.			
SR 4759	25.5	3345	53000	SR 4759	15.5	2665	44200	SR 4759	17.5	2935	51900	SR 4759	24.5	2430	51200
IMR 4227	24.5	3295	52500	IMR 4227	17.0	2835	45800	IMR 4227	17.5	2975	52000	IMR 4227	25.0	2450	52000
IMR 4198	32.0	3685	53000	IMR 4198	20.0	2990	42600	IMR 4198	22.0	3270	51900	IMR 4198	31.0	2750	52000
IMR 3031	37.5	3845	51400	IMR 3031	23.0C	2945	38300	IMR 3031	25.5C	3225	45300	IMR 3031	35.5	2825	51300
IMR 4064	39.5	3895	52500	IMR 4064	23.5C	2825	34100	IMR 4064	25.5C	3150	44200	IMR 4064	38.0	2910	51000
IMR 4895	38.5	3805	52100	IMR 4895	25.0C	3085	45900	IMR 4895	26.5C	3270	48800	IMR 4895	37.0	2910	52000
IMR 4320	40.0	3790	53000	IMR 4320	25.5C	2985	43500	IMR 4320	27.5C	3200	48300	IMR 4320	39.5	2950	52000
IMR 4350	43.5C	3740	49100	IMR 4350	24.5C	2475	26800	IMR 4350	26.0C	2650	31000	IMR 4350	43.5	2980	51300
IMR 4831	43.5C	3560	41700	IMR 4831	24.5C	2300	24100	IMR 4831	26.0C	2475	27400	IMR 4831	46.0C	3010	51800
.220 SWIFT				.22-250 REMINGTON											
REM. CASE; REM. 9 1/2 PR HORNADY 60 GR. SPIRE PT				REM. CASE; REM. 9 1/2 PR SIERRA 50 GR. SPITZER											
.224" DIA.; 24" BBL.; 2.680" C.O.L.				.224" DIA.; 24" BBL.; 2.350" C.O.L.											
SR 4759	23.5	2980	52500	SR 4759	23.0	3205	52500								
IMR 4227	23.5	3000	53000	IMR 4227	21.5	3140	49300								
IMR 4198	28.5	3265	52200	IMR 4198	28.5	3565	53000								
IMR 3031	34.0	3470	52300	IMR 3031	35.0	3785	52700								
IMR 4064	35.5	3505	52300	IMR 4064	35.0	3745	52100								
IMR 4895	34.5	3470	53000	IMR 4895	36.0	3755	52700								
IMR 4320	36.5	3480	52800	IMR 4320	37.0	3700	53000								
IMR 4350	39.5	3500	53000	IMR 4350	40.0C	3565	47000								
IMR 4831	42.5C	3555	53000	IMR 4831	40.0C	3390	41600								

Velocity and pressure readings represent average values obtained under controlled conditions. The values shown may vary substantially with the components and the reloading techniques employed. We suggest the charge weights shown be reduced initially by 10% to compensate for possible variations from the published data. The loads may then be increased as pressure indications permit.

RIFLE

IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER
POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)
6 MM REMINGTON				.25-06 REMINGTON				6.5 x 55 SWEDISH				.270 WINCHESTER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR			
REM. 80 GR. PTD. SP				SIERRA 100 GR. SPITZER				140 GR SIERRA SPITZER B.T.,				REM. 150 GR. SPCL			
.243" DIA.; 22" BBL.; 2.790" C.O.L.				.257" DIA.; 24" BBL.; 3.090" C.O.L.				.264" DIA.; 24" BBL.; 3.000" C.O.L.				.277" DIA.; 24" BBL.; 3.250" C.O.L.			
SR 4759	24.5	2640	50600	SR 4759	30.0	2660	52100	IMR 3031	34.5	2355	45800	SR 4759	26.0	2045	51600
IMR 4227	24.5	2650	50200	IMR 4227	29.5	2645	52900	IMR 4064	37.5	2465	45600	IMR 4227	29.0	2215	51000
IMR 4198	31.5	3015	51500	IMR 4198	36.0	2905	52800	IMR 4895	36.5	2430	45000	IMR 4198	34.5	2460	21800
IMR 3031	39.5	3275	52000	IMR 3031	45.5	3215	53000	IMR 4320	37.5	2465	45500	IMR 3031	42.0	2690	51800
IMR 4064	41.0	3295	52000	IMR 4064	47.5	3240	52800	IMR 4350	42.5	2525	45400	IMR 4064	47.0	2770	51800
IMR 4895	36.5	3105	51300	IMR 4895	43.0	3110	52400	IMR 4831	43.5	2530	45800	IMR 4895	44.0	2715	52000
IMR 4320	40.0	3180	52000	IMR 4320	45.5	3125	52400	IMR 7828	47.5	2600	45000	IMR 4320	44.5	2700	51000
IMR 4350	46.0	3310	52000	IMR 4350	53.5	3290	52900					IMR 4350	53.5	2920	51800
IMR 4831	48.0	3300	51900	IMR 4831	56.0	3335	53000					IMR 4831	55.0	2920	51400
												IMR 7828	59.0C	2985	51000
6 MM REMINGTON				.25-06 REMINGTON				.264 WINCHESTER MAG.				7 x 57 MM MAUSER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				REM. CASE; REM. 9 1/2 PR			
REM. 100 GR. PTD. SPCL				SIERRA 120 GR. HOLLOW PT. BT				SIERRA 100 GR. HP				SPEER 130 GR. SPITZER			
.243" DIA.; 22" BBL.; 2.735" C.O.L.				.257" DIA.; 24" BBL.; 3.100" C.O.L.				.264" DIA.; 24" BBL.; 3.100" C.O.L.				.284" DIA.; 24" BBL.; 2.965" C.O.L.			
SR 4759	23.5	2400	51600	SR 4759	27.5	2315	52000	SR 4759	36.5	2845	53900	SR 4759	23.5	2055	46000
IMR 4227	23.5	2395	51500	IMR 4227	28.0	2370	53000	IMR 4227	36.5	2835	53600	IMR 4227	22.5	2080	44300
IMR 4198	29.0	2660	52000	IMR 4198	34.0	2615	51400	IMR 4198	43.5	3100	53900	IMR 4198	29.0	2365	45100
IMR 3031	36.5	2925	52000	IMR 3031	40.5	2800	52000	IMR 3031	48.0	3150	54000	IMR 3031	38.0	2640	45500
IMR 4064	38.0	2945	51000	IMR 4064	43.5	2885	52300	IMR 4064	51.5	3250	52900	IMR 4064	41.0	2675	44900
IMR 4895	35.5	2880	51600	IMR 4895	40.5	2805	52600	IMR 4895	51.5	3295	53800	IMR 4895	36.5	2540	45300
IMR 4320	37.0	2875	51300	IMR 4320	43.0	2850	51700	IMR 4320	54.0	3325	54000	IMR 4320	7.5	2540	46000
IMR 4350	43.5	3055	52000	IMR 4350	48.5	2950	51500	IMR 4350	60.0	3385	53900	IMR 4350	47.0	2710	45500
IMR 4831	45.5	3095	52000	IMR 4831	50.0	2945	52000	IMR 4831	61.5	3360	53600	IMR 4831	50.0C	2750	46000
IMR 7828	48.0C	3040	48000	IMR 7828	55.0	3105	52800								
.250 SAVAGE				.257 ROBERTS				.264 WINCHESTER MAG.				7 x 57 MM MAUSER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				REM. CASE; REM. 9 1/2 PR			
SIERRA 87 GR. SPITZER				SIERRA 100 GR. SPITZER				SIERRA 140 GR. SPITZER BT				SPEER 145 GR. SPITZER			
.257" DIA.; 24" BBL.; 2.515" C.O.L.				.257" DIA.; BBL.; 2.775" C.O.L.				.264" DIA.; 24" BBL.; 3.230" C.O.L.				.284" DIA.; BBL.; 3.065" C.O.L.			
SR 4759	20.5	2515	44700	SR 4759	22.0	2315	45000	SR 4759	34.0	2400	54000	SR 4759	23.0	1835	45100
IMR 4227	21.5	2570	45000	IMR 4227	23.5	2930	44000	IMR 4227	34.5	2420	54000	IMR 4227	22.5	1840	44400
IMR 4198	27.5	2875	43900	IMR 4198	30.5	2720	45000	IMR 4198	39.5	2580	54000	IMR 4198	29.0	2260	45800
IMR 3031	34.0	3055	44200	IMR 3031	3.0	2935	44400	IMR 3031	44.0	2665	53700	IMR 3031	38.0	2530	46000
IMR 4064	35.5	3075	45000	IMR 4064	39.5	2945	44800	IMR 4064	46.0	2710	53600	IMR 4064	40.0	2555	45300
IMR 4895	34.5	3000	44900	IMR 4895	36.5	2850	45000	IMR 4895	45.5	2715	53600	IMR 4895	35.0	2475	46000
IMR 4320	35.5	2975	45000	IMR 4320	38.5	2860	45000	IMR 4320	47.5	2745	53900	IMR 4320	36.0	2365	45100
IMR 4350	39.0C	2905	39500	IMR 4350	44.5	2930	44600	IMR 4350	52.5	2850	53700	IMR 4350	47.0	2650	46000
IMR 4831	39.0C	2740	35400	IMR 4831	46.5	2950	44300	IMR 4831	54.5	2875	53600	IMR 4831	48.0C	2625	46000
								IMR 7828	65.0	3115	53600				
.250 SAVAGE				.257 ROBERTS				.270 WINCHESTER				7 x 57 MM MAUSER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR			
HORNADY 100 GR. SPIRE PT.				SIERRA 120 GR. HP BT				REM. 100 GR. PSP				SPEER 160 GR. SPITZER			
.257" DIA.; 24" BBL.; 2.515" C.O.L.				.257" DIA.; 24" BBL.; 2.775" C.O.L.				.277" DIA.; 24" BBL.; 3.075" C.O.L.				.284" DIA.; 24" BBL.; 3.065" C.O.L.			
SR 4759	20.0	2290	43700	SR 4759	20.5	2120	45000	SR 4759	30.5	2720	41200	SR 4759	22.5	1855	45700
IMR 4227	21.0	2380	43100	IMR 4227	22.0	2180	44400	IMR 4227	30.0	2711	51400	IMR 4227	22.5	1890	46000
IMR 4198	27.0	2685	45000	IMR 4198	27.5	2440	45000	IMR 4198	38.0	3050	51000	IMR 4198	28.5	2135	44900
IMR 3031	33.0	2865	44500	IMR 3031	33.0	2635	44200	IMR 3031	48.5	3320	51300	IMR 3031	38.0	2430	45800
IMR 4064	34.5	2875	44100	IMR 4064	35.5	2695	44000	IMR 4064	52.0	3400	50900	IMR 4064	40.0	2480	46000
IMR 4895	34.0	2845	45000	IMR 4895	33.5	2615	45000	IMR 4895	49.0	3310	52000	IMR 4895	35.0	2325	45800
IMR 4320	34.5	2785	45000	IMR 4320	34.5	2615	44800	IMR 4320	51.0	3340	51000	IMR 4320	36.0	2295	45200
IMR 4350	38.5C	2780	41400	IMR 4350	41.5	2780	45000	IMR 4350	57.5	3300	51500	IMR 4350	45.0	2510	45800
IMR 4831	38.5C	2615	37000	IMR 4831	44.0	2810	45000	IMR 4831	59.5C	3325	51300	IMR 4831	47.5C	2540	45600
				IMR 7828	47.0C	2745	43900	IMR 7828	61.0C	3300	52000				
.25-06 REMINGTON				6.5 x 55 SWEDISH				.270 WINCHESTER				.280 REMINGTON			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR			
SIERRA 87 GR. SPITZER				85 GR. SIERRA H.P.				NOSLER 130 GR. PARTITION				REM. 125 GR. PTD. SPCL			
.257" DIA. 24" BBL.; 3.100" C.O.L.				.264" DIA.; 24" BBL.; 2.800" C.O.L.				.277" DIA.; 24" BBL.; 3.250" C.O.L.				.283" DIA.; 24" BBL.; 3.250" C.O.L.			
SR 4759	32.0	2935	51500	IMR 3031	43.5	3310	46000	SR 4759	27.5	2260	51300	SR 4759	30.0	2445	49700
IMR 4227	30.5	2895	51700	IMR 4064	47.0	3350	45000	IMR 4227	30.0	2435	51200	IMR 4227	28.5	2375	48400
IMR 4198	37.0	3135	53000	IMR 4895	46.0	3335	45900	IMR 4198	35.5	2660	51000	IMR 4198	36.0	2680	50000
IMR 3031	48.0	3500	53000	IMR 4320	45.5	3260	45100	IMR 3031	45.5	2945	51700	IMR 3031	47.0	2975	48900
IMR 4064	49.5	3500	53000	IMR 4350	51.0C	3230	43700	IMR 4064	48.0	3030	51200	IMR 4064	50.0	3055	49700
IMR 4895	46.0	3395	53000					IMR 4895	46.0	2945	52000	IMR 4895	44.0	2745	49100
IMR 4320	49.0	3410	53000					IMR 4320	45.5	2880	51400	IMR 4320	46.5	2880	49900
IMR 4350	56.0	3495	52100					IMR 4350	55.0	3075	51100	IMR 4350	56.5	3055	48600
IMR 4831	59.0C	3560	52200					IMR 4831	56.5	3080	51200	IMR 4831	60.0C	3115	50000
								IMR 7828	60.0C	3140	52000				

RIFLE

IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)
.280 REMINGTON				.284 WINCHESTER				.30 M1 CARBINE				.300 SAVAGE			
REM. CASE; REM. 9 1/2 PR				WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 6 1/2 PR				REM. CASE; REM. 9 1/2 PR			
REM. 150 GR. PTD. SPCL				SPEER 130 GR. SPITZER				HORNADY 100 GR. SHORT JACKET				SPEER 150 GR. SPITZER			
.284" DIA.; 24" BBL.; 3.325" C.O.L.				.284" DIA.; 24" BBL.; 2.800" C.O.L.				.3085 DIA.; 18" BBL.; 1.760" C.O.L.				.308" DIA.; 24" BBL.; 2.600" C.O.L.			
SR 4759	29.5	2200	50000	SR 4759	30.0	2425	51900	SR 4759	11.0C	1575	23700	SR 4759	23.5	2095	45500
IMR 4227	27.5	2115	49500	IMR 4227	30.0	2460	52300	IMR 4227	16.0C	2005	40000	IMR 4227	24.0	2105	44800
IMR 4198	34.5	2375	49200	IMR 4198	38.0	2775	52400	IMR 4198	14.5C	1530	20700	IMR 4198	30.0	2365	44100
IMR 3031	45.5	2745	48800	IMR 3031	48.0	3055	54000					IMR 3031	38.5	2575	44500
IMR 4064	48.0	2810	50000	IMR 4064	50.0	3085	54000					IMR 4064	40.0	2565	45400
IMR 4895	42.5	2635	49300	IMR 4895	45.0	2905	52800					IMR 4895	40.0	2470	45900
IMR 4320	44.5	2655	50000	IMR 4320	46.0	2890	52300					IMR 4320	41.5	2555	46000
IMR 4350	55.0	2895	50000	IMR 4350	57.0	3130	53600					IMR 4350	44.0C	2415	39800
IMR 4831	57.0	2930	50000	IMR 4831	59.0C	3100	50600					IMR 4831	44.0C	2260	36200
.280 REMINGTON				.284 WINCHESTER				.30 M1 CARBINE				.300 SAVAGE			
REM. CASE; REM. 9 1/2 PR				WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 6 1/2 PR				REM. CASE; REM. 9 1/2 PR			
REM. 165 GR. SPCL				SPEER 160 GR. SPITZER				HORNADY 110 GR. RN				SPEER 180 GR. RN			
.284" DIA.; 24" BBL.; 3.325" C.O.L.				.284" DIA.; 24" BBL.; 2.800" C.O.L.				.308" DIA.; 18" BBL.; 1.680" C.O.L.				.308" DIA.; 24" BBL.; 2.600" C.O.L.			
SR 4759	29.0	2150	50000	SR 4759	27.5	2105	53500	SR 4759	11.0C	1545	26100	SR 4759	22.5	1910	45500
IMR 4227	27.0	2050	50000	IMR 4227	28.0	2170	52200	IMR 4227	15.0C	1900	40000	IMR 4227	23.0	1965	44800
IMR 4198	33.5	2295	49400	IMR 4198	34.5	2440	52500	IMR 4198	14.5C	1495	20900	IMR 4198	29.5	2190	45200
IMR 3031	44.5	2615	49700	IMR 3031	45.0	2660	52700					IMR 3031	37.0	2390	45900
IMR 4064	46.5	2640	48800	IMR 4064	47.0	2760	53700					IMR 4064	38.5	2395	45900
IMR 4895	42.0	2525	49400	IMR 4895	41.0	2584	53500					IMR 4895	38.5	2390	45700
IMR 4320	44.0	2550	49900	IMR 4320	43.5	2635	53900					IMR 4320	40.0	2390	46000
IMR 4350	53.5	2750	49600	IMR 4350	52.0C	2720	47700					IMR 4350	44.0C	2350	41900
IMR 4831	55.5	2775	50000	IMR 4831	52.0C	2635	43800					IMR 4831	44.0C	2240	39300
7 MM-08 REMINGTON				7 MM REMINGTON MAG.				.30-30 WINCHESTER				.308 WINCHESTER			
REM. CASE; REM 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR			
HORNADY 139 GR. SPIRE PT.				HORNADY 120 GR. SPIRE PT.				HORNADY 150 GR. RN				HORNADY 110 GR. SPIRE PT.			
.284" DIA.; 24" BBL.; 2.800" C.O.L.				.284" DIA.; 24" BBL.; 3.290" C.O.L.				.308" DIA.; 20" BBL.; 2.550" C.O.L.				.308" DIA.; 23" BBL.; 2.600" C.O.L.			
SR 4759	26.5	2270	51800	SR 4759	36.5	2695	51900	SR 4759	19.5	1840	37300	SR 4759	31.0	2710	51600
IMR 4227	25.5	2285	51800	IMR 4227	37.0	2705	51300	IMR 4227	20.0	1905	37500	IMR 4227	32.0	2835	51900
IMR 4198	32.0	2565	51500	IMR 4198	44.0	2980	51000	IMR 4198	28.0	2210	37300	IMR 4198	38.5	3015	51100
IMR 3031	40.5	2830	51900	IMR 3031	52.5	3180	51200	IMR 3031	35.5C	2370	37700	IMR 3031	45.0C	2990	42200
IMR 4064	42.5	2835	51300	IMR 4064	55.5	3245	51200	IMR 4064	37.5C	2350	37800	IMR 4064	47.0C	2955	43300
IMR 4895	40.5	2790	51000	IMR 4895	54.5	3215	52000	IMR 4895	35.5	2315	38000	IMR 4895	49.0C	3130	49200
IMR 4320	41.5	2800	50400	IMR 4320	55.5	3185	51400	IMR 4320	36.0	2240	37300	IMR 4320	49.0C	3010	49200
IMR 4350	46.0C	2750	44200	IMR 4350	65.0	3300	51400	IMR 4350	38.5C	2080	29600	IMR 4350	47.0C	2500	32000
IMR 4831	46.0C	2645	38800	IMR 4831	68.5	3335	51400	IMR 4831	38.5C	1925	24100	IMR 4831	47.0C	2330	29200
7 MM-08 REMINGTON				7 MM REMINGTON MAG.				.30-30 WINCHESTER				.308 WINCHESTER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 PR			
HORNADY 162 GR. BTHP				REM. 150 GR. PTD. SPCL				REM. 170 GR. SPCL				REM. 150 GR. PTD. SPCL			
.284" DIA.; 24" BBL.; 2.800" C.O.L.				.284" DIA.; 24" BBL.; 3.290" C.O.L.				.308" DIA.; 20" BBL.; 2.520" C.O.L.				.308" DIA.; 23" BBL.; 2.700" C.O.L.			
SR 4759	24.5	2060	51800	SR 4759	35.0	2420	51500	SR 4759	18.0	1605	37300	SR 4759	27.5	2325	51500
IMR 4227	24.0	2095	51900	IMR 4227	35.0	2455	51000	IMR 4227	19.0	1645	37700	IMR 4227	26.0	2260	51100
IMR 4198	29.5	2330	50300	IMR 4198	43.0	2705	52000	IMR 4198	24.5	1915	38000	IMR 4198	35.5	2595	51300
IMR 3031	38.0C	2585	51100	IMR 3031	51.0	2850	52000	IMR 3031	32.0	2120	37700	IMR 3031	45.0C	2831	52000
IMR 4064	39.0C	2535	46500	IMR 4064	54.0	2935	51600	IMR 4064	34.0C	2130	38000	IMR 4064	46.0C	2800	51500
IMR 4895	38.5	2595	52000	IMR 4895	52.0	2880	51500	IMR 4895	31.5	2045	38000	IMR 4895	44.5	2780	52000
IMR 4320	40.0	2625	51500	IMR 4320	54.0	2895	51300	IMR 4320	33.5	2050	37300	IMR 4320	45.0	2710	52000
IMR 4350	41.5C	2440	40800	IMR 4350	63.0	3010	51700	IMR 4350	36.5C	1935	30200	IMR 4350	46.0C	2415	36600
IMR 4831	41.5C	2355	35900	IMR 4831	66.5	3055	52000	IMR 4831	36.5C	1795	25100	IMR 4831	46.0C	2265	32600
7 MM-08 REMINGTON				7 MM REMINGTON MAG.				Velocity and pressure readings represent average values obtained under controlled conditions. The values shown may vary substantially with the components and the reloading techniques employed. We suggest the charge weights shown be reduced initially by 10% to compensate for possible variations from the published data. The loads may then be increased as pressure indications permit.							
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. M 9 1/2 PR											
SIERRA 168 GR. MATCH KING HP				REM. 175 GR. PTD. SPCL											
.284" DIA.; 24" BBL.; 2.800" C.O.L.				.284" DIA.; 24" BBL.; 3.290" C.O.L.											
SR 4759	24.0	1995	50500	SR 4759	34.0	2220	51200								
IMR 4227	23.5	2025	51400	IMR 4227	35.5	2240	51800								
IMR 4198	29.5	2290	51100	IMR 4198	41.5	2440	52000								
IMR 3031	37.0C	2515	50500	IMR 3031	47.5	2555	50700								
IMR 4064	38.0C	2475	46000	IMR 4064	51.0	2645	51500								
IMR 4895	38.0C	2535	51400	IMR 4895	50.0	2645	52000								
IMR 4320	40.0C	2590	51800	IMR 4320	50.5	2665	52000								
IMR 4350	40.0C	2365	39800	IMR 4350	59.5	2765	51800								
IMR 4831	40.0C	2255	34200	IMR 4831	63.0	2790	52000								
				IMR 7828	66.0	2910	52000								

RIFLE

IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER
POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)
.308 WINCHESTER				.30-06				.300 H & H MAG.				.300 WINCHESTER MAG.			
REM. CASE; REM. 9 1/2 PR				WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 9 1/2 M PR				WIN. CASE; WIN. 8 1/2-120 PR			
REM. 180 GR. PTD. SPCL				REM. 180 GR. PTD. SPCL				REM. 220 GR. SPCL				REM. 220 GR. SPCL			
.308" DIA.; 23" BBL.; 2.725" C.O.L.				.308" DIA.; 23" BBL.; 3.200" C.O.L.				.308" DIA.; 24" BBL.; 3.575" C.O.L.				.308" DIA.; 24" BBL.; 3.340" C.O.L.			
SR 4759	26.5	2085	51200	SR 4759	29.5	2135	50000	SR 4759	36.5	2030	54000	SR 4759	36.5	2115	52800
IMR 4227	27.0	2110	52000	IMR 4227	28.5	2045	49800	IMR 4227	35.5	2015	53600	IMR 4227	36.0	2090	54000
IMR 4198	33.5	2350	51600	IMR 4198	36.0	2350	49800	IMR 4198	42.0	2240	52600	IMR 4198	43.5	2310	53000
IMR 3031	41.5C	2550	51700	IMR 3031	44.5	2540	49800	IMR 3031	52.5	2485	53300	IMR 3031	52.5	2505	54000
IMR 4064	43.5C	2580	51700	IMR 4064	49.5	2670	49200	IMR 4064	56.5	2565	53300	IMR 4064	57.5	2575	53000
IMR 4895	42.5C	2540	50900	IMR 4895	43.5	2520	50000	IMR 4895	51.5	2465	53300	IMR 4895	53.5	2525	53500
IMR 4320	44.5C	2550	52000	IMR 4320	49.0	2595	49700	IMR 4320	54.0	2495	53000	IMR 4320	54.0	2520	53200
IMR 4350	46.0C	2365	38900	IMR 4350	57.0C	2750	49700	IMR 4350	65.0	2695	54000	IMR 4350	66.0	2690	53700
IMR 4831	46.0C	2225	36900	IMR 4831	59.0C	2700	44200	IMR 4831	67.0	2710	54000	IMR 4831	70.0C	2730	53100
												IMR 7828	70.0	2750	53000
.30-40 Krag				.30-06				.300 WINCHESTER MAG.				7.62 MM X 39			
WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				IMI CASE; CCI 200 PR			
SPEER 150 GR. SPITZER				SIERRA 200 GR. MATCH KING HP				REM. 150 GR. PTD. SPCL				SPEER 125 GR. SP; .311 DIA.			
.308" DIA.; 25.5" BBL.; 3.00" C.O.L.				.308" DIA.; 23" BBL.; 3.340" C.O.L.				.308" DIA.; 24" BBL.; 3.340" C.O.L.				20" BBL.; 2.180" C.O.L.			
SR 4759	24.5	2080	37300	SR 4759	28.5	2000	49800	SR 4759	41.5	2660	53400	IMR 4227	18.5	1995	44100
IMR 4227	23.5	2090	37700	IMR 4227	28.5	2045	50000	IMR 4227	39.5	2590	52400	IMR 4198	24.0	2250	42500
IMR 4198	30.0	2355	38100	IMR 4198	36.0	2285	48400	IMR 4198	49.0	2900	53600				
IMR 3031	42.0	2695	39500	IMR 3031	44.5	2450	49700	IMR 3031	63.0	3200	53900				
IMR 4064	44.0	2695	39000	IMR 4064	47.5	2530	49200	IMR 4064	65.5	3240	53700				
IMR 4895	36.0	2435	39700	IMR 4895	43.0	2445	49700	IMR 4895	64.0	3240	53000				
IMR 4320	37.0	2420	39700	IMR 4320	46.0	2445	48800	IMR 4320	66.5	3230	53700				
IMR 4350	48.5C	2615	36300	IMR 4350	55.0C	2635	49900	IMR 4350	76.0	3335	53900				
IMR 4831	48.5C	2430	29800	IMR 4831	58.0C	2660	49900	IMR 4831	80.0	3365	54000				
				IMR 7828	55.0C	2385	44100								
.30-40 Krag				.30-06				.300 WINCHESTER MAG.				8 X 57 MM MAUSER			
WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				WIN. CASE; WIN. 8 1/2-120 PR			
REM. 180 GR. SPCL				HORNADY 220 GR. RN				NOSLER 165 GR. SPITZER				SPEER 150 GR. SPITZER			
.308" DIA.; 25.5" BBL.; 3.00" C.O.L.				.308" DIA.; 23" BBL.; 3.185" C.O.L.				.308" DIA.; 24" BBL.; 3.340" C.O.L.				.323" DIA.; 25" BBL.; 2.945" C.O.L.			
SR 4759	24.0	1940	39100	SR 4759	27.0	1835	50000	IMR 7828	77.5	3210	53700	SR 4759	21.5	1960	37000
IMR 4227	23.0	1900	37800	IMR 4227	27.0	1850	50000					IMR 4227	22.5	2015	36700
IMR 4198	29.5	2150	39800	IMR 4198	33.0	2055	48800					IMR 4198	28.5	2225	37000
IMR 3031	38.0	2375	39300	IMR 3031	42.5	2300	49000					IMR 3031	34.5	2335	37000
IMR 4064	41.0	2435	39000	IMR 4064	46.0	2370	50000					IMR 4064	36.0	2305	37000
IMR 4895	35.5	2270	38800	IMR 4895	40.5	2230	50000					IMR 4895	36.0	2310	37000
IMR 4320	35.5	2210	38100	IMR 4320	44.0	2295	49500					IMR 4320	36.0	2270	36900
IMR 4350	46.0C	2445	38700	IMR 4350	53.5C	2470	50000					IMR 4350	43.0	2315	36800
IMR 4831	49.0C	2425	35900	IMR 4831	56.0C	2490	49500					IMR 4831	47.0	2325	36800
				IMR 7828	55.0C	2285	41900								
.30-06				.300 H & H MAG.				.300 WINCHESTER MAG.				8 x 57 MM MAUSER			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				WIN. CASE; WIN. 8 1/2-120 PR				WIN. CASE; WIN. 8 1/2-120 PR			
HORNADY 110 GR. SPIRE PT.				REM. 150 GR. PTD. SPCL				REM. 180 GR. PTD. SPCL				HORNADY 170 GR. RN			
.308" DIA.; 23" BBL.; 3.130" C.O.L.				.308" DIA.; 24" BBL.; 3.550" C.O.L.				.308" DIA.; 24" BBL.; 3.250" C.O.L.				.323" DIA.; 25" BBL.; 2.840" C.O.L.			
SR 4759	35.0	2820	49700	SR 4759	40.0	2455	53600	SR 4759	38.5	2435	53700	SR 4759	20.5	1855	37000
IMR 4227	32.0	2730	49400	IMR 4227	37.0	2515	54000	IMR 4227	37.5	2390	53400	IMR 4227	21.5	1860	36600
IMR 4198	39.5	2980	49400	IMR 4198	44.0	2715	53500	IMR 4198	47.0	2690	54000	IMR 4198	27.54	2075	37000
IMR 3031	56.0	3365	49300	IMR 3031	60.0	3100	51000	IMR 3031	58.5	2900	53700	IMR 3031	32.5	2105	36100
IMR 4064	58.0C	3320	49400	IMR 4064	64.0	3170	53800	IMR 4064	62.5	2995	53800	IMR 4064	35.0	2175	36900
IMR 4895	54.5	3265	49300	IMR 4895	55.0	2960	54000	IMR 4895	59.5	2950	53900	IMR 4895	33.5	2145	37000
IMR 4320	57.5	3255	49100	IMR 4320	58.0	2970	53700	IMR 4320	60.5	2920	53700	IMR 4320	34.5	2105	36200
IMR 4350	59.0C	2960	36900	IMR 4350	73.0	3215	53600	IMR 4350	71.5	3100	54000	IMR 4350	42.0	2180	37000
IMR 4831	59.0C	2780	32500	IMR 4831	75.5C	3200	53100	IMR 4831	75.5C	3105	53700	IMR 4831	46.0	2255	37000
								IMR 7828	74.0	3050	53900				
.30-06				.300 H & H MAG.				.300 WINCHESTER MAG.				8 MM REMINGTON MAG.			
REM. CASE; REM. 9 1/2 PR				REM. CASE; REM. 9 1/2 M PR				WIN. CASE; WIN. 8 1/2-120 PR				REM. CASE; REM. 9 1/2 M PR			
REM. 150 GR. PTD. SPCL				REM. 180 GR. PTD. SPCL				SIERRA 200 GR. SPITZER BT				REM. 185 GR. PSPCL			
.308" DIA.; 23" BBL.; 3.200" C.O.L.				.308" DIA.; 24" BBL.; 3.520" C.O.L.				.308" DIA.; 24" BBL.; 3.340" C.O.L.				.323" DIA.; 24" BBL.; 3.560" C.O.L.			
SR 4759	31.0	2365	49700	SR 4759	38.0	2330	54000	IMR 7828	71.0	2900	53800	SR 4759	45.0	2480	52600
IMR 4227	30.0	2310	50000	IMR 4227	36.0	2300	54000					IMR 4227	42.5	2420	54000
IMR 4198	38.0	2600	50000	IMR 4198	43.0	2515	53000					IMR 4198	51.0	2660	52800
IMR 3031	49.5	2850	49800	IMR 3031	57.0	2815	53400					IMR 3031	62.5	2895	53100
IMR 4064	52.0	2885	50000	IMR 4064	60.0	2875	53400					IMR 4064	66.5	2975	54000
IMR 4895	49.5	2845	50000	IMR 4895	54.5	2760	53800					IMR 4895	61.0	2855	53300
IMR 4320	51.0	2825	50000	IMR 4320	57.5	2795	53800					IMR 4320	62.0	2850	53000
IMR 4350	59.0C	2825	47800	IMR 4350	69.0	2990	54000					IMR 4350	77.5	3090	53100
IMR 4831	59.0C	2715	42900	IMR 4831	73.0C	3035	53500					IMR 4831	79.5	3095	52900

RIFLE

IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER
POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)	POWDER	(grains)	(ft/sec)	PRESS. (cup)

8 MM REMINGTON MAG.

REM. CASE; REM. 9 1/2 M PR REM. 220 GR. PSPCL			
.323" DIA.; 24" BBL.; 3.560" C.O.L.			
SR 4759	42.0	2180	54000
IMR 4227	39.5	2185	51700
IMR 4198	47.5	2400	53300
IMR 3031	59.0	2620	53000
IMR 4064	62.5	2700	53800
IMR 4895	59.0	2615	51300
IMR 4320	59.5	2595	51200
IMR 4350	72.0	2795	53000
IMR 4831	76.0	2745	53800

.338 WINCHESTER MAG.

WIN. CASE; WIN 8 1/2-120 PR WIN. 200 GR. POWDER PT. SP			
.338" DIA.; 25" BBL.; 3.330" C.O.L.			
SR 4759	39.5	2335	54000
IMR 4227	38.0	2300	53500
IMR 4198	47.5	2565	53500
IMR 3031	61.0	2860	54000
IMR 4064	64.0	2920	54000
IMR 4895	61.0	2880	53700
IMR 4320	63.0	2875	54000
IMR 4350	73.0	3030	53900
IMR 4831	76.0C	3020	51000

.338 WINCHESTER MAG.

REM. CASE; REM. 9 1/2 M PR NOSLER 250 GR. SPITZER			
.338" DIA.; 24" BBL.; 3.340" C.O.L.			
IMR 7828	74.0C	2565	44400

.338 WINCHESTER MAG.

REM. CASE; REM. 9 1/2 M PR SPEER 275 GR. SPITZER			
.338" DIA.; 24" BBL.; 3.340" C.O.L.			
IMR 7828	71.0C	2430	43400

.338 WINCHESTER MAG.

WIN. CASE; WIN 8 1/2-120 PR WIN. 300 GR. POWER PT. SP			
.338" DIA.; 25" BBL.; 3.330" C.O.L.			
SR 4759	34.5	1795	54000
IMR 4227	34.0	1800	53600
IMR 4198	42.5	2050	53500
IMR 3031	53.5	2260	53800
IMR 4064	56.0	2305	53800
IMR 4895	52.5	2265	54000
IMR 4320	54.5	2275	53700
IMR 4350	64.5	2410	53800
IMR 4831	68.5C	2480	54000

.357 MAGNUM (RIFLE)

REM. CASE; REM. 5 1/2 PR HORNADY 125 GR. HP			
.357" DIA.; 18.5" BBL.; 1.590" C.O.L.			
"Hi-Skor"			
700-X	6.7	1455	35700
PB	7.2	1435	34600
SR 7625	7.4	1460	35300
SR 4756	9.2	1615	35800
IMR 4227	20.0X	1935	34100

.357 MAGNUM (RIFLE)

REM. CASE; REM. 5 1/2 PR HORNADY 158 GR. HP			
.357" DIA.; 18.5" BBL.; 1.590" C.O.L.			
"Hi-Skor"			
700-X	5.7	1185	35200
PB	6.0	1160	35600
SR 7625	6.5	1215	36000
SR 4756	8.0	1340	36000
IMR 4227	16.3C	1605	34900

.35 REMINGTON

REM. CASE; REM. 9 1/2 PR REM. 150 GR. PT. SPCL			
.358" DIA.; 23" BBL.; 2.500" C.O.L.			
SR 4759	23.0	1985	35000
IMR 4227	22.0	1935	33600
IMR 4198	29.0	2190	35000
IMR 3031	42.0C	2390	34200
IMR 4064	43.0C	2390	34200
IMR 4895	43.0C	2340	34600
IMR 4320	42.5	2295	34700
IMR 4350	43.5C	1985	24100
IMR 4831	43.5C	1850	21300

.35 REMINGTON

REM. CASE; REM. 9 1/2 PR HORNADY 200 GR. RN			
.358" DIA.; 23" BBL.; 2.500" C.O.L.			
SR 4759	20.5	1770	35000
IMR 4227	21.0	1760	35000
IMR 4198	27.0	1915	33500
IMR 3031	37.5	2110	34700
IMR 4064	39.5C	2080	34200
IMR 4895	36.5	2030	3490
IMR 4320	38.5	2020	35000
IMR 4350	43.0C	1915	29200
IMR 4831	43.0C	1780	25900

.358 WINCHESTER

WIN. CASE; WIN. 8 1/2-120 PR WEST. 200 GR. SILVER TIP			
.358" DIA.; 25" BBL.; 2.765" C.O.L.			
SR 4759	29.5	2170	52000
IMR 4227	28.5	2130	50800
IMR 4198	40.0	2495	52000
IMR 3031	49.0C	2630	51800
IMR 4064	49.0C	2525	46200
IMR 4895	49.0C	2565	50800
IMR 4320	51.0C	3656	62800
IMR 4350	51.0C	2270	37600
IMR 4831	51.0C	2115	32300

.358 WINCHESTER

WIN. CASE; WIN. 8 1/2-120 PR WEST. 250 GR. SILVER TIP			
.358" DIA.; 25" BBL.; 2.780" C.O.L.			
SR 4759	26.0	1845	51400
IMR 4227	26.5	1860	52000
IMR 4198	32.5	2045	51700
IMR 3031	42.0	2260	50800
IMR 4064	44.0C	2270	52000
IMR 4895	43.0	2235	51200
IMR 4320	44.5	2210	51400
IMR 4350	47.0C	2115	41700
IMR 4831	47.0C	1975	37100

.35 WHELEN

REM. CASE; REM. 9 1/2 PR REM. 200 GR. PSP			
.358" DIA.; 24" BBL.; 3.075" C.O.L.			
SR 4759	34.5	2265	51400
IMR 4227	36.5	2290	51500
IMR 4198	46.0	2595	51900
IMR 3031	55.0C	2650	49000
IMR 4064	58.0C	2700	50000
IMR 4895	58.0C	2655	49400
IMR 4320	58.0C	2640	51000
IMR 4350	60.0C	2345	39100

.35 WHELEN

REM. CASE; REM. 9 1/2 PR HORNADY 250 GR. R.N.			
.358" DIA.; 24" BBL.; 3.240" C.O.L.			
SR 4759	32.5	1975	50600
IMR 4227	35.0	2015	51600
IMR 4198	43.0	2295	50000
IMR 3031	53.0C	2480	51800
IMR 4064	55.5C	2505	51900
IMR 4895	55.0C	2475	51600
IMR 4320	55.0C	2475	51300
IMR 4350	58.0C	2265	41200

.375 H & H MAG.

WIN. CASE; WIN. 8 1/2-120 PR REM. 270 GR. SP			
.375" DIA.; 25" BBL.; 3.600" C.O.L.			
SR 4759	41.5	2085	53000
IMR 4227	39.5	2070	53000
IMR 4198	49.0	2300	53000
IMR 3031	65.5	2610	53000
IMR 4064	69.0	2655	52500
IMR 4895	65.0	2565	53000
IMR 4320	66.5	2545	52000
IMR 4350	78.5C	2710	53000
IMR 4831	82.5C	2690	50700

.375 H & H MAG.

WIN. CASE; WIN. 8 1/2-120 PR WIN. 300 GR. SILVER TIP			
.375" DIA.; 25" BBL.; 3.600" C.O.L.			
SR 4759	39.0	1925	53000
IMR 4227	38.05	1935	52600
IMR 4198	47.0	2145	53000
IMR 3031	63.0	2465	52500
IMR 4064	67.0	2525	52500
IMR 4895	61.0	2400	52800
IMR 4320	63.0	2405	53000
IMR 4350	78.0C	2620	52700
IMR 4831	80.0C	2560	48300

.416 REMINGTON MAGNUM

REM. CASE; REM. 9 1/2 M PR SWIFT 350 GR SSSP,			
.416" DIA.; 24" BBL.; 3.545" C.O.L.			
IMR 3031	76.5	2450	53000
IMR 4064	81.0	2485	51600
IMR 4895	77.0	2425	53700

.416 REMINGTON MAGNUM

REM. CASE; REM. 9 1/2 M PR HORNADY 400 GR. FMJ,			
.416" DIA.; 24" BBL.; 3.555" C.O.L.			
IMR 3031	75.0	2315	52100
IMR 4064	78.0	2335	52000
IMR 4895	76.5	2325	53800

.44 REMINGTON MAG.

REM. CASE; REM. 2 1/2 PR REM. 240 GR. SP			
.430" DIA.; 22" BBL.; 1.610" C.O.L.			
SR 4759	21.0C	1630	38500
IMR 4227	23.5C	1680	39500
IMR 4198	25.5C	1515	26400
IMR 3031	27.0C	1190	18900
IMR 4064	27.5C	1145	16600
IMR 4895	28.0C	1225	18300
IMR 4320	28.5C	1200	20900
IMR 4350	27.0C	850	13900
IMR 4831	27.0C	720	12500

.444 MARLIN

REM. CASE; REM. 9 1/2 PR REM. 240 GR. SP			
.430" DIA.; 25" BBL.; 2.570" C.O.L.			
SR 4759	33.0	2055	43600
IMR 4227	32.5	2030	44000
IMR 4198	47.0	2335	44000
IMR 3031	54.5C	2175	35900
IMR 4064	54.5C	2055	32200
IMR 4895	56.0C	2200	38600
IMR 4320	56.0C	2125	37500
IMR 4350	55.5C	1775	24200

.45-70 GOVT.

WIN. CASE; WIN. 8 1/2-120 PR WIN. 405 GR. SP			
.457" DIA.; 25" BBL.; 2.550" C.O.L.			
SR 4759	29.0	1500	26900
IMR 4227	30.0	1465	26500
IMR 4198	38.0	1620	27400
IMR 3031	51.45	1795	27000
IMR 4064	55.0C	1780	26700
IMR 4895	52.5	1785	26900
IMR 4320	53.5	1720	27300
IMR 4350	56.0C	1555	20000
IMR 4831	56.0C	1390	17800

*Note - These loads must not be used in any trapdoor single shot rifle.

.458 WINCHESTER MAG.

WIN. CASE; WIN. 8 1/2-120 PR WIN. 510 GR. SP			
.457" DIA.; 25" BBL.; 3.340" C.O.L.			
SR 4759	44.5	1645	52400
IMR 4227	45.0	1665	52700
IMR 4198	58.0	1925	52500
IMR 3031	69.0C	2030	43900
IMR 4064	71.0C	2020	41300
IMR 4895	72.5	2100	53000
IMR 4320	74.0C	2070	51500
IMR 4350	72.0C	1810	30300
IMR 4831	72.0C	1680	24900

Velocity and pressure readings represent average values obtained under controlled conditions. The values shown may vary substantially with the components and the reloading techniques employed. We suggest the charge weights shown be reduced initially by 10% to compensate for possible variations from the published data. The loads may then be increased as pressure indications permit.

IMR 7828

WEATHERBY CARTRIDGES RELOADING DATA

CALIBER	PRIMER	BULLET	CARTRIDGE OVERALL LENGTH (IN.)	IMR POWDER	POWDER CHARGE GRAINS	VELOCITY FT/SEC	CHAMBER PRESSURE (CUP)
.240 Weatherby Magnum	Fed. 210	Hornady 70 gr. Spire Point	3.063	IMR 7828	56.0C	3505	47500
		Hornady 87 gr. Spire Point	3.063	IMR-7828	54.5C	3360	50700
		Nosler 100 gr. Spitzer	3.063	IMR-7828	53.5C	3240	52000
.257 Weatherby Magnum	Fed. 215	Hornady 87 gr. Spire Point	3.170	IMR-7828	74.5	3775	53500
		Nosler 100 gr. Spitzer	3.160	IMR-7828	73.0	3655	53100
		Hornady 117 gr. Boat Tail Spire Pt.	3.170	IMR-7828	70.0	3390	52600
		Nosler 120 gr. Spitzer	3.170	IMR-7828	69.0	3325	53000
.270 Weatherby Magnum	Fed. 215	Hornady 100 gr. Spire Point	3.250	IMR-7828	78.5C	3645	48200
		Nosler 130 gr. Spitzer	3.250	IMR-7828	76.0	3500	53000
		Hornady 140 gr. Boat Tail Spire Pt.	3.295	IMR-7828	73.5	3325	53000
		Nosler 150 gr. Spitzer	3.250	IMR-7828	72.0	3215	53600
7mm Weatherby Magnum	Fed. 215	Hornady 139 gr. Flat Spire Point	3.068	IMR-7828	76.0C	3335	51500
		Nosler 140 gr. Spitzer	3.250	IMR-7828	76.5C	3390	53300
		Hornady 154 gr. Spire Point	3.337	IMR-7828	74.5	3250	53400
		Nosler 160 gr. Spitzer	3.337	IMR-7828	73.5	3210	53500
		Hornady 175 gr. Spire Point	3.360	IMR-7828	70.5	2975	53000
.300 Weatherby Magnum	Fed. 215	Nosler 150 gr. Spitzer	3.560	IMR-7828	89.0C	3425	49900
		Nosler 180 gr. Spitzer	3.560	IMR-7828	86.0C	3240	52500
		Nosler 200 gr. Spitzer	3.560	IMR-7828	83.0C	3065	50600
		Hornady 220 gr. Round Nose	3.560	IMR-7828	81.0	2940	52400
.340 Weatherby Magnum	Fed. 215	Nosler 210 gr. Spitzer	3.608	IMR-7828	90.5C	3070	51600
		Hornady 225 gr. Spire Point	3.645	IMR-7828	89.0C	2965	51000
		Hornady 250 gr. Round Nose	3.658	IMR-7828	87.5C	2860	53100
.378 Weatherby Magnum	Fed. 215	Speer 285 gr. Grand Slam	3.625	IMR-7828	117.0C	3060	51600
		Hornady 300 gr. Round Nose	3.644	IMR-7828	118.0C	3055	53500
.460 Weatherby Magnum	Fed. 215	Hornady 500 gr. Round Nose	3.720	IMR-7828	117.0C	2360	41900

Notes:

- Brass—Weatherby Factory Shells
- C = Compressed Load
- Barrel Length—26 inch
- All Nosler bullets used were partition type
- Recommended using only primer shown for each load

RIFLE DATA SHOWING CHAMBER PRESSURE IN PSI

IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER	IMR	CHARGE	VELOCITY	CHAMBER
POWDER	(grains)	(ft/sec)	PRESS. (psi)	POWDER	(grains)	(ft/sec)	PRESS. (psi)	POWDER	(grains)	(ft/sec)	PRESS. (psi)	POWDER	(grains)	(ft/sec)	PRESS. (psi)
243 WINCHESTER				25-06 REMINGTON				260 REMINGTON				260 REMINGTON			
WIN. CASE; FED. 210 PR				REM. CASE; FED. 210 PR				REM. CASE; WIN. WLR PR				REM. CASE; WIN. WLR PR			
NOSLER 55 GR. BALLISTIC TIP				NOSLER 115 GR. BALLISTIC TIP				SIERRA 120 GR. SPITZER				REM. 140 GR. PSPCL			
.243" DIA.; 24" BBL.; 2.580" C.O.L.				.257" DIA.; 24" BBL.; 3.175" C.O.L.				.264" DIA.; 24" BBL.; 2.780" C.O.L.				.264" DIA.; 24" BBL.; 2.780" C.O.L.			
IMR 4064	44.0	3900	56000	IMR 7828	55.5	3040	57000	SR 4759	17.0	1755	37500	SR 4759	18.0	1735	39800
243 WINCHESTER				260 REMINGTON				SR 4759	23.5	2280	57600	SR 4759	23.0	2135	56500
WIN. CASE; FED. 210 PR				REM. CASE; WIN. WLR PR				IMR 3031	34.0	2720	57600	IMR 3031	32.5	2505	56200
BARNES 85 GR. XBTLC				SIERRA 100 GR. HOLLOW PT.				IMR 4064	37.0	2805	57700	IMR 4064	36.0	2615	56900
.243" DIA.; 24" BBL.; 2.670" C.O.L.				.264" DIA.; 24" BBL.; 2.700" C.O.L.				IMR 4895	36.0	2770	57100	IMR 4895	35.5	2605	57600
IMR 4350	45.0	3170	55000	IMR 3031	35.5	2995	57100	IMR 4320	37.5	2805	58400	IMR 4320	36.0	2600	57600
IMR 4831	46.0	3170	54000	IMR 4064	39.5	3095	57000	IMR 4350	43.0	2885	58000	IMR 4350	43.0	2715	57000
243 WINCHESTER				IMR 4895	38.0	3045	57300	IMR4831	44.0	2885	58400	IMR 4831	44.0	2715	57000
WIN. CASE; FED. 210 PR				IMR 4320	39.0	3040	57300	IMR 7828	47.0C	2895	57800	IMR 7828	47.0C	2755	57200
HORNADY 100 GR. SP				IMR 4350	45.0	3120	57500	260 REMINGTON				260 REMINGTON			
.243" DIA.; 24" BBL.; 2.670" C.O.L.				IMR 4831	46.5	3130	58300	REM. CASE; WIN. WLR PR				REM. CASE; WIN. WLR PR			
IMR 4350	38.2	2850	56000	IMR 7828	49.0C	3025	53300	HORNADY 129 GR. SPIRE PT.				HORNADY 160 GR. RN			
25-06 REMINGTON				25-06 REMINGTON				.264" DIA.; 24" BBL.; 2.780" C.O.L.				.264" DIA.; 24" BBL.; 2.800" C.O.L.			
REM. CASE; FED. 210 PR				REM. CASE; FED. 210 PR				IMR 3031	33.0	2590	56800	IMR 4350	40.5	2520	57400
BARNES 115 GR. X				BARNES 115 GR. X				IMR 4064	36.5	2690	58300	IMR 4831	41.5	2520	57200
.257" DIA.; 24" BBL.; 3.175" C.O.L.				.257" DIA.; 24" BBL.; 3.175" C.O.L.				IMR 4895	36.5	2725	58100	IMR 7828	45.0	2580	58100
IMR 7828	51.5	2900	57000	IMR 7828	51.5	2900	57000	IMR 4320	36.5	2685	58600				
								IMR 4350	41.5	2765	57300				
								IMR4831	43.0	2785	58300				
								IMR 7828	45.0	2775	57200				

RIFLE

IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS.(psi)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS.(psi)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS.(psi)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS.(psi)
270 WINCHESTER				7 MM SHOOTING TIMES WESTERNER				30-06 SPRG				REM 300 ULTRA MAG			
REM. CASE; FED. 210 PR SIERRA 140 GR. HPBT				REM. CASE; FED. 215 PR SWIFT 160 GR. A-FRAME				REM. CASE; FED. 210 PR SIERRA 180 GR. SPITZER BT				REM. CASE; FED. 215 PR NOSLER 180 GR. PARTITION			
.277" DIA.; 24" BBL.; 3.252" C.O.L.				.284" DIA.; 24" BBL.; 3.600" C.O.L.				.308" DIA.; 24" BBL.; 3.325" C.O.L.				.308" DIA.; 24" BBL.; 3.600" C.O.L.			
IMR 4831 55.0 2980 62000				IMR 4350 66.5 2995 62000				IMR 4064 46.0 2600 55000				IMR 7828 87.0 3140 61000			
IMR 7828 56.5 2860 55000				IMR 4831 68.5 3010 62400				IMR 4350 54.3 2670 55000							
				IMR 7828 76.0 3110 62300				IMR 4831 55.8 2700 57000							
								IMR 4831 55.3 2670 56000							
7MM REMINGTON MAG				308 WINCHESTER				300 WINCHESTER MAG				REM 300 ULTRA MAG			
REM. CASE; FED. 215 PR BARNES 140 GR. XBTLC				REM. CASE; FED. 210 PR NOSLER 150 GR. BALLISTIC TIP				WIN. CASE; FED. 215 PR NOSLER 165 GR. PARTITION				REM. CASE; FED. 215 PR NOSLER 200 GR. PARTITION			
.284" DIA.; 24" BBL.; 3.270" C.O.L.				.308" DIA.; 24" BBL.; 2.755" C.O.L.				.308" DIA.; 24" BBL.; 3.330" C.O.L.				.308" DIA.; 24" BBL.; 3.600" C.O.L.			
IMR 4350 65.3 3060 58000				IMR 3031 41.5 2750 57000				IMR 4350 71.5 3110 61000				IMR 7828 85.8 2990 61000			
IMR 4831 66.5 3040 56000								IMR 4831 73.0 3100 61000							
IMR 7828 72.3c 3100 58000								IMR 7828 79.3 3110 60000							
7MM REMINGTON MAG				308 WINCHESTER				300 WINCHESTER MAG				338 WINCHESTER MAG			
REM. CASE; FED. 215 PR NOSLER 150 GR. BALLISTIC TIP				REM. CASE; FED. 210 PR BARNES 165 GR. X				WIN. CASE; FED. 215 PR SIERRA 165 GR. HPBT				WIN. CASE; FED. 215 PR NOSLER 210 GR. PARTITION			
.284" DIA.; 24" BBL.; 3.290" C.O.L.				.308" DIA.; 24" BBL.; 2.800" C.O.L.				.308" DIA.; 24" BBL.; 3.330" C.O.L.				.338" DIA.; 24" BBL.; 3.300" C.O.L.			
IMR 4350 60.6 2940 56000				IMR 4064 42.5 2600 58000				IMR 4350 70.5 3080 59000				IMR 4350 68.7 2830 60000			
IMR 4831 63.2 2960 57000								IMR 4831 73.2 3100 61000				IMR 4831 72.0 2860 60000			
IMR 7828 68.2 3000 57000								IMR 7828 78.8 3110 60000				IMR 7828 75.0c 2790 56000			
7MM REMINGTON MAG				308 WINCHESTER				300 WINCHESTER MAG				338 WINCHESTER MAG			
REM. CASE; FED. 215 PR SWIFT 150 GR. SCIROCCO				REM. CASE; FED. 210 PR NOSLER 165 GR. BALLISTIC TIP				WIN. CASE; FED. 215 PR SIERRA 165 GR. HPBT				WIN. CASE; FED. 215 PR NOSLER 250 GR. PARTITION			
.284" DIA.; 24" BBL.; 3.270" C.O.L.				.308" DIA.; 24" BBL.; 2.755" C.O.L.				.308" DIA.; 24" BBL.; 3.330" C.O.L.				.338" DIA.; 24" BBL.; 3.325" C.O.L.			
IMR 4350 58.8 2930 56000				IMR 4064 43.0c 2640 57000				IMR 4350 70.5 3080 59000				IMR 4350 65.2 2560 60000			
IMR 4831 62.0 2940 57000								IMR 4831 73.2 3100 61000				IMR 4831 67.0 2570 61000			
IMR 7828 67.1 2980 56000								IMR 7828 77.0c 2930 56000				IMR 7828 71.0c 2590 59000			
7MM REMINGTON MAG				308 WINCHESTER				300 WINCHESTER MAG				338 WINCHESTER MAG			
REM. CASE; FED. 215 PR NOSLER 160 GR. PARTITION				REM. CASE; FED. 210 PR SIERRA 165 GR. HPBT				WIN. CASE; FED. 215 PR NOSLER 180 GR. PARTITION				WIN. CASE; FED. 215 PR SWIFT 250 GR. A-FRAME			
.284" DIA.; 24" BBL.; 3.290" C.O.L.				.308" DIA.; 24" BBL.; 2.755" C.O.L.				.308" DIA.; 24" BBL.; 3.330" C.O.L.				.338" DIA.; 24" BBL.; 3.300" C.O.L.			
IMR 4350 58.7 2880 57000				IMR 4064 42.5 2640 57000				IMR 4350 69.0 2970 61000				IMR 4350 65.0 2560 60000			
IMR 4831 60.2 2860 56000								IMR 4831 71.5 2950 59000				IMR 4831 66.8 2550 60000			
IMR 7828 66.0 2940 57000								IMR 7828 77.0c 2930 56000				IMR 7828 71.5c 2590 59000			
7MM REMINGTON MAG				30-06 SPRG				300 WINCHESTER MAG				45-70 GOVT			
REM. CASE; FED. 215 PR SWIFT 160 GR. A-FRAME				REM. CASE; FED. 210 PR NOSLER 150 GR. BALLISTIC TIP				WIN. CASE; FED. 215 PR SWIFT 180 GR. A-FRAME				FED. CASE; FED. 210 PR HORNADY 300 GR. HP			
.284" DIA.; 24" BBL.; 3.250" C.O.L.				.308" DIA.; 24" BBL.; 3.300" C.O.L.				.308" DIA.; 24" BBL.; 3.310" C.O.L.				.458" DIA.; 2.540" C.O.L.			
IMR 7828 66.5 2940 59000				IMR 4350 59.0c 2960 57000				IMR 4350 70.0 2970 58000				IMR 4198 41.2 1900 27000			
								IMR 4831 71.5 2950 59000				IMR 3031 54.0 1960 28000			
								IMR 7828 77.0c 2930 56000							
7MM REMINGTON MAG				30-06 SPRG				300 WINCHESTER MAG				45-70 GOVT			
REM. CASE; FED. 215 PR SWIFT 160 GR. A-FRAME				REM. CASE; FED. 210 PR NOSLER 165 GR. BALLISTIC TIP				WIN. CASE; FED. 215 PR SWIFT 180 GR. SCIROCCO				FED. CASE; FED. 210 PR NOSLER 300 GR. FN PARTITION			
.284" DIA.; 24" BBL.; 3.250" C.O.L.				.308" DIA.; 24" BBL.; 3.335" C.O.L.				.308" DIA.; 24" BBL.; 3.340" C.O.L.				.458" DIA.; 2.500" C.O.L.			
IMR 7828 66.5 2940 59000				IMR 4831 56.0 2760 56000				IMR 4350 67.8 2930 60000				IMR 4198 41.2 1880 28000			
								IMR 4831 69.7 2930 60000				IMR 3031 51.5 1890 27000			
								IMR 7828 74.5 2880 56000							
7 MM SHOOTING TIMES WESTERNER				30-06 SPRG				REM 300 ULTRA MAG				45-70 GOVT			
REM. CASE; FED. 215 PR BARNES 120 GR. XFB				REM. CASE; FED. 210 PR SIERRA 165 GR. HPBT				REM. CASE; FED. 215 PR BARNES GR. 165 XSP				FED. CASE; FED. 210 PR SIERRA 300 GR. FN HP			
.284" DIA.; 24" BBL.; 3.580" C.O.L.				.308" DIA.; 24" BBL.; 3.215" C.O.L.				.308" DIA.; 24" BBL.; 3.600" C.O.L.				.458" DIA.; 2.530" C.O.L.			
IMR 4350 73.0 3460 63000				IMR 4350 54.0 2760 55000				IMR 7828 89.0 3200 61000				IMR 4198 43.0 1940 26000			
IMR 4831 74.0 3445 63400												IMR 3031 55.2 2010 28000			
IMR 7828 80.0 3495 62900															
7 MM SHOOTING TIMES WESTERNER				30-06 SPRG				REM 300 ULTRA MAG				45-70 GOVT			
REM. CASE; FED. 215 PR NOSLER 140 GR. BALLISTIC TIP				REM. CASE; FED. 210 PR SWIFT 165 GR. A-FRAME				REM. CASE; FED. 215 PR SWIFT 165 GR. A-FRAME				FED. CASE; FED. 210 PR SIERRA 300 GR. FN PARTITION			
.284" DIA.; 24" BBL.; 3.580" C.O.L.				.308" DIA.; 24" BBL.; 3.205" C.O.L.				.308" DIA.; 24" BBL.; 3.550" C.O.L.				.458" DIA.; 2.500" C.O.L.			
IMR 4350 71.5 3285 62700				IMR 4350 56.0 2790 55000											

*Note - These loads must not be used in any trapdoor single shot rifle.

HANDGUN

IMR				CHARGE				VELOCITY				CHAMBER				IMR				CHARGE				VELOCITY				CHAMBER				IMR				CHARGE				VELOCITY				CHAMBER																			
POWDER		(grains)		(ft/sec)		PRESS. (cup)		POWDER		(grains)		(ft/sec)		PRESS. (cup)		POWDER		(grains)		(ft/sec)		PRESS. (cup)		POWDER		(grains)		(ft/sec)		PRESS. (cup)		POWDER		(grains)		(ft/sec)		PRESS. (psi)																									
.357 MAGNUM																.38 SPECIAL																.38 SPECIAL																10 MM AUTO															
REM. CASE; REM. 5 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 2 1/2 PR															
REM. 158 GR. SJHP; .357" DIA.;																SPEER 140 GR. JHP; .357" DIA.;																HORNADY 158 GR. JFP; .357" DIA.;																REM. 155 GR. JHP; .400" DIA.															
6.0" REVOLVER BBL.; 1.580" C.O.L.																6.0" REVOLVER BBL.; 1.455" C.O.L.																6.0" REVOLVER BBL.; 1.465" C.O.L.																5.0" BBL.; 1.250" C.O.L.															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
700-X 5.2 885 35800																700-X 3.7 730 15900																700-X 3.4 585 15300																700-X 6.4 1220 34300															
PB 5.7 875 36000																PB 4.2 735 15700																PB 3.9 620 16000																PB 7.2 1235 35000															
IMR 7625 6.2 855 35700																SR 7625 4.6 480 15800																SR 7625 4.3 660 15700																SR 7625 7.8 1275 34300															
SR 4756 7.5 940 35700																SR 4756 5.6 765 16000																SR 4756 5.2 705 15300																SR 4756 8.5 1310 34400															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
800-X 8.6 1080 35400																800-X 6.0 830 15700																800-X 5.5 695 15400																800-X 9.8 1350 30000															
IMR 4227 15.3C 1075 36000																IMR 4227 10.3 800 15600																IMR 4227 9.7 705 15900																															
.357 MAGNUM																.38 SPECIAL																.38 SPECIAL																10 MM AUTO															
REM. CASE; REM 5 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 2 1/2 PR															
SIERRA 170 GR. SILHOUETTE FMJ;																SPEER 146 GR. JHP; .357" DIA.;																REM. 158 GR. LEAD RN; .358" DIA.;																WIN. 180 GR. JHP; .400 DIA.															
.357" DIA.; 6.0" REVOLVER BBL.;																6.0" REVOLVER BBL.; 1.395" C.O.L.																6.0" REVOLVER BBL.; 1.520" C.O.L.																5.0" BBL.; 1.250" C.O.L.															
1.580" C.O.L.																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
"Hi-Skor"																700-X 3.5 725 15900																700-X 3.0 740 11700																700-X 6.0 1105 34400															
700-X 4.8 795 35600																PB 3.9 725 15700																"Hi-Skor"																PB 6.4 1105 34900															
PB 5.1 785 35600																SR 7625 4.2 740 15600																700-X 3.6 790 15800																SR 7625 7.0 1140 35100															
SR 7625 5.6 815 35600																SR 4756 5.2 840 15600																PB 3.4 745 11700																SR 4756 7.6 1155 34400															
SR 4756 7.1 885 35600																"Hi-Skor"																PB 4.0 775 15500																"Hi-Skor"															
"Hi-Skor"																800-X 5.8 805 15400																SR 7625 3.7 745 10000																800-X 8.7 1210 30000															
800-X 8.3 1030 35500																IMR 4227 10.3 880 15700																SR 7625 4.3 790 15200																															
IMR 4227 13.7 985 35500																																"Hi-Skor"																															
																																800-X 4.8 750 11500																															
																"Hi-Skor"																800-X 5.7 875 16000																															
																800-X 5.2 825 15800																SR 4756 5.2 825 15800																															
																IMR 4227 9.5 825 15700																IMR 4227 9.5 825 15700																															
.357 MAGNUM																.38 SPECIAL																.38 SPECIAL																10 MM AUTO															
REM. CASE; REM. 5 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 2 1/2 PR															
REM. 200 GR. LEAD RN; .358" DIA.;																SPEER 148 GR. LEAD BBWC;																REM. 158 GR. LEAD SWC; .358" DIA.;																HORNADY 200 GR. HP/XTP; .400 DIA.															
6.0" REVOLVER BBL.; 1.590" C.O.L.																.358" DIA.; 6.0" REVOLVER BBL.;																6.0" REVOLVER BBL.; 1.550" C.O.L.																5.0" BBL.; 1.250" C.O.L.															
1.295" C.O.L.																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
"Hi-Skor"																700-X 2.6 710 87000																700-X 3.2 745 13100																700-X 6.2 1210 32900															
700-X 4.3 795 35800																"Hi-Skor"																700-X 3.5 790 15400																700-X 6.2 1210 32900															
PB 4.6 780 35700																700-X 3.5 850 16000																"Hi-Skor"																PB 7.5 1230 31000															
SR 7625 5.1 795 35700																PB 2.8 705 8400																700-X 3.6 750 12200																PB 7.5 1230 31000															
SR 4756 6.2 885 35900																PB 3.8 855 15800																PB 4.0 800 15800																SR 7625 7.8 1250 30200															
"Hi-Skor"																SR 7625 3.2 715 8200																SR 7625 3.8 750 11000																SR 4756 9.0 1285 30000															
800-X 7.5 995 36000																SR 7625 4.2 845 16000																SR 7625 4.5 790 16000																"Hi-Skor"															
IMR 4227 12.5 955 35500																"Hi-Skor"																800-X 5.0 750 11600																800-X 10.5 1305 24000															
																800-X 4.3 710 8600																"Hi-Skor"																															
																"Hi-Skor"																800-X 5.9 880 16000																															
																800-X 5.5 905 15900																800-X 5.7 875 16000																															
																SR 4756 5.2 905 16000																SR 4756 5.4 840 45900																															
																IMR 4227 11.4 945 16000																IMR 4227 9.7 825 15700																															
.38 SPECIAL																.38 SPECIAL																.38 SPECIAL																40 S & W															
REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																WIN. CASE; WIN WSP PR															
REM. 95 GR. SJHP; .357" DIA.;																REM. 148 GR. LEAD WC; .358" DIA.;																REM. 158 GR. LEAD SWC; .358" DIA.;																NOSLER 135 GR. HP; .400" DIA.															
6.0" REVOLVER BBL.; 1.470" C.O.L.																6.0" REVOLVER BBL.; 1.225" C.O.L.																6.0" REVOLVER BBL.; 1.500" C.O.L.																4.0" PISTOL BBL.; 1.125" C.O.L.															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
700-X 4.6 1025 15600																700-X 2.4 715 8800																700-X 3.5 790 15400																700-X 6.2 1210 32900															
PB 5.1 1055 15600																PB 2.7 710 7900																PB 3.6 750 12200																PB 7.5 1230 31000															
SR 7625 5.6 1065 15700																SR 7625 2.9 700 6900																SR 7625 3.8 750 11000																SR 7625 7.8 1250 30200															
SR 4756 6.5 1080 15900																"Hi-Skor"																SR 7625 4.5 790 16000																SR 4756 9.0 1285 30000															
"Hi-Skor"																800-X 4.0 705 9400																"Hi-Skor"																"Hi-Skor"															
800-X 7.8 1195 15700																																800-X 5.0 750 11600																800-X 10.5 1305 24000															
IMR 4227 11.9 1090 15900																																"Hi-Skor"																															
																																800-X 5.9 880 16000																															
																800-X 5.4 840 45900																800-X 5.7 875 16000																															
																IMR 4227 9.7 825 15700																IMR 4227 9.7 825 15700																															
.38 SPECIAL																.38 SPECIAL																.38 SPECIAL																40 S & W															
REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																WIN. CASE; WIN WSP PR															
HORNADY 110 GR. HP; .357" DIA.;																REM. 148 GR. LEAD WC; .358" DIA.;																REM. 200 GR. LEAD RN; .358" DIA.;																HORNADY 180 GR. HP/XTP; .400" DIA.															
6.0" REVOLVER BBL.; 1.460" C.O.L.																6.0" REVOLVER BBL.; 1.225" C.O.L.																6.0" REVOLVER BBL.; 1.500" C.O.L.																4.0" PISTOL BBL.; 1.125" C.O.L.															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
700-X 4.2 970 15400																700-X 2.4 715 8800																700-X 3.5 790 15400																700-X 6.2 1210 32900															
PB 4.8 990 15200																PB 2.7 710 7900																PB 3.6 750 12200																PB 7.5 1230 31000															
SR 7625 5.5 1060 15400																SR 7625 2.9 700 6900																SR 7625 3.8 750 11000																SR 7625 7.8 1250 30200															
SR 4756 6.2 1040 15600																"Hi-Skor"																SR 7625 4.5 790 16000																SR 4756 9.0 1285 30000															
"Hi-Skor"																800-X 4.0 705 9400																"Hi-Skor"																"Hi-Skor"															
800-X 7.2 1095 15800																																800-X 5.0 750 11600																800-X 10.5 1305 24000															
IMR 4227 11.1 1020 15800																																"Hi-Skor"																															
																																800-X 5.9 880 16000																															
																800-X 5.4 840 45900																800-X 5.7 875 16000																															
																IMR 4227 9.7 825 15700																IMR 4227 9.7 825 15700																															
.38 SPECIAL																.38 SPECIAL																.38 SPECIAL																40 S & W															
REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																REM. CASE; REM. 1 1/2 PR																WIN. CASE; WIN WSP PR															
REM. 125 GR. SJHP; .357" DIA.;																SIERRA 150 GR. JHC; .357" DIA.;																REM. 200 GR. LEAD RN; .358" DIA.;																HORNADY 180 GR. HP/XTP; .400" DIA.															
6.0" REVOLVER BBL.; 1.525" C.O.L.																6.0" REVOLVER BBL.; 1.445" C.O.L.																6.0" REVOLVER BBL.; 1.500" C.O.L.																4.0" PISTOL BBL.; 1.125" C.O.L.															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
700-X 4.1 840 15600																700-X 3.5 755 15900																700-X 3.0 725 15000																700-X 4.3 840 33800															
PB 4.6 865 15500																PB 4.0 765 15900																PB 3.4 760 15800																PB 4.5 845 33900															
SR 7625 5.3 935 15900																SR 7625 4.3 770 15700																SR 7625 3.5 755 15800																SR 7625 5.2 885 34100															
SR 4756 6.1 925 15900																SR 4756 5.4 765 16000																SR 4756 4.3 740 15700																SR 4756 5.6 905 34200															
"Hi-Skor"																"Hi-Skor"																"Hi-Skor"																"Hi-Skor"															
800-X 6.9 980 15500																800-X 5.7 795 15600																800-X 4.6 725 15500																800-X 6.3 925 26100															
IMR 4227 10.8 930 16000																IMR 4227 10.0 770 15900																IMR 4227 9.2 870 15900																															

55

HANDGUN

IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)	IMR POWDER	CHARGE (grains)	VELOCITY (ft/sec)	CHAMBER PRESS. (cup)
7 MM BR REMINGTON				9 MM LUGER				.25 A.C.P.				380 A.C.P.			
REM. CASE; BR (URBR) FORMED IN RECBS DIES; REM. BR 7 1/2 PR HORNADY 162 GR. HPBT; .284" DIA.; 15" BBL.; 2.375" C.O.L.				REM. CASE; CCI 500 PR. REM. 124 GR. MC; .354" DIA.; 4.0" PISTOL BBL.; 1.125" C.O.L.				REM. CASE; CCI 500 PR HORNADY 50 GR. FMJ; .251" DIA.; 2.0" PISTOL BBL.; .900" C.O.L.				REM. CASE; CCI 500 PR. HORNADY 100 GR. FMJ; .355" DIA.; 3.75" PISTOL BBL.; .980" C.O.L.			
IMR 4198	22.5	2000	50600	"Hi-Skor"				"Hi-Skor"				"Hi-Skor"			
IMR 3031	26.0C	2015	4400	700-X	4.8	1110	32600	700-X	1.1	740	14400	700-X	2.7	840	15200
IMR 4064	26.0C	1870	38600	PB	4.9C	1050	32500	PB	1.1	740	17700	PB	2.8	835	15400
IMR 4895	27.0C	2015	48000	SR 7625	4.9	1040	32300	SR 7625	1.2	755	17900	SR 7625	3.0	855	15500
				SR 4756	6.3C	1160	32400	SR 4756	1.4	770	16900	SR 4756	3.5	875	15900
				"Hi-Skor"				"Hi-Skor"				"Hi-Skor"			
				800-X	6.5C	1115	28600	800-X	1.8	815	17800	800-X	4.0	840	14700
				IMR 4227	8.8C	790	13200								
9 MM LUGER				9 MM LUGER				380 A.C.P.				38 A.C.P.			
REM. CASE; REM. 1 1/2 PR. REM. 115 GR. JHP; .354" DIA.; 4.0" PISTOL BBL.; 1.110" C.O.L.				REM. CASE; FED. 100 PR HORNADY 147 GR. BTHP/XTP .355" DIA.; 4.0" PISTOL BBL.; 1.130" C.O.L.				REM. CASE; REM. 1 1/2 PR. HORNADY 90 GR. HP; .355" DIA.; 3.75" PISTOL BBL.; .970" C.O.L.				REM. NICKEL CASE; CCI 500 PR. HORNADY 115 GR. HP; .357" DIA.; 5.0" PISTOL BBL.; 1.265" C.O.L.			
"Hi-Skor"				"Hi-Skor"				"Hi-Skor"				"Hi-Skor"			
700-X	4.7	1130	32600	700-X	3.7	935	32100	700-X	2.9	985	15900	700-X	4.0	955	22900
PB	4.8	1075	32500	PB	4.0	950	32800	PB	3.0	890	15700	PB	4.0	955	22500
SR 7625	5.1	1095	32400	SR 7625	4.3	950	32900	SR 7625	3.2	880	14700	SR 7625	4.5	955	21800
SR 4756	6.3C	1175	30600	SR 4756	4.4	950	32700	SR 4756	3.6	880	15500	SR 4756	5.2	965	21800
"Hi-Skor"				"Hi-Skor"				"Hi-Skor"				"Hi-Skor"			
800-X	6.5	1150	30300	800-X	5.3	1025	32900	800-X	4.1	870	15500	800-X	5.9	1015	21900
IMR 4227	8.8C	820	14500												

THOMPSON/CENTER CONTENDER RELOADING DATA (ALL DATA DEVELOPED IN T/C CONTENDER COMMERCIAL BARRELS)

KEY TO ABBREVIATIONS FOR T/C CONTENDER DATA

BR	Bench Rest	FMJ	Full Metal Jacket	PSP	Pointed Soft Point
BR PR	Bench Rest Primer	FP	Flat Point	SPCL	Soft Point "Cole-Lokt"
BT	Boat Tail	HP	Hollow Point	T/C	Thompson Center
C	Compressed Charge	J	Jacketed		
C.O.L.	Cartridge Overall Length				

BULLET WT.	DIA.	IMR POWDER	CHARGE (GRAINS)	VELOCITY (FT/SEC) 10" BARREL	14" BARREL	CHAMBER PRESSURE (CUP)	CARTRIDGE OVERALL LENGTH (IN.)
.222 REMINGTON—REM. CASE, REM. 7 1/2 BR PR							
45 GR.	.224"	IMR 4227	17.1	2500	-	45200	2.130"
SIERRA SPITZER		IMR 4198	21.1	2640	-	45800	
		IMR 4895	24.2C	2380	-	37400	
50 GR.	.224"	IMR 4227	16.1	2365	-	45800	2.130"
REMINGTON PSP		IMR 4198	20.0	2510	-	45600	
		IMR 4895	24.2C	2365	-	39300	
52 GR.	.224"	IMR 4227	15.8	2300	-	45600	2.190"
SIERRA HPBT BR		IMR 4198	19.8	2455	-	45800	
		IMR 4895	23.8C	2325	-	40500	
55 GR.	.224"	IMR 4198	19.0	2375	-	45200	2.085"
SPEER FMJ		IMR 3031	21.5C	2225	-	37800	
		IMR 4895	23.0C	2275	-	41200	
60 GR.	.224"	IMR 4227	14.7	2105	-	45000	2.245"
HORNADY HP		IMR 4198	19.1	2330	-	45800	
		IMR 4895	23.0C	2235	-	42400	
70 GR.	.224"	IMR 4198	17.9	2145	-	45700	2.060"
SPEER		IMR 3031	20.5C	2000	-	34900	
SEMI-SPITZER		IMR 4895	21.5C	2050	-	37900	

THOMPSON/CENTER CONTENDER RELOADING DATA

(ALL DATA DEVELOPED IN T/C CONTENDER COMMERCIAL BARRELS)

BULLET		IMR POWDER	CHARGE (GRAINS	VELOCITY (FT/SEC)		CHAMBER PRESSURE (CUP)	CARTRIDGE OVERALL LENGTH (IN.)
WT.	DIA.			10" BARREL	14" BARREL		
.25/.35 WINCHESTER—REM. CASE, FED. 210 BR PR							
60 GR.	.257"	IMR 3031	28.3	2325	-	36900	2.390"
SPEER SPIRE POINT		IMR 4064	30.5C	2285	-	36000	
87 GR.	.257"	IMR 3031	23.4	1965	-	36800	2.690"
HORNADY SPIRE POINT		IMR 4064	25.7	1960	-	36500	
100 GR.	.257"	IMR 3031	22.1	1845	-	36500	2.700"
SPEER SPITZER		IMR 4064	25.2	1875	-	37000	
		IMR 4350	31.0C	1900	-	36400	
117 GR.	.257"	IMR 3031	21.5	1760	-	36700	2.700"
SIERRA		IMR 4895	22.2	1750	-	37000	
SPITZER BT		IMR 4350	28.3C	1760	-	35900	
.30 HERRETT—REM. (FORMED BY T/C), CASE, FED. 210 BR PR							
110 GR.	.308"	IMR 4227	18.8	1910	2035	44600	2.020"
HORNADY FMJ		IMR 4198	24.3	2075	2210	44600	
		IMR 3031	28.0C	1940	2070	36000	
130 GR.	.308"	IMR 4227	18.0	1775	1885	44800	2.175"
HORNADY		IMR 4198	22.5	1895	2015	44400	
SPIRE POINT		IMR 3031	26.0C	1765	1875	36300	
150 GR.	.308"	IMR 4198	21.3	1760	1870	44200	2.300"
SIERRA SPITZER		IMR 3031	25.2C	1680	1785	36700	
		IMR 4895	27.0C	1735	1845	40700	
170 GR.	.308"	IMR 4198	19.2	1575	1670	44600	2.165"
REMINGTON SPCL		IMR 3031	24.5C	1590	1690	37800	
		IMR 4895	26.0C	1625	1725	41200	
.30/.30 WINCHESTER—REM. CASE, FED. 210 BR PR							
110 GR.	.308"	IMR 3031	36.0C	2110	34000	2..450"	
HORNADY FMJ		IMR 4895	34.6	2080	2235	37800	
		IMR 4064	36.5C	2020	2170	33200	
130 GR.	.308"	IMR 3031	36.0C	2025	2175	37000	2.725"
HORNADY SPIRE POINT		IMR 4064	36.5C	1965	2110	36500	
150 GR.	.308"	IMR 3031	33.0	1895	2035	37500	2.855"
SIERRA SPITZER		IMR 4064	34.4	1855	1995	37400	
170 GR.	.308"	IMR 3031	27.4	1660	1780	37600	2.700"
REMINGTON SPECIAL		IMR 4064	32.8	1750	1875	37900	2.700"

Velocity and pressure readings represent average values obtained under controlled conditions. The values shown may vary substantially with the components and the reloading techniques employed. We suggest the charge weights shown be reduced initially by 10% to compensate for possible variations from the published data. The loads may then be increased as pressure indications permit.

THOMPSON/CENTER CONTENDER RELOADING DATA

(ALL DATA DEVELOPED IN T/C CONTENDER COMMERCIAL BARRELS)

BULLET		IMR POWDER	CHARGE (GRAINS	VELOCITY (FT/SEC)		CHAMBER PRESSURE (CUP)	CARTRIDGE OVERALL LENGTH (IN.)
WT.	DIA.			10" BARREL	14" BARREL		
.357 HERRETT—WIN. (FORMED BY T/C) CASE, FED. 210 BR PR							
110 GR.	.357"	SR 4759	24.5C	1950	2070	35600	2.080"
HORNADY JHP		IMR 4227	23.8	2095	2225	44500	
		IMR 4198	32.0C	2070	2200	33900	
125 GR.	.357"	SR 4759	24.0C	1880	1990	38400	2.080"
HORNADY JHP		IMR 4227	22.3	1995	2070	44900	
		IMR 4198	31.0C	2015	2135	38100	
158 GR.	.357"	SR 4759	23.0C	1705	1810	42000	2.150"
HORNADY JFP		IMR 4227	20.2	1710	1815	44900	
		IMR 4198	29.9C	1925	2045	44900	
170 GR.	.357"	SR 4759	23.0C	1655	1750	41400	2.230"
SIERRA FMJ SILHOUETTE		IMR 4227	20.1	1640	1735	45000	
		IMR 4198	30.0C	1835	1940	44600	
200 GR.	.358"	SR 4759	23.0C	1575	1675	44100	2.540"
HORNADY SPIRE POINT		IMR 4198	28.2	1715	1820	45000	
		IMR 3031	31.0C	1540	1635	32400	
		IMR 4895	34.0C	1605	1705	38300	
.35 REMINGTON—REM. CASE, FED. 210 BR PR							
158 GR.	.357"	IMR 3031	38.4c	-	2030	34500	2.300"
HORNADY JFP		IMR 3895	37.8	-	1975	34700	
		IMR 4064	39.5C	-	1925	32600	
170 GR.	.357"	IMR 3031	38.5C	-	1985	33700	2.405"
SIERRA FMJ SILHOUETTE		IMR 4895	37.8	-	1920	34100	
		IMR 4064	38.1	-	1850	35000	
250 GR.	.358"	IMR 3031	31.0	-	1620	35000	2.800"
SPEER SPITZER		IMR 4064	33.0	-	1610	34800	

IMR HANDLOADING POWDER SELECTION GUIDE

The following table lists the IMR Handloading Powders and the general area of use for each powder. Whenever a specific powder appears in more than one section of this Guide (for example, shotshell and handgun), the same powder can be used for all recommended loads shown with this powder. Powders can be used in case bullet rifle loads as specified in reliable published loading data.

POWDER DESIGNATION	SHOTSHELL (GAUGE)						CONTAINER NET WEIGHT LBS.		
							CANISTER	CADDY	KEG
	10	12	16	20	28	410			
"HI-SKOR" 700-X	x	x	x	x			1/2	5	12
"HI-SKOR" 800-X	x	x	x	x	x		1/2	5	12
PB	x	x	x	x	x		1/2	5	12
SR 7625	x	x	x	x	x		1/2	5	12
SR 4756	x	x	x	x	x		1/2	5	12
SR 4759							1/2	5	12
IMR 4227						x	1	8	20
IMR 4198						x	1	8	20
IMR 3031						x	1	8	20
IMR 4064						x	1	8	20
IMR 4895						x	1	8	20
IMR 4320						x	1	8	20
IMR 4350						x	1	8	20
IMR 4831							1	8	20
IMR 7828							1	8	20

IMR

SMOKELESS POWDER DISTRIBUTORS

Camfour, Inc.

Westfield Industrial Park
Westfield, MA 01085-1693
Phone: (413) 568-3371
Fax: (413) 568-9663
Email: sales@camfour.com
Website: <http://www.camfour.com>

W. A. Murphy, Inc.

P.O. Box 4607
El Monte, CA 91734-0607
Phone: (626) 444-9271
Fax: (626) 575-2848
Website: www.murphypowder.com
E-mail: reloadit@murphypowder.com

Dole Explosives Inc.

Box 71
Rosemount, MN 55068
Phone: (651) 423-1141
Fax: (651) 322-6168
Email: dolepowder@aol.com

Western Powders, Inc.

"Formerly Roundup Powder Co."
P.O. Box 158
Miles City, MT 59301
Phone: (406) 232-0422
1-800-497-1007
Fax: (406) 232-0430
Website: www.westernpowder.com

Hall Explosives, Inc.

RR 1, Box 148B
Hershey, PA 17033
Phone: (717) 533-6565
Fax: (717) 533-6716
Terryreigle@aol.com

(CANADA)

Hummason Mfg. Ltd.

P.O. Box 81047
623 Trinity Road
Ancaster, Ont. L9G 4X1
Phone: (905) 648-3430
Fax: (905) 648-4616

The information presented in this booklet is based upon results obtained in our ballistics laboratory, and is offered without charge as an aid to handloaders, to be employed at their own discretion and risk. Safe loading practices should be observed at all times. Since we have no control over the circumstances of loading, we assume no liability for the results obtained, and we guarantee only that powder meets our manufacturing standards.

IMR POWDER COMPANY
PLATTSBURGH, NY 12901

Website: www.imrpowder.com

